MEASUREMENTS GROUP -- TYPE 361A-20R SOLDER -- 3439-00-064-2017 Product ID:TYPE 361A-20R SOLDER MSDS Date:01/01/1985 FSC:3439 NIIN:00-064-2017 MSDS Number: BCWYS === Responsible Party === Company Name: MEASUREMENTS GROUP Emergency Phone Num:919-365-3800 CAGE:88952 === Contractor Identification === Company Name: MEASUREMENTS GROUP INC Address:9517 US 64 HWY Box:City:WENDELL State:NC ZIP:27591 Country:US Phone:919-365-3800 CAGE:88 952 ======= Composition/Information on Ingredients ======== Ingred Name:TIN CAS:7440-31-5

RTECS #:XP7320000 Fraction by Wt: 63% OSHA PEL:2 MG/M3 ACGIH TLV:2 MG/M3; 9192

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS #: OF7525000 Fraction by Wt: 36.6%

OSHA PEL:0.05 MG/M3;1910.1025 ACGIH TLV:0.15 MG/M3;DUST 9192

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: ANTIMONY (SARA III)

CAS:7440-36-0

RTECS #:CC4025000 Fraction by Wt: 0.35% OSHA PEL:0.5 MG/M3

ACGIH TLV:0.5 MG SB/M3; 9192

Fraction by Wt: 3.4%
Ingred Name:ALIPHATIC ALCOHOL Fraction by Wt: 0.18%
============= Hazards Identification ===============
Effects of Overexposure:FLUX: CAN CAUSE IRRITATION OF SKIN & MUCOUS MEMBRANE.
======================================
First Aid:REMOVE VICTIM FROM CONTAMINATED AREA & KEEP EWARM & QUIET IN FRESH AIR.
======================================
Flash Point:261F,127C COC Extinguishing Media:FLUX:CO*2,DRY CHEMICAL Unusual Fire/Explosion Hazard:IN A FIRE MATERIAL COULD EMIT TOXIC & CORROSIVE FUMES.
========= Accidental Release Measures ===========
Spill Release Procedures:FLUX MAY BE WIPED FROM A SURFACE WITH ISOPROPYL ALCOHOL & A SPONGE.
======================================
Handling and Storage Precautions: USE WITH ADEQUATE LOCAL VENTILATION, STORE BELOW 100F, 38C.
====== Exposure Controls/Personal Protection ========
Ventilation:LOCAL EXHAUST Supplemental Safety and Health ADDTNL INGRED:10017650H ORGANIC HALIDE 0.04%. FL PT IS FOR FLUX. MELTING PT:361F,183C. DIMENSIONS:0.063 INCHES DIAMETER; 1 LB. SPOOL. FED SPEC:QQ-S-571E.
========= Physical/Chemical Properties ===========
HCC:N1 Appearance and Odor:ALLOY:DULL SILVER. FLUX:AMBER. WIRE W/ROSIN CORE.
========= Stability and Reactivity D

PA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS
Hazardous Decomposition Products: MAY EVOLVE ACIDS, HALOGENS, AMINES.

Waste Disposal Methods: IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS.

======= Disposal Considerations ===========

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

ata =========

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.