View NSN Online: https://aerobasegroup.jp/nsn/6810-00-097-4159

Product ID:HEPTANE MSDS Date:01/01/1987 FSC:6810 NIIN:00-097-4159 MSDS Number: BCYNF === Responsible Party === Company Name: MALLINCKRODT INC., SCIENCE PRODUCTS DIVISION Address: PARIS BYPASS Box:M City:PARIS State:KY ZIP:40361 Country:US Info Phone Num:314-982-5000 **Emergency Phone Num:314-98** 2-5000 CAGE:62910 === Contractor Identification === Company Name: MALLINCKRODT SPECIALTY CHEMICALS CO Address:222 RED SCHOOL LANE Box:City:PHILLIPSBURG State:NJ ZIP:08865 Country:US Phone:908-859-2151 CAGE:62910 Ingred Name:N-HEPTANE CAS:142-82-5 RTECS #:MI7700000 Fraction by Wt: >99% OSHA PEL:500 PPM/500 STEL ACGIH TLV:400 PPM/500STEL;9293

Effects of Overe

## xposure:INH:MAY IRRIT RESP TRACT.CAUSES HEADACHE,DIZZ,NAUSEA;ING:SYMP LIKE INH;SKIN/EYES:VAP/LIQ IRRITANT.

First Aid:INHAL:RMV TO FRESH AIR.IF NEEDED, GIVE CPR/OXYGEN.GET MD;INGEST: GIVE SEVRL GL OF WATER. DO NOT INDUCE VOMITG. IMMED GET MD;SKIN:FLUSH W/LG QTY OF H\*20 FOR 15 MIN.REMV CONTMNTD CLOTHES.GET MD:EYES: IMMED F LUSH W/PLENTY OF H\*20 FOR AT LEAST 15 MIN.GET MD. Flash Point Method:CC Flash Point:=-3.7C, 25.F Autoignition Temp:=215.C, 419.F Lower Limits:1.05 Upper Limits:6.7 Extinguishing Media: DRY CHEMICALS, FOAM, CO\*2; WATER SPRAY TO KEEP EXPSD CANS COOL Fire Fighting Procedures: USE H\*20 TO COOL EXPD CONTRS. USE SCBA & FULL PROT.CLTHG. Unusual Fire/Explosion Hazard: ABOVE FLASH POINT, VAP-AIR MIXTURES ARE EXPLOSIVE.A DANGEROUS EXPLOSION HAZARD WHEN HEATED. 

====

Spill Release Procedures:RMV IGN SOURCES.VENT AREA.USE RESP PROTCTION & PROTCTV CLOTHG.KEEP OUT OF SURF H\*20,SEWRS/CONFND AREAS;SM SPILL:ABSORB W/PAPER TOWELS.EVAP UNDER FUME HOOD THEN BURN CAREFULLY;LG SPILL:DIKE AREA.CONTAI N & RECOVER SPILL IF POSS;SHOVL RESDUE INTO DRUMS.

Handling and Storage Precautions:PROTCT AGAINST PHYSICAL DAMAGE.STORE IN COOL,DRY WELL VNTLTD AREA AWAY FM IGN/HEAT SOURCES,OXI DZG

MATL.OUTSIDE OR DETACHED STORAGE IS PREFERRED. Other Precautions:KEEP AWAY FROM HEAT,SPARKS,FLAMES.KEEP CONTNRS CLOSED.USE W/ADEQUATE VENT.AVOID BRTHG VAPS.WASH THOROUGHLY AFTER HNDLG.BOND/GROUND CONTNRS WHEN TRNSFRG MATERL.USE NON-SPARKG TYPE TOOL & EQUIP.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:FULL FACE RESPIRATOR Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV. Protective Gloves:IMPERVIOUS Eye Protection:SAFETY/CHEM GOGGL ES Other Protective Equipment: FULL PROTECTIVE CLOTHING, SAFETY SHOWER, EYE WASH STATION Supplemental Safety and Health MSDS FROM MFR DATED 30 JUL, 85 CONFORMS TO OSHA HAZ COMM STD. HCC:F2 NRC/State Lic Num:NOT RELEVANT Boiling Pt:=98.3C, 209.F Vapor Pres:40 Vapor Density:3.5 Spec Gravity:0.683 Appearance and Odor: COLORLESS LIQ.MILD GASOLINE-LIKE ODOR. Sta bility Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:HEAT, IGNITION SOURCES Hazardous Decomposition Products:CO, CO\*2 WHEN HEATED TO DECOMPOSITION Waste Disposal Methods: LG SPILL & LOT SIZES OF HAZ WASTE CAN BE ATOMIZED IN A RCRA APPRVD COMBUSTION CHAMBER OR DISPOSED OF IN A RCRA APPROVED LAND FILL FACILITY.DO NOT FLUSH TO SEWER.ENSURE COMPLIANCE W/FED, STATE & LOCAL R EGS; R EPORTABLE QTY (RQ)

(CWA/CERCLA): NOT KNOWN

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.