View NSN Online: https://aerobasegroup.jp/nsn/3040-00-204-3295

EATON CORP, OPERNS & TECHNICAL CENTER -- 48-338-6 -- 6110-00-204-3295

Product ID:48-338-6 MSDS Date:01/01/1985

FSC:6110

NIIN:00-204-3295

MSDS Number: BDJMC === Responsible Party ===

Company Name: EATON CORP, OPERNS & TECHNICAL CENTER

Address:4201 N 27TH ST

City:MILWAUKEE

State:WI

ZIP:53216-1807 Country:US

Emergency Phone Num:804-279-4371

CAGE:KO601 === Contractor Id entification ===

Company Name: EATON CORP OPERATIONS AND TECHNICAL CTR

Address:4201 N 27TH ST Box:City:MILWAUKEE

State:WI

ZIP:53216-1807 Country:US

Phone:414-449-6000

CAGE:15605

Company Name: EATON CORP, OPERNS & TECHNICAL CENTER

Address:4201 N 27TH ST Box:City:MILWAUKEE

State:WI

ZIP:53216-1807 Country:US CAGE:KO601

======= Composition/Information on Ingredients ========

Ingred Name: ASBESTOS (AMIANTHUS, OBSOLETE AMOSITE), (FOR OSHA PEL, SEE 29CFR 1910.1101)

CAS:1332-21-4

RTECS #:

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB ========== Hazards Identification =============== Effects of Overexposure: ASBESTOS DUST IS KNOWN HUMAN CARCINOGEN. ALSO COUGH, SHORT OF BREATH, WEAKNESS, CYANOSIS, ETC. First Aid:SKIN:CONSULT DOCTOR FOR DERMATITIS.EYES:FLUSH WITH WATER FOLLOWED BY TREATMENTS OF OPHTHALMOLOGIST.INHALATION:CONSULT **PHYSIC** IAN AT ONCE. ============= Fire Fighting Measures ======================== Extinguishing Media: EXTINQUISH W. AGENT SUITABLE FOR SURROUNDING FIRE. Fire Fighting Procedures: WEAR SELF-CNTND BRTHG APP ========= Accidental Release Measures ================ Spill Release Procedures: PICK UP MATERIAL & RETURN TO CONTAINER. IF ANY BROKEN MATERIAL EXISTS, BE CAREFUL TO AVOID DUSTING CONDITIONS.PLACE BROKEN MATERIAL INTO A SEALED CONTAINER. VACUUM OR WET CLEAN ONLY.DO NOT D RY SWEEP. ============= Handling and Storage ========================== Handling and Storage Precautions: AVOID CUTTING OR GRINDING ON ITEM.AVOID ANY DUSTING CONDITIONS.MAINTAIN GOOD HOUSEKEEPING. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: NIOSH APPROVED DUST MASK AS A MINIMUM. SELF CONT APP FOR DUSTING COND Ventilation: PROVIDE GOOD LOCAL VENTILATION TO KEEP BELOW PEL Protective Gloves: WORKING GLOVES Eye Protection: SAFETY GLASSES

CI6475000

Ot

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:0.5 FIBERS/CC; A1;89

SAFETY DATA DEVELOPED BY DGSC-STF.STORAGE CODE BASED ON FACT THAT ASBESTOS IS BOUND UP & NOT LOOSE.
========= Physical/Chemical Properties ==========
HCC:Z1 Appearance and Odor:ASBESTOS FIBERS IN BOUND FORM IN FRICTION LINING.
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES NONE KNOWN Haz
ardous Decomposition Products:NONE KNOWN
======= Disposal Considerations ==========
Waste Disposal Methods:PLACE IN SEALED PLASTIC BAG OR CONTAINER ULTIMATE DISPOSAL MUST COMPLY WITH ALL LOCAL STATE &

her Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR

PROLONGED CONTACT.
Supplemental Safety and Health

FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.