View NSN Online: https://aerobasegroup.jp/nsn/9150-00-235-5568

NONFLUID OIL CORP. -- VV-G-671 (GREASE, GRAPHITE) -- 9150-00-235-5568

Product ID:VV-G-671 (GREASE, GRAPHITE)

MSDS Date:12/01/1986

FSC:9150

NIIN:00-235-5568

MSDS Number: BDLPM === Responsible Party ===

Company Name: NONFLUID OIL CORP.

Address:298 DELANCY ST

City:NEWARK

State:NJ ZIP:07105 Country:US

Info Phone Num:(201)344-3451

Emergency Phone Num:(201)344-3451

CAGE:7 6736

=== Contractor Identification ===

Company Name: NONFLUID OIL CORP/NFO TECHNOLOGIES, INC

Address:298 DELANCY ST

City:NEWARK

State:NJ

ZIP:07105-3009

Country:US

Phone:201-344-3451/800-424-9300(CHEMTREC)

CAGE:76736

======= Composition/Information on Ingredients ========

Ingred Name: NON-HAZARDOUS COMPONENTS (PER MSDS) SEE INGREDIENTS #2,3 AND

4 AS GIVEN IN CTDF

Other REC Limits:5MG/CUM AS OIL MIST

Ingred Name: CALCIUM SOAP (USED AS THICKENER)

Ingred Name: GRAPHITE, NATURAL

CAS:7

782-42-5 RTECS #:MD9659600 **OSHA PEL:15 MPPCF RDUST** ACGIH TLV:2 MG/M3 RDUST; 9293 Ingred Name: MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST') CAS:8012-95-1 RTECS #:PY8030000 Other REC Limits:5MG/CUM AS OILMIST OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3/10 STEL;9192 ========== Hazards Identification ================ Health Hazards Acute and Chronic: AS WITH ALL PETROLEUM PRODUCTS, PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE MILD IRRITATION, DEFATTING ON SKIN IS POSSIBLE, EXPOSUR E TO FUMES OR MISTS MAY CAUSE MUCOUS MEMBRANE IRRITATION. Effects of Overexposure: MILD IRRITATION OF SKIN AND MUCOUS MEMBRANE. First Aid:EYE:FLUSH WITH LARGE AMOUNTS OF WATER AND SEE A DOCTOR; SKIN: WIPE OFF AND WASH WITH SOAP AND WATER; INHALATION: REMOVE TO FRESH AIR; INGESTION: GIVE WATER & SEEK MEDICAL AID. ============ Fire Fighting Measures ========================= Flash Point Method:COC Flash Point:410F ,210C Lower Limits:1 **Upper Limits:6** Extinguishing Media:CO\*2,DRY CHEMICAL,FOAM AND WATER FOG (CAREFULLY TO PREVENT FROTHING) Fire Fighting Procedures: WEAR SCBA WITH FACE SHIELD IN ENCLOSED AREAS. Unusual Fire/Explosion Hazard:NONE ========= Accidental Release Measures ============ Spill Release Procedures: STOP FLOW. ELIMINATE IGNITION SOURCES. RECOVER FREE PRODUCT. ADD ABSORBENT MATERIAL SUCH AS CLAY TO SPILL AREA.

SWEEP OR SCRAPE UP.

====== Handli

ations =========

Waste Disposal Methods:DISPOSE OF IAW FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.