SOUTHWEST PETRO-CHEM DIV WITCO CHEMICAL CORP -- XP-400 RUST INHIBITED POLISH -- 8030-00-244-1294

Product ID:XP-400 RUST INHIBITED POLISH MSDS Date:01/01/1985 FSC:8030 NIIN:00-244-1294 MSDS Number: BDMZY === Responsible Party === Company Name: SOUTHWEST PETRO-CHEM DIV WITCO CHEMICAL CORP Address:1400 S HARRISON Box:1974 City:OLATHE (FORMALLY IN OVERLAND PARK) State:KS ZIP:66061 Country:US Info Phone Num:913-782-5800 Emergency P hone Num:913-782-5800/800-424-9300(CHEMTREC) CAGE:70878 === Contractor Identification === Company Name: EXXON CO USA-SOUTHWEST GREASE BUSINESS UNIT Address:1400 S HARRISON Box:1974 **City:OLATHE** State:KS ZIP:66061 Country:US Phone:913-656-3701/800-424-9300(CHEMTREC) CAGE:70878 Ingred Name:STODDARD SOLVENT CAS:8052-41-3

CAS:8052-41-3 RTECS #:WJ8925000 OSHA PEL:500 PPM ACGIH TLV:100 PPM; 9293

===== Hazards Identification ====

Effects of Overexposure:IRRIT	TO EYES/SKIN.	MAY PRODUCE DIZZ	, HDACHES,
NAUSEA.			

First Aid:EYES: FLUSH W/LG AMT WATER 15 MIN, CALL MD IMMED. SKIN: WASH W/SOAP & WATER. INH: IF OVERCOME BY VAPORS, REMOVE FROM CONTAM AREA. CALL MD IMMED. INGEST: CALL MD IMMED.

Flash Point:38C, 101F PMCC Lower Limits:1.1 Upper Limits:6.1 Extinguis hing Media:DRY CHEM, CO*2, WATER FOG, FOAM, SAND, EARTH Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR SELF-CNTND BRTHNG APPARATUS Unusual Fire/Explosion Hazard:DENSE SMOKE

Spill Release Procedures: VENT AREA, UTILIZING PROPER PERSONAL PROT EQUIP, TRANSFER BULK OF MATL INTO ANOTHER CNTNR. ABSORB REMAINING RESIDUE W/PROPER ABSORBENTS. SWEEP UP & DISPOSE OF AS SOLID WASTE IAW LOCAL, STATE, FED REG.

Handling and Storage Precautions: KEEP CNTNRS CLOSED Other Precautions: KEEP OUT OF REACH OF CHILDREN

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NIOSH/MSHA APPRVD SELF-CNTND BRTHNG APPARATUS OR RESP Ventilation:ANY SUFFICIENT TO KEEP BELOW TLV

Protective Gloves:RUBBER/PLASTIC Eye Protection:SPLSH GOGGL&/OR FACE SHL Supplemental Safety and Health CHEMICAL AND PHYSICAL DATA BASED ON STODD ARD SOLVENT MFR'S CODE 18879. PRODUCT IS GRADE 3

HCC:F4 Boiling Pt:B.P. Text:149C, 300F Vapor Density:4.8 Spec Gravity:0.791 Evaporation Rate & amp; Reference:41 ETHYL ETHER Solubility in Water:NEGLIGIBLE Appearance and Odor:AMBER LIQ, STODDARD SLVNT Percent Volatiles by Volume:50.

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS SUCH A S CHROMIC ACID,BROMINE&H*2O*2 Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE

Waste Disposal Methods: BY METHODS CONSISTENT W/LOCAL, STATE, FED REG

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.