View NSN Online: https://aerobasegroup.jp/nsn/8010-00-290-1180

REICHHOLD CHEMICALS, INC. -- S.D. WOOD TURPENTINE -- 8010-00-290-1180

Product ID:S.D. WOOD TURPENTINE MSDS Date:01/01/1985 FSC:8010 NIIN:00-290-1180 MSDS Number: BDVCQ === Responsible Party === Company Name: REICHHOLD CHEMICALS, INC. Address:NINE OHIO RIVER BLVD City:SEWICKLEY State:PA ZIP:15143-2199 Country:US CAGE:DO591 === Contractor Identification === Company Name:NU-BRITE CHEMICAL CO INC, STERLING GROUP Address:NINE OHIO RIVER BLVD Box:City:SEWICKLEY State:PA ZIP:15143-2199 Country:US Phone:CHEMTREC 800-424-9300 CAGE:78580 Company Name: REICHHOLD CHEMICALS, INC., Address:Box:13852 City:REASARCH TRIANGLE PARK State:NC ZIP:27709 Country:US Phone:800-275-6353 CAGE:DO591

Ingred Name:S.D. WOOD TURPENTINE RTECS #:VO8400000 Fraction by Wt: 100% ACGIH TLV:100PPM

====== На

Effects of Overexposure:SKIN:IRRIT,DERMAT, BURNS. EYE IRRIT,DAMAGING, VAPOR IRRIT. INGEST:SERIOUS ILLNESS,DEATH-SUPP DATA.

First Aid:EYE: FLUSH W/WATER FOR 15 MIN,CALL MD. SKIN: WASH W/SOAP & WATER,CALL MD IF NEC. REMOVE & WASH CONTAMINATED CLOTH. INH: REMOVE FROM EXPOS,CALL MD IF NEC. INGEST: CALL MD IMMED,GIVE EDIBLE OIL,STOMACH PUMP MAY BE NEC,ASPIRATION A HAZAR D IF VOMITING.

Flash Point:92F;33C, TCC Lower Limits:0.8 Extinguishing Media:DRY CHEMICAL, CO*2, FOAM, WATER MAY BE INEFFECTIVE. Fire Fighting Procedures:USE WATER TO COOL HEAT EXPOSED CONTAINERS Unusual Fire/Explosion Hazard:POSSIBLE EXPLOSION HAZARD DUE TO PRESSURE BUILD UP IN HEAT EXPOSED CONTAINERS.

Spill Release Procedures: AVOID INHAL OF VAPORS. RE MOVE ANY POSS SOURVES

OF IGNITION. VENTILATE AREA THOROUGHLY. MOP UP SPILLED MATERIAL W/MOPS & RAGS, FOLLOWED BY WASHING W/DETERGENT & WATER.

Handling and Storage Precautions:STORE & KEEP AWAY FROM ALL SOURCES OF HEAT & FLAME. STORE AWAY FROM STRONG OXIDIZING AGENTS & MATERIALS. CONTAINER:5 GALLON PAIL
Other Precautions:GROUND CONTAINER WHEN POURING, FREE FALL OF LIQUID SHOULD NOT BE OVER A FEW INCHES. DO N
OT INGEST. AVOID PROLONGED CONTACT W/SKIN. PRODUCT HAS BEEN DISCONTINUED. SPEC:TY 1 CL 2-CANCELLED 7-79.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NIOSH/MSHA APPRVD RESPIRATOR RECOMMENDED FOR EXPOSURE OF CONCERN. Ventilation:LOCAL EXHAUST 6 MECHANICAL RECOMMENDED TO KEEP BELOW TLV. Protective Gloves:RUBBER GE REF Eye Protection:CHEM GOGGLES (GE REF) Supplemental Safety and Health SYNONYM:SPIRITS OF TURPENTINE. OVEREXPOS:INH:HDACHIDIZ

Z,CHEST PAIN,

NARCOSIS. OVEREXPOS 6 FIRST AID FROM GE MSDS REFERENCE. VP VALUE IS FOR ALPHA PINENE. SP GRAV VALUE IS AT 15.5C.

HCC:F4 Boiling Pt:B.P. Text:311F;155C Vapor Pres:3.2 Vapor Density:4.84 Spec Gravity:0.862 Evaporation Rate & amp; Reference:375 ETHER=17 Solubility in Water:SLIGHT Appearance and Odor:CLEAR,WATER WHITE OILY LIQUID;AROMATIC ODOR Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, OXIDATION CATALYSTS-GE MSDS REF. Hazardous Decomposition Products:CO*2,CARBON MONOXIDE

Waste Disposal Methods:MFR RECOMMENDS REMOVING CONTAMINATED MOPS & RAGS TO DMP AREA & DISPOSING OF BY BURNING THEM. DO NOT INCINERATE CLOSED CONTAINERS OF TURPENTINE. DISPOSAL METHOD MUST BE IAW FEDERAL,STATE & LOCAL CODES.

D

isclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation