

SPE-DE-WAY PRODUCTS CO.,INC. -- THINNER, PAINT; TT-T-291, TYPE 1, GRADE A --
8010-00-290-4079

===== Product Identification =====

Product ID:THINNER, PAINT; TT-T-291, TYPE 1, GRADE A

MSDS Date:01/01/1985

FSC:8010

NIIN:00-290-4079

MSDS Number: BDVDT

=== Responsible Party ===

Company Name:SPE-DE-WAY PRODUCTS CO.,INC.

CAGE:33439

=== Contractor Identification ===

Company Name:SPE-DE-WAY PRODUCTS CO IN

C

Address:8000 N E 14TH PLACE

Box:17192

City:PORTLAND

State:OR

ZIP:97217

Country:US

CAGE:33439

Company Name:WOOD-KOTE PRODUCTS INC FRMLY SP-DE-WAY PROD.

Address:8000 N.E. 14TH PLACE

Box:City:PORTLAND

State:OR

ZIP:97217

Country:US

Phone:1-800-535-5053

CAGE:33429

===== Composition/Information on Ingredients =====

Ingred Name:PARAFFINS (INCLUDING NAPHTHENES)

Fraction by Wt: 92.0%

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 1

.0%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:AROMATIC COMPOUNDS CONTAINING MORE THAN EIGHT CARBONS.
Fraction by Wt: 7.0%

=====
Hazards Identification
=====

Effects of Overexposure:MAY CAUSE EYE IRRIT, SKIN DERMATITIS. INHAL MAY
SHOW SIGNS OF CNS DEPRESSION.

=====
First Aid Measures
=====

First Aid:FLUSH EYES AT LEAST 15 MIN. INHAL: REMOVE TO FRESH
AIR.
INGESTION: DO NOT INDUCE VOMITING. CONSULT MD.

=====
Fire Fighting Measures
=====

Flash Point:100F TCC
Lower Limits:1.0
Upper Limits:6.0
Extinguishing Media:CO*2, DRY CHEMICAL, FOAM, WATER SPRAY
Fire Fighting Procedures:USE SELF-CONTAINED OBA IN ENCLOSED SPACE

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION IN VICINITY OF
SPILL OR RELEASED VAPORS. CLEAN UP AS SOON AS POSSIBLE.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP AWAY FROM HEAT OR OPEN FLAME.
AVOID PROLONGED OR REPEATED BREATHING OF VAPOR OR SKIN & EYE
CONTACT.
Other Precautions:HARMFUL OR FATAL IF SWALLOWED

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:IN HIGH CONC USE APPROVED RESPIRATOR OR
SELF-CONTAINED OBA
Ventilation:ADEQUATE TO KEEP VAPOR OR MIST BELOW SUGGESTED TLV
Protectiv

e Gloves:RUBBER
Eye Protection:CHEMICAL GOGGLES
Supplemental Safety and Health
VAPOR PRESSURE IS GIVEN AT 77.8F CONFORMS TO TT-T-291, TYPE 1, GRADE A

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:313-404 F
Vapor Pres:5.0
Vapor Density:4.9
Spec Gravity:0.801
Evaporation Rate & Reference:0.13 BUTYL ACETATE
Solubility in Water:NEGLIGIBLE
Appearance and Odor:COLORLESS LIQUID
Percent Volatiles by Volume:99.0

===== Stability and Re
activity Data =====

Stability Indicator/Materials to Avoid:YES
MAY REACT W/STRONG OXIDIZING MATERIALS
Hazardous Decomposition Products:INCOMPLETE COMBUSTION: CARBON MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:ABSORB LARGE SPILLS W/ABSORBENT CLAY OR
DIATOMACEOUS EARTH. DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, FED
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is
formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.