View NSN Online: https://aerobasegroup.com/nsn/8010-00-290-4079

UNION OIL CO. OF CALIF.; UNION 76 DIV. -- MINERAL SPIRITS 75 -- 8010-00-290-4079

========= Product Identification ============

Product ID:MINERAL SPIRITS 75

MSDS Date:01/01/1985

FSC:8010

NIIN:00-290-4079

MSDS Number: BDVDV === Responsible Party ===

Company Name: UNION OIL CO. OF CALIF.; UNION 76 DIV.

Address:1650 EAST GOLF ROAD

City:SCHAUMBURG

State:IL ZIP:60195 Country:US

Info Phone Num:312-619-2644

Emergen

cy Phone Num:312-619-2644

CAGE:EO159

=== Contractor Identification ===

Company Name: UNION OIL CO OF CALIFORNIA, CORP. DIV-EASTERN

Address:1650 EAST GOLF ROAD

Box:City:SCHAUMBURG

State:IL ZIP:60195 Country:US

Phone:708-619-2644

CAGE:77416

Company Name: UNION OIL CO. OF AMERICA, UNION CHEMICALS DIV.

Address:1900 E GOLF ROAD

City:SCHAUMBURG

State:IL

ZIP:60194-5021 Phone:312-490-2500

CAGE:EO159

======= Composition/Information on Ingredients ========

Ingred Name: NAPHTHA (PETROLEUM SPIRIT

Fraction by Wt: 100% OSHA PEL:100 PPM ============= Hazards Identification ======================== Effects of Overexposure: EYES: SEVERE IRRIT. SKIN: DRYNESS. INH: HDCH, DIZZ, NAUSEA. First Aid:EYES:FLUSH W/WATER 15 MINS, CALL MD.SKIN:WASH W/MILD SOAP & WATER, APPLY SKIN CREAM. INH: MOVE TO FRESH AIR & CALL MD. APPLY ARTIFICIAL RESP IF NEC. _____ Fire Fighting Measures ========== Flash Point:108F,42C PCC Lower Limits: 1.0 Upper Limits:6.0 Extinguishing Media: WATER SPRAY, CO*2, FOAM, DRY CHEMICAL. Fire Fighting Procedures: WEAR SCBA. USE WATER SPRAY TO COOL FIRE-EXPOSED CONTAINERS. Unusual Fire/Explosion Hazard: A DANGEROUS FIRE HAZARD IF HEATED OR SPRAYED IN AIR. ========= Accidental Release Measures ============== Spill Release Procedures: FLUSH WITH WATER INTO RETAINING AREA OR CONTAINER. AVOID EXPO SURE TO SPARKS, FIRE, OR HOT METAL SURFACES. VENTILATE AREA. ============ Handling and Storage =========================== Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS & OPEN FLAME. USE WITH ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED CONTACT W/SKIN. KEEP CNTNRS CLSD WHEN NOT IN USE. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: SCBA FOR CONCENTRATIONS ABOVE TLV LIMITS. (MFG) Ventilation:LOCAL EXHAUST Protecti

S OR BENZIN) CAS:8030-30-6

RTECS #:SE7555000

ve Gloves:YES
Eye Protection:YES
Other Protective Equipment:EYE BATH AND SAFETY SHOWER.
Supplemental Safety and Health
CONFORMS T TT-T-291E, TYPE II, GRADE A. BP:156-198C. EVAP
RATE: