View NSN Online: https://aerobasegroup.jp/nsn/6750-00-291-5858

EASTMAN CHEMICAL PRODUCTS, INC. -- HYDROQUINONE -- 6750-00-291-5858

Product ID: HYDROQUINONE MSDS Date:06/25/1984 FSC:6750 NIIN:00-291-5858 MSDS Number: BDVMF === Responsible Party === Company Name: EASTMAN CHEMICAL PRODUCTS, INC. Address:WILCOX DR AND LINCOLN ST Box:431 City:KINGSPORT State:TN ZIP:37662 Country:US CAGE:78364 === Contractor Identification === Compa ny Name: CANCELLED WITHOUT REPLACEMENT (WAS SNYDER, GEO H INC) Box:431 Phone:NONE CAGE:78364 Company Name: EASTMAN CHEM PRODUCTS A SUB OF EASTMAN KODAK CO Address: EASTMAN ROAD Box:City:KINGSPORT State:TN ZIP:37662 Country:US Phone:423-229-2000 CAGE:74364

Ingred Name:HYDROQUINONE (SARA III) CAS:123-31-9 RTECS #:MX3500000 Fraction by Wt: 99% OSHA PEL:2 MG/M3 ACGIH TLV:2 MG/M3; 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

=================

LD50 LC50 Mixture: ACUTE ORAL RAT 400 MG/KG Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: EYE INJURY FROM REPEATED EXPOSURE. MAY PRODUCE ALLERGIC SKIN REACTIONS. Effects of Overexposure: IRRITATION TO EYE & SKIN.

Medical Cond Aggravated by Exposure: ALLERGIC SKIN CONDITIONS.

F

irst Aid: EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION.

 Fire Fighting Measures	
ine ingitting measures	

Flash Point Method:COC Flash Point:350F,177C Autoignition Temp:Autoignition Temp Text:930F Extinguishing Media:WATER SPRAY, DRY CHEMICAL, CO*2 Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN AND EYES. Unusual Fire/Explosion Hazard: THIS MATERIAL IS CAPABLE OF CREATING A

DUST EXPLOSION.

Spill Release Procedures: COLLECT AND CONTAIN FOR SALVAGE OR DISPOSAL. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. KEEP AWAY FROM FOODSTUFF. Other Precautions:NONE

R

espiratory Protection:NONE NORMALLY REQUIRED.
Ventilation:MECHANICAL (GENERAL) AND LOCAL RECOMMENDED FOR DUST OR VAPOR CONTROL.
Protective Gloves:IMPERVIOUS/RUBBER PROTECTIVE GLOVES
Eye Protection:SAFETY GLASSES
Other Protective Equipment:EYE BATH & WASHING FACILITIES SHOULD BE AVAILABLE.
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.
Supplemental Safety and Health NONE

HCC:T4

Melt/Freeze Pt:M.P/F.P Text:347F ,175C Vapor Pres:NIL Vapor Density:3.81 Spec Gravity:1.34 Solubility in Water:MODERATE Appearance and Odor:WHITE CRYSTALS, ODORLESS Percent Volatiles by Volume:0

Stability Indicator/Materials to Avoid:YES OXIDIZING MATERIALS. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:CARBON DIOXIDE AND CARBON MONOXIDE

Waste

Disposal Methods:INCINERATE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL LAWS & REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to veri

fy and

assume responsibility for the suitability of this information to their particular situation.