View NSN Online: https://aerobasegroup.jp/nsn/8010-00-297-0584

Product ID: ENAMEL ALKYD SG WHITE 27875 (745720) MSDS Date:01/01/1987 FSC:8010 NIIN:00-297-0584 MSDS Number: BDVZV === Responsible Party === Company Name: PRAXAIR INC Address:39 OLD RIDGEBURY RD Box:2153 City:DANBURY State:CT ZIP:06817-0001 Country:US Info Phone Num:203-794-5782 **Emergency Phone** Num:203-794-5782 CAGE:0LV01 === Contractor Identification === Company Name: PRATT AND LAMBERT INC Box:6027 City:CLEVELAND State:OH ZIP:44101-1027 Country:US Phone:216-566-2902 CAGE:61196 Company Name: PRAXAIR, INC. Address:39 OLD RIDGEBURY RD Box:City:DANBURY State:CT ZIP:06810-5113 Country:US Phone:800-772-9247; 800-PRAXAIR CAGE:0LV01

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE CAS:14464-46-1 RTECS #:VV7325000 OSHA PEL:SEE TABLE Z3 ACGIH TLV:0.05 MG/M3 RDUST9293

Ingred Name:TALC (CONTAINING NO ASBESTOS) CAS:14807-96-6 RTECS #:WW2710000 OSHA PEL:2 MG/M3 RDUST ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:TITANIUM DIOXIDE RTECS #:XR2100000 ACGIH TLV:10 MG/CU.M.

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III) CAS:1330-20-7 RTECS #:ZE2100000 OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:MINERAL SPIRITS CAS:64475-85-0 RTECS #:PY8240000 ACGIH TLV:100 PP M

Effects of Overexposure:SWALLOWING CAN CAUSE GASTROINTESTINAL IRRITATION,ANESTHETIC,MAY CAUSE HEADACHE OR NAUSEA

First Aid:IF SWALLOWED INDUCE VOMITING.CONSULT PHYSICIAN OR POISON CONTROL CENTER.INHALATION-REMOVE TO FRESH AIR.EYE-FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES.SKIN-WASH AFFECTED AREA WITH SOAP AND WATER. GET MEDICAL ATTE NTION IF IRRITATION PERSISTS

Flash Point:80F(26.67C) Lower Limits:1.10 Extinguishing Media:CLASS B FIRE EXTINGUISHERS Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED.ISOLATE FROM HEAT.CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT

Spill Release Procedures: KEEP SPECTATORS A

WAY.ELIMINATE ALL IGNITION SOURCES.DIKE AND CONTAIN SPILL WITH INERT MATERIAL.TRANSFER LIQUIDS TO COVERED METAL CONTAINERS FOR RECOVERY OR DISPOSAL.PREVENT CONTAMINATION OF SEWERS,STR EAMS AND GROUND WATER WITH SPILLED MATERIAL

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106 Other Precautions:DO NOT TAKE INTERNALLY.CLOSE CONTAINER AFTER E ACH

USE.DO NOT BREATHE SANDING DUST.EMPTY CONTAINERS MUST NOT BE WASHED OR REUSE.NEVER USE PRESSURE TO EMPTY CONTAINER.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:USE NIOSH APPROVED MECHANICAL FILTER OR AIR-SUPPLIED RESPIRATOR Ventilation:PROVIDE GENERAL DILUTION AND LOCAL EXHAUST VENTILATION Protective Gloves:IMPERMEABLE Eye Protection:GOGGLES AND FACE SHIELD Other Protective Equipment:NONE LIKELY TO BE NEEDED Supplemental Safety and Health

HCC:F3 Boiling Pt:B.P. Text:244F Vapor Pres:5 Vapor Density:>1 Evaporation Rate & amp; Reference:SLOWER THAN ETHER Percent Volatiles by Volume:56

Stability Indicator/Materials to Avoid:YES STRONG ACIDS OR ALKALINE MATERIALS Stability Condition to Avoid:NONE KNOWN Hazardous Decomposition Products:BURNING WILL PRODUCE SMOKE,CARBON MONOXIDE AND DIOX IDE

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL LAWS.DO NOT INCINERATE CLOSED CONTAINERS.INCINERATE ONLY IN EPA PERMITTED FACILITY.OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIALS

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner wh atsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.