

SENTRY PAINT & CHEMICAL CO, DARBY, PA. 19023 -- X-3917 ZINC CHROMATE PRIMER --
8010-00-515-2208

===== Product Identification =====

Product ID:X-3917 ZINC CHROMATE PRIMER

MSDS Date:01/01/1985

FSC:8010

NIIN:00-515-2208

MSDS Number: BFCBY

=== Responsible Party ===

Company Name:SENTRY PAINT & CHEMICAL CO, DARBY, PA. 19023

Emergency Phone Num:215-GL9-5320

CAGE:GO855

=== Contractor Identification ===

Co

Company Name:SENTRY PAINT & CHEM CO

Address:MILL AND LAWRENCE ST

Box:City:DARBY

State:PA

ZIP:19023

Country:US

CAGE:GO855

Company Name:SENTRY PAINT AND CHEMICAL CO

Address:MILL AND LAWRENCE ST

Box:City:DARBY

State:PA

ZIP:19023

Country:US

CAGE:34346

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

OSHA PEL:100 PPM

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

OSHA PEL:200 PPM/150

STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ZINC CHROMATE
CAS:13530-65-9
RTECS #:GB3290000
OSHA PEL:0.1 MG/M3 (CRO3)
ACGIH TLV:0.01MG/M3(CR)A1;9192

Ingred Name:TALC (CONTAINING NO ASBESTOS)
CAS:14807-96-6
RTECS #:WW2710000
OSHA PEL:2 MG/M3 RDUST
ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:ALKYD

===== Hazards Identification =====

Effects of Overexposure:DIZZINESS, HEADACHE AND NAUSEA

===== First Aid Measures =====

First Aid:REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF BREATHING STOPS.

===== Fire Fighting Measures =====

Lower Limits:1.0
Upper Limits:7.0
Extinguishing Media:FOAM,CO2,DRY CHEMICAL
Fire Fighting Procedures:USE EQUIPMENT SUPPLIED AIR SUPPLY FOR ENCLOSED AREAS.
Unusual Fire/Explosion Hazard:COMBUSTIBLE LIQUID,COOL EXPOSED CONTAINERS.

===== Accidental Release Measures =====

Spill

Release Procedures:CLEAN UP AS ANY FLAMMABLE LIQUID. AVOID
SPARKS, USE DRY ABSORBENT IF POSSIBLE. AVOID IGNITION SOURCE.USUAL
ADEQUATE VENTILATION

===== Handling and Storage =====

Handling and Storage Precautions:AVOID OPEN FLAME AND HIGH TEMPERATURE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:CARTRIDGE TYPE RESPIRATOR,ORGANIC VAPOR AND DUST
RESPIRATION

Ventilation:LOCAL EXHAUST

Supplemental Safety

and Health

1000163PC PHENOLIC

IPALC

HEPTURE

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:240F

Vapor Pres:36

Vapor Density:3.9

Evaporation Rate & Reference:FASTER THAN NBUACT

Solubility in Water:NONE

Appearance and Odor:YELLOW PRIMER

Percent Volatiles by Volume:63.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:HIGH

TEMPERATURE AND IGNITION SOURCES

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should s

seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.