

GOAL CHEMICAL SEALANTS CORP. -- GC-1300 TYPE II, CLASS 1,2, & 3 -- 8030-00-515-2271

=====
Product Identification
=====

Product ID:GC-1300 TYPE II, CLASS 1,2, & 3
MSDS Date:01/01/1985
FSC:8030
NIIN:00-515-2271
Kit Part:Y
MSDS Number: BFCDT
=== Responsible Party ===
Company Name:GOAL CHEMICAL SEALANTS CORP.
Address:3137 E 26TH ST
City:LOS ANGELES
State:CA
ZIP:90023-4206
Country:US
CAGE:04011
=== Con
tractor Identification ===
Company Name:GOAL CHEMICAL SEALANTS CORP
Address:3137 E 26TH ST
Box:City:LOS ANGELES
State:CA
ZIP:90023-4206
Country:US
Phone:213-269-0461
CAGE:04011

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 2%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
Hazards Identification
=====

Effects

of Overexposure:MAY CAUSE SKIN & EYE IRRITATION

=====
First Aid Measures
=====

First Aid:EYE CONTACT-FLUSH WITH WATER

=====
Fire Fighting Measures
=====

Flash Point:170F COC 77C

Lower Limits:2.7

Extinguishing Media:WATER, CO*2, DRY CHEMICALS

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE SOURCES OF INGITION. SCRAPE UP EXCESS &
STORE IN CONTAINER. REMOVE RESIDEU W
/1,1,1 TRICHLOROETHANE-SOAKED
RAGS.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES.

Other Precautions:REMOVE SOURCES OF IGNITION.

=====
Exposure Controls/Personal Protection
=====

Ventilation:LOC EXHAUST-OPTIONAL, MECH-YES

Protective Gloves:NEOPRENE/BUTYL

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NONE

Supplemental Safety and Health

KEY1:F8.

=====
Physical/Che
mical Properties
=====

HCC:V4

Boiling Pt:B.P. Text:233F MIXTR

Vapor Density:3.2

Spec Gravity:1.62

Evaporation Rate & Reference:ETHYL ETHER 4.5

Appearance and Odor:WHITE PASTE, MERCAPTAN ODOR

Percent Volatiles by Volume:2

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:STRONG BASES, OXIDIZING AGENTS

Conditions to Avoid Polymerization:STORE BELOW 80F

=====
Disposal
=====

Considerations =====

Waste Disposal Methods: REACT W/CATALYST & DISPOSE AS INERT MATERIAL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.