View NSN Online: https://aerobasegroup.com/nsn/4730-00-542-3362

PHILADELPHIA RESINS CORP. -- PHILLYBOND,6 HARDENER -- 4730-00-542-3362

Product ID:PHILLYBOND,6 HARDENER

MSDS Date:01/01/1987

FSC:4730

NIIN:00-542-3362

Kit Part:Y

MSDS Number: BFDMK === Responsible Party ===

Company Name: PHILADELPHIA RESINS CORP.

Emergency Phone Num:215-855-8450

CAGE:20420

=== Contractor Identification ===

Company Name: ITW PHILADELPHIA RESINS

Add

ress:130 COMMERCE DR Box:City:MONTGOMERYVILLE

State:PA ZIP:18936 Country:US

Phone:215-855-8450

CAGE:20420

======= Composition/Information on Ingredients ========

Ingred Name: SILICA, AMORPHOUS, DUST

CAS:112945-52-5 RTECS #:VV7310000 OSHA PEL:6 MG/M3

ACGIH TLV:10 MG/M3; 8990

Ingred Name: CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000 OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3; 9192

Ingred Name: TALC (CONTAINING NO ASBESTOS)

CAS:14807-96-6

RTECS #:WW2710000

OSHA PEL:2 MG/M3 RDUST

ACGIH TLV

Ingred Name:PHENOL CAS:108-95-2 RTECS #:SJ3325000 OSHA PEL:S, 5 PPM ACGIH TLV:S, 5 PPM; 8990 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS
========= Hazards Identification ===========
Effects of Overexposure:SKIN-IRRIT,SENSITIZER
======================================
First Aid:EYE-FLUSH W/ WATER FOR 15 MIN & CALL MD.SKIN-WASH W/ SOAP & WATER IMMEDIATELY
======================================
Flash Point:200F,93C PMCC Extinguishing Media:CO*2,FOAM,DRY CHEMICALS,WATER Fire Fighting Procedures:NONE PER MFR Unusual Fire/Explosion Hazard:NONE KNOWN PER MFR
======== Accidental Release Measures =========
Spill Release Procedures:WIPE UP WITH CLEAN RAGS.RESIDUE MAY BE CLEANED W/ SOLVENT DAMPENED RAG.
============ Handling and Storage ==============
Handling and Storage Precautions: AVOID BREATHING VAPORS AND AVOID SKIN CONTACT.
=== ====== Exposure Controls/Personal Protection =========
Ventilation:LOCAL EXHAUST PREFERABLE,MECHANICAL ACCEPTABLE. Protective Gloves:IMPRV RUB,PLAST Eye Protection:GOGGLES Other Protective Equipment:CLEAN LONG LEGGED & SLEEVED CLOTHING Supplemental Safety and Health
MSDS PREP:85244.SPEC:ASSEMBLY 2.PART A OF 2 PART KIT.
======================================
Boiling Pt:B.P. Text:N/K PER MFR Spec Gravity:2 Evaporation Rate & Description Rate & Des

:2 MG/M3 RDUST; 9192

Appearance and Odor:BLACK,AMINE ODOR
========= Stability and Reactivity Data ===========
Stability Indicator/Materials to Avoid:YES STRONG ACIDS & BASES Hazardous Decomposition Products:CO,CO*2,OXIDES OF N*2 Conditions to Avoid Polymerization:UNCONTROLLED AMOUNTS OF EPOXY RESIN

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE & LOCAL REGULATIONS.

======= Disposal Considerations ===========

Disclaimer

ubility in Water:N/K PER MFR

(provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.