View NSN Online: https://aerobasegroup.jp/nsn/6850-00-570-9360

CHEMTRONICS, INC -- ELECTRIC CONTACT, CLEANG & LUBRICATING CMPD -- 6850-00-570-9360

Product ID:ELECTRIC CONTACT, CLEANG & LUBRICATING CMPD

MSDS Date:01/01/1987

FSC:6850

NIIN:00-570-9360

MSDS Number: BFFPV === Responsible Party ===

Company Name: CHEMTRONICS, INC Address:681 OLD WILLETS PATH

City:HAUPPAUGE

State:NY ZIP:11787 Country:US

Info Phone Num:800-645-5244

Emerge

ncy Phone Num:800-645-5244

CAGE:LO604

=== Contractor Identification ===

Company Name: CHEMTRONICS INC Address:8125 COBB CENTER DRIVE

Box:City:KENNESAW

State:GA ZIP:30152 Country:US

Phone:770-424-4888/800-645-5244

CAGE:21267

Company Name: CHEMTRONICS, INC Address:681 OLD WILLETS PATH

Box:City:HAUPPAUGE

State:NY ZIP:11787 Country:US

Phone:800-645-5244

CAGE:LO604

======= Composition/Information on Ingredients ========

Ingred Name: METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS

:71-55-6 RTECS #:KJ2975000 Fraction by Wt: 66.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:350 PPM ACGIH TLV:350 PPM/450STEL;9394 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ozone Depleting Chemical:1
Ingred Name:DICHLORODIFLUOROMETHANE (SARA III) CAS:75-71-8 RTECS #:PA8200000 Fraction by Wt: 32.0% OSHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ozone Depleting Chemical:1
Ingred Name:POLY(ETHYL)SILOXANE CAS:9016-00-6 RTECS #:TQ2690000 Fraction by Wt: 2.0% A CGIH TLV:NOT SPECIFIED
======================================
Effects of Overexposure:LIGHT-HEADNESS,GIGINESS,NARC,CARDIAC ARRYTHMIAS.AT HIGH CONCENTRATIONS,IF INHALED,CAN CAUSE DEATH.
======================================
First Aid:SKIN:WASH W.SOAP & H*2O. EYES:FLUSH W. H*2O. INGESTED:DON'T INDUCE VOMITING. INHALED:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. NEVER GIVE
ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.
=========== Fire Fighting Measures ===========
Flash Point:N/A(SEE SUP DAT) Extinguishing Media:WATER FOG Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP Unusual Fire/Explosion Hazard:CONTAINERS MAY RUPTURE IN HEAT OF FIRE.TOXIC GAS MAY EXCAPE DURING FIRE.
=========== Accidental Release Measures ==============

Spill Release Procedures: VENTILATE AREA-ESPECIALLY LOW PLACES WHERE HEAVY VAPOR MIGHT COLLE

CT.REMOVE IGNITION SOURCES.KEEP OUT OF WATER
SUPPLIES.ABSORB AND WIPE UP SMALL SPILLS.TRANSFER TO CLOSED METAL
CONTAINERS.LG SPILL:DIK E WITH COMMERCIAL OR OTHER
ABSORBENT,DISPOSE LATER

=========== Handling and Storage ============================

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED,LOW FIRE RISK AREA. PROTECT FROM PHYSICAL DAMAGE.KEEP CONTAINERS CLOSED. MAINTAIN STRICT HYGIENE FOR CHEM HANDLING.

Other Precautions: NONE

====== Ex

posure Controls/Personal Protection =======

Respiratory Protection: USE AIR MASKS IN HIGH CONCENTRATIONS.

Ventilation:LG AMTS RELEASED-LOCAL EXHAUST, MECHANICAL IN LOW AREAS.

Protective Gloves: IMPERVIOUS

Eye Protection: CHEM SPLASH GOGGLES

Other Protective Equipment: FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT.

Supplemental Safety and Health

BP RANGE:-6C-149C.VAP PRESS:DICHLORODIFLUOROETHANE-4893MM.FP FOR POLYSILOXANE G1:500F TOC.

======= Physical/Chemica

I Properties ========

HCC:V2

Boiling Pt:B.P. Text:-21F-300F

Vapor Pres:SUP Vapor Density:6.33 Spec Gravity:1.3

Evaporation Rate & Evaporation R

Solubility in Water: NEGLIGIBLE

Appearance and Odor: COLORLESS-SLIGHT ETHEREAL ODOR.

Percent Volatiles by Volume:96

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES IN WATER-SLOW HYDROLYSIS TO CORR ACID,ALUMINUM & ITS ALLOYS. Stability Condition to Avoid:OPEN FLAMES

,HIGH TEMPERATURES,WELDING ARCS.

Hazardous Decomposition Products:HCL,HF,POSS CARBONYL FLUORIDES,SM AMTS PHOSGENE,FLUOR,CHLOR.

======= Disposal Considerations ===========

Waste Disposal Methods:RECLAIM BY DISTILATION.SEND TO LICENSED RECLAIMER OR DISPOSAL CONTRACTOR.COMPLY WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.