Product ID:CLEANING & LUBRICATING CPD, ELECTRIC CONTACT

MSDS Date:01/01/1985

FSC:6850

NIIN:00-570-9360

MSDS Number: BFFPY === Responsible Party ===

Company Name: W.M. BARR & CO Emergency Phone Num: 901-775-0100

CAGE:IO929

=== Contractor Identification ===
Company Name:W.M. BARR & CO
Address:2105 CHANNEL AVE

Box:1879 City:MEMPHIS

State:TN ZIP:38101 Country:US

Phone:901-775-0100

CAGE:IO929

Company Name: W.M. BARR & COMPANY/KLEAN-STRI, DIVISION OF

Address:2105 CHANNEL AVENUE

Box:1879 City:MEMPHIS

State:TN ZIP:38101 Country:US

Phone:901-775-0100

CAGE:91522

======= Composition/Information on Ingredients ========

Ingred Name: METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6


RTECS #:KJ2975000 Fraction by Wt: 63.5%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:350 PPM

ACGIH TLV:350 PPM/450STEL;9394

EPA Rpt Qty:1000 LBS



Handling and Storage ========== Handling and Storage Precautions: STORE IN COOL, DRY, WELL VENTILATED, LOW FIRE RISK AREA. PROTECT FROM PHYSICAL DAMAGE.KEEP CONTAINERS CLOSED. MAINTAIN STRICT HYGIENE FOR CHEM HANDLING. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: USE AIR MASK WITH AIR SUPPLY IN HEAVY CONCENTRATIONS. Ventilation: USE LOCAL EXHAUST FOR LG SPILL; MECH WHEN VAP IN LOW AREAS Protective Gloves: IMPERVIOUS **Eve Protecti** on:CHEM SPLASH GOGGLES Other Protective Equipment: WEAR IMPERVIOUS CLOTHING/BOOTS. Supplemental Safety and Health BOILING PT:34% INGRED:-21.6F;63.5% INGRED:162-190F.EVAP RATE:34% INGRED-RAPID;63.5% INGRED-SLOWER 0.4 OF ETHER WHICH=1.MEETS REGMTS FOR TYPE II UNDER MIL-C-83360 ========= Physical/Chemical Properties =========== HCC:V2 Boiling Pt:B.P. Text:SEE SUP AT Vapor Pres:100 Vapor Density:>1 Spec Gravity:1.3 Evaporation Rate & Evaporation R Solubility in Water: NEGLIGIBLE Appearance and Odor: AEROSAL FORMULATION Percent Volatiles by Volume:97.5 ======== Stability and Reactivity Data =========== Stability Indicator/Materials to Avoid:YES ALKALI/AKALINE EARTH METALS, POWDERED ALUMINUM, ZINC, BERYLIUM. Stability Condition to Avoid: OPEN FLAMES, HOT SURFACES, SPARKS AND IGNITION SOURCES.

Hazardous Decomposition Products:HYDROCHLORIC & HYDROFLUORIC ACIDS,CARBONYL HALIDE(PHOSGENE).

====== Disposal Considerations

\_\_\_\_\_

particular situation.

Waste Disposal Methods: EVAPORATION IS FAIRLY RAPID. USE ABSORPTIVE MEDIA FOR LARGE AMOUNTS. DISPOSE IAW APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. An y person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their