

AMERON INDUSTRIAL COATINGS DIVISION -- YELLOW #13578 -- 8010-00-584-3082

===== Product Identification =====

Product ID:YELLOW #13578

MSDS Date:01/01/1987

FSC:8010

NIIN:00-584-3082

MSDS Number: BFGLC

=== Responsible Party ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

City:BREA

State:CA

ZIP:92621-3904

Country:US

Info Phone Num:714-529-4597

Emergency Phone Num:714-529-45

97

CAGE:09869

=== Contractor Identification ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 44.6%

OSHA PEL:100 PPM

===== Hazards Identification =====

Effects of Overexposure:ANESTHETIC, IR

R. OF RESPIRATORY TRACT OR ACUTE
NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION

===== First Aid Measures =====

First Aid:IN CASE OF CONTACT FLUSH SKIN AND EYES WITH WATER AND REMOVE
CONTAMINATED CLOTHING. IF INHALED REMOVE TO FRESH AIR. CALL A
PHYSICIAN IF CONDITIONS PERSIST.

===== Fire Fighting Measures =====

Flash Point:85F TCC
Lower Limits:1.1
Extinguishing Media:SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LAG
E
FIRES-FOAM
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLODE

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID
BREATHING VAPORS. REMOVE WITH INERT ABSORBENT AND NON-SPARKING

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STO
RE LARGE
QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE
FLAMMABLES.
Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID
FREE FAL OF LIQUID IN EXCESS OF A FEW INCHES

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED PAINT RESPIRATOR OR AIR
SUPPLIED RESPIRATOR
Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECESSARY
Supplemental Safety and Health
RESPIRATOR USE BASED ON CHEM. CON

C. AND CONDITIONS OF USE.

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:311-373F

Vapor Density:>1

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:61.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AVOID FIRE,HEAT AND HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Metho

ds:DISPOSE IN ACCORDANCE WITH LOCAL,STATE AND

FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.