

SEAGRAVE CORP TITANINE DIVISION -- M-430 CEMENT TYPE I MMM-A-105 -- 8040-00-664-7073

=====
Product Identification
=====

Product ID:M-430 CEMENT TYPE I MMM-A-105

MSDS Date:05/05/1987

FSC:8040

NIIN:00-664-7073

MSDS Number: BFKSN

=== Responsible Party ===

Company Name:SEAGRAVE CORP TITANINE DIVISION

Address:320 PATERSON PLANK RD

City:CARLSTADT

State:NJ

ZIP:07072-2302

Country:US

Info Phone Num:(201)9

33-1000

Emergency Phone Num:(201)933-1000

CAGE:78767

=== Contractor Identification ===

Company Name:SEAGRAVE CORP TITANINE DIVISION

Address:320 PATERSON PLANK RD

Box:City:CARLSTADT

State:NJ

ZIP:07072-2302

Country:US

CAGE:78767

Company Name:STEVENS INDUSTRIES

Address:39 AVE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002

Country:US

Phone:201-437-6500

CAGE:70372

=====
Composition/Information on Ingredients
=====

Ingred Name:LACTOL SPIRITS

CAS:64742-89-8

Fraction by Wt:

Other REC Limit

s:400 PPM
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt:
Other REC Limits:100PPM
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt:
Other REC Limits:400PPM
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt:
Other REC Limits:100PPM
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:N-BUTYL ACETATE (SARA III)
CAS:123-86-4
RTECS #:AF7350000
Fraction by Wt:
Other REC Limits:150 PPM
OSHA PEL:150 PPM/200 STEL
ACGIH TLV:150 PPM/200STEL;9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:N/K
Routes of Entry: Inhalation:YES Skin:YES Ingestion:

YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:PALE, NAUSEOUS, DIZZY, WEAKNESS.
CHRONIC:UNKNOWN.

Explanation of Carcinogenicity:NOT APPLICABLE

Effects of Overexposure:POSSIBLE

DIZZINESS,HEADACHE,NAUSEOUS,WEAK/IRRITATION.

Medical Cond Aggravated by Exposure:UNKNOWN.

=====
First Aid Measures
=====

First Aid:TREAT SYMPTOMATICALLY-CONSULT PHYSICIAN.EYE-FLUSH IMME W/LGE
AMTS OF WTR FOR AT LEAST 15 MI

N.TAKE TO PHYSICIAN.INHAL:REMOVE TO

FRESH AIR.RESTORE BREATHING(GIVE O*2/ARTIFICIAL RESPIRATION), TREAT
SYMPTOMATICALLY-CONSULT PHYSICIAN.INGES:DRINK 1-2 GLASSES OF WATER
TO DILUTE.DO NOT INDUCE VOMITING.CONSULT PHYSICIAN.SKIN:WASH W/SOAP
& WTR,RMOV CONTAM CLTHNG,CONSULT PHYS IF NEEDED.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC

Flash Point:21F/-6.1C

Lower Limits:1.4

Upper Limits:12.0

Extinguishing Media:CO*2,DRY CHEMICAL, FOAM.

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE
EQUIPMENT .DO NOT USE WATER-EXCEPT W/FOG NOZZLES.

Unusual Fire/Explosion Hazard:DO NOT USE ON HOT SURF/IN AREAS WHERE
ELEC SPRK MAY BE PRESENT/WHERE STATIC CHARGE MAY BE GENERATED.DUE
TO EXTREML HEAT EXPO,PRESS MAY BLD UP IN CLOSED(SUP DAT)

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ANY SOURCE OF SPARK/FLAME, PROVIDE
IMMEDIATE VENTILATION, AVOID BREAT
HING VAPORS & WEAR APPROPRIATE
RESPIRATOR. ADD ABSORBENT TO SPILL, PLACE IN SEALED METAL
CONTAINERS USING NON-SPARKING TOOLS .

Neutralizing Agent:N/K

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN RED LABEL AREA IN ORIGINAL
CONTAINERS.

Other Precautions:GROUND ALL EQUIPMENT & CONTAINERS.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE NIOSH/MSHA APPROVED CHEMICAL FILTERS

DESIGNED TO REMOVE A COMBINATION OF PARTICLES/VAPORS. IN CONFINED AREAS USE APPROVED AIR LINE TYPE RESPIRATORS/HOODS.

Ventilation:NECESSARY, LOCAL EXHAUST-RECOMMENDED, MECHANICAL(GENERAL)-ACCEPTABLE. SPECIAL-WEAR DUST MASK WHILE SANDNG DRY PAINT FILM

Protective Gloves:SOLVENT RESISTANT GLOVES.

Eye Protection:CHEMICAL WORKER GOGGLES.

Other Protective Equipment:APRON & BOOTS RECOMMENDED.IF SKIN CONTACT IS LIKELY USE PROTECTIVE SKIN CREAM.EYE BATH & SAFETY SHOWER.

Work Hygienic

Practices:N/K

Supplemental Safety and Health

BP:79.4-126.1C.% VOLT:N/K-PH:N/K-UNU FR&EXPLO HAZ:CNTNR,WHCH MAY EXPLODE.WTR MAY BE USED TO COOL UNRUPTURED CONTAINERS.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175-259F

Melt/Freeze Pt:M.P/F.P Text:N/APPLICABL

Decomp Temp:Decomp Text:N/K

Vapor Density:HV THN AIR

Spec Gravity:0.86

Evaporation Rate & Reference:N/K

Solubility in Water:NONE

Appearance and Odor:LIQUID-MILD

Corrosion Rate

:

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE KNOWN.

Stability Condition to Avoid:EXCESSIVE HEAT & FIRE.

Hazardous Decomposition Products:OXIDES OF CARBON.

Conditions to Avoid Polymerization:HIGH TEMPERATURE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compi

ling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.