View NSN Online: https://aerobasegroup.com/nsn/8040-00-701-9514

HYSOL DIV, DEXTER CORPORATION, DEXTER ELECTRONICS -- HD-3475 (FORMERLY H2-3475) -- 8040-00-701-9514

============ Product Identification =========================

Product ID:HD-3475 (FORMERLY H2-3475)

MSDS Date:02/10/1989

FSC:8040

NIIN:00-701-9514
MSDS Number: BFLXV
=== Responsible Party ===

Company Name: HYSOL DIV, DEXTER CORPORATION, DEXTER ELECTRONICS

Address:211 FRANKLIN STREET

City:OLEAN State:NY ZIP:14760 Country:US

Info P

hone Num:716-372-6300

Emergency Phone Num:716-372-6309 Preparer's Name:JAMES P. HORNBURG

CAGE:HO241

=== Contractor Identification ===

Company Name: DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV

Address:211 FRANKLIN ST.

Box:City:OLEAN

State:NY

ZIP:14760-1297 Country:US

Phone:716-372-6300/6309

CAGE:04347

Company Name: HYSOL DIV, DEXTER CORP, WORNOW PROD DIV

CAGE:HO241

======= Composition/Information on Ingredients ========

Ingred Name: DIETHYLENE TRIAMINE

CAS:111-40-0

RTECS #:IE1225000

Fraction by Wt: >10%. OSHA PEL:1 PPM ACGIH TLV:S, 1 PPM; 9192
========== Hazards Identification ===========
Effects of Overexposure:CAUSES SEVERE EYE & SKIN BURNS
======================================
First Aid:SKIN:WASH IMMEDIATELY W/SOAP & WATER.EYES:IMMEDIATELY FLUSH W/WATER AT LEAST 15 MIN.CALL MD.
======================================
Flash Point Method:COC Flash Point:215F,102C Extinguishing Medi a:WATER SPRAY,DRY CHEMICAL,"ALCOHOL"FOAM,CO*2 Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL PROT EQUIP.USE H*2O TO KEEP FIRE EXPO CNTNR COOL.H*2O SPRAY MAY BE USED TO FLUSH SPILL AWAY FROM EXPOSURE (SUPP DATA) Unusual Fire/Explosion Hazard:CARE MUST BE USED TO PREVENT IGNITION WHEN PROCESSING OR HANDLING AT TEMPS ABOVE THE FLASH POINT
======== Accidental Release Measures ==========
Spill Release Procedures:SMALL AMOUNTS CAN BE FLUSHED AWAY WITH
WATER.LARGER SPILLS SHOULD BE SCRAPED UP, TRANSFER TO A METAL CONTAINER.
======================================
Handling and Storage Precautions:PROTECT FROM PHYSICAL DAMAGE.STORE IN A COOL DRY WELL VENTILATED AREA AWAY FROM ACUTE FIRE HAZARD.STRONG SKIN SENSITIZER.AVOID SKIN CONTACT Other Precautions:WATER SPRAY MAY BE USED DURING FIRE TO FLUSH SPILLS AWAY FROM EXPOSURES AND TO DILUTE SPILLS TO NON FLAMMABLE MIXTURES
====== Exposure Contr

ols/Personal Protection =======

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATORY PROTECTION IF NECESSARY

Ventilation:DO NOT RECIRCULATE UNLESS SCRUBBED W/ACID

Protective Gloves:PLASTIC/RUBBER

Eye Protection: GOGGLES IF SPLASH LIKELY

Other Protective Equipment: USE OF PROTECTIVE SKIN CREAM IS RECOMMENDED

Supplemental Safety and Health

VAPOR PRESSURE: