

CON-LUX COATINGS, INC -- GREEN 14050, ENAMEL ALKYD GLOSS, COMP L -- 8010-00-753-4549

=====  
Product Identification  
=====

Product ID:GREEN 14050, ENAMEL ALKYD GLOSS, COMP L

MSDS Date:01/01/1987

FSC:8010

NIIN:00-753-4549

MSDS Number: BFMYP

=== Responsible Party ===

Company Name:CON-LUX COATINGS, INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

CAGE:6A064

=== Contract

or Identification ===

Company Name:CON-LUX COATINGS, INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:908-287-4000

CAGE:6A064

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 49.2%

OSHA PEL:100 PPM

Ingred Name:DRIERS

Fraction by Wt: 1.3%

=====  
Hazards Identification  
=====

Effects of Overexposure:INH:AN

ESTHETIC. IRRIT RESP TRACT OR ACUTE CNS  
DEPRSSN W/HDACHE,DIZ,UNCON OR COMA. SKIN & EYE:IRRIT.

=====  
First Aid Measures  
=====

First Aid:FUMES: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM & QUIET. CALL MD. SPLASH: EYES-FLUSH IMMEDIATELY W/LG AMT OF RUNNING WATER AT LEAST 15 MIN. SEE MD. SKIN-REMOVE W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING.

=====  
Fire Fighting Measures  
=====

Flash Point:105F TCC

Lower Limits:0.9

Upper Limits:6.0

Extinguishing Media:CO\*2, DRY CHEMICAL, OR FOAM. WATER SPRAY MAY BE INEFFECTIVE.

Fire Fighting Procedures:USE WATER TO COOL CL CONTAINERS. KEEP CANS TIGHTLY CLOSED.

Unusual Fire/Explosion Hazard:ISOLATE FROM IGNITION SOURCES. EXCESSIVE HEAT MAY EXPLODE CLOSED CANS. DO NOT APPLY TO HOT SURFACES.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES, ELECTRICAL, STATIC OR FRICTIONAL SPARKS). AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE W/INERT ABSORBENT & NON-SPARKING TOOLS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMPS. KEEP AWAY FROM OPEN FLAME, SPARKS.

Other Precautions:DO NOT TAKE INTERNALLY. GROUND CONTAINERS WHEN POURING. AVOID PROLONGED OR REPEATED CONTACT W/SKIN. DOT: FLAMMABLE.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:APPROVED CHEMICAL-MECHANICAL FILTER RESP

Ventilation:SUFFICIENT TO KEEP TLV BELOW ACCEPTABLE LIMIT

Protective Gloves:YES

Eye Protection:YES, FOR SPLASH

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT W/CONTAMINATED CLOTHING

Supplemental Safety and Health

PRODUCT CONTAINS 11.7% PIGMENTS, 37.8% VEHICLE.

=====  
Physical/Chemical Properties  
=====

HCC:F4

Boiling Pt:B.P. Text:315F

Vapor Pres:1

Vapor Density:4.70

Spec G

ravity:0.9800

Evaporation Rate & Reference:0.15 BUAC

Solubility in Water:NEGLIGIBLE

Appearance and Odor:MILD ALIPHATIC ODOR, CLEAR WATER-WHITE

Percent Volatiles by Volume:62.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:EMITS ACRID FUMES

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE IAW  
FED, STATE  
, LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to the

ir

particular situation.