View NSN Online: https://aerobasegroup.com/nsn/6810-00-879-6133 ROHM AND HAAS COMPANY -- AMBERLITE IR-120 PLUS (H)RESIN,CODE#69454 -- 6810-00-879-6133 Product ID:AMBERLITE IR-120 PLUS (H)RESIN,CODE#69454 MSDS Date:01/01/1987 FSC:6810 NIIN:00-879-6133 MSDS Number: BFTPH === Responsible Party === Company Name: ROHM AND HAAS COMPANY Emergency Phone Num:(215)592-3000 CAGE:77902 === Contractor Identification === Company Name: ROHM AND HAAS CO Address: 100 INDEPENDENCE MALL WEST Box:City:PHILADELPHIA State:PA ZIP:19106-2399 Country:US Phone:215-592-2521/215-592-3000 CAGE:77902 ======= Composition/Information on Ingredients ======== Ingred Name: ION EXCHANGE RESINS (CATION EXCHANGER) 46-51% Fraction by Wt: 48.5% ACGIH TLV:NOT SPECIFIED Effects of Overexposure: NONE SPECIFIED. MAY IRRITATE EYES AND SKIN. (FINE PARTICLES OF SAME MATERIAL HAS SHOWN CORNEAL DAMAG

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*20 FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

Autoignition Temp:Autoignition Temp Text:800F Extinguishing Media:CO*2,DRY CHEMICAL,WATER FOG Fire Fighting Procedu

Unusual Fire/Explosion Hazard:TOXIC COMBUSTION PRODUCTS INCLUDE SOJ*2,SO*3
======== Accidental Release Measures ==========
Spill Release Procedures:USE PROPER PERSONAL PROTECTION. SWEEP UP AND TRANSFER TO CONTAINERS FOR RECOVERY OR DISPOSAL.
============ Handling and Storage ============
Handling and Storage Precautions:STORE IN COOL DRY AREA.DO NOT HANDLE WITH HNO*3 AND OT HER STRONG OXIDIZING AGENTS,MAY CAUSE EXPLOSIVE-TYPE REACTIONS. Other Precautions:AVOID SKIN AND EYES CONTACT.
====== Exposure Controls/Personal Protection =======
Respiratory Protection:NO SPECIAL REQMNTS UNDER ORDINARY CONDITIONS/ADEQUATE VENT. Ventilation:NORMAL ROOM VENTILATION. Protective Gloves:IMPERVIOUS Eye Protection:CHEM SPLASH GOGGLES Other Protective Equipment:SAFETY SHOWER & EYE BATH Supplemental Safety and Health MSDS DATED 03/26/82
========= Phy sical/Chemical Properties ==========
HCC:N1 Boiling Pt:B.P. Text:U/K Vapor Pres:U/K Vapor Density:U/K Spec Gravity:1.26 Evaporation Rate & Description Rate & Descri

res:WEAR NIOSH/MSHA APPROVED SCBA FOR FIRES AND