

NORTON CHEMPLAST -- FLUOROGLIDE F.B.AEROSOL (FILM BONDING) -- 9150-00-903-6431

===== Product Identification =====

Product ID:FLUOROGLIDE F.B.AEROSOL (FILM BONDING)

MSDS Date:07/01/1987

FSC:9150

NIIN:00-903-6431

MSDS Number: BFVSX

=== Responsible Party ===

Company Name:NORTON CHEMPLAST

Address:150 DEY ROAD

City:WAYNE

State:NJ

ZIP:07470-4670

Country:US

Emergency Phone Num:201-696-4700

CAGE:18632

===

Contractor Identification ===

Company Name:NORTON PERFORMANCE PLASTICS CORP.

Address:150 DEY RD

Box:City:WAYNE

State:NJ

ZIP:07470-4670

Country:US

Phone:973-696-4700

CAGE:18632

===== Composition/Information on Ingredients =====

Ingred Name:ACRYLIC COPOLYMER 1-5%

Fraction by Wt: 3.0%

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: 88.0%

OSHA PEL:350 PPM/450 STEL

ACGIH TLV:350 PPM/450 STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS
Ozone Depleting Chemical:1

Ingred Name:FLUOROETELOMER MIXTURE; 5-7%,(CONTAINS
TRICHLOROTRIFLUOROETHANE,80-85% AND TELOMER OF TETRAFLUOROETHYLENE
15-20%)
CAS:22-57-5
Fraction by Wt: 6.0%

Ingred Name:CARBON DIOXIDE
CAS:124-38-9
RTECS #:FF6400000
Fraction by Wt: 3.0%
OSHA PEL:5000 PPM
ACGIH TLV:5000PPM/30000STEL;93

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF SINUS AND
EYES;ANESTHETIC AND NARCOTIC EFFECTS;CHRONIC:CORNEAL
INJURY, DRYING OF SKIN OR DERMATITIS, DIZZINESS, CARDIAC
IRREGULARITIES.
Effects of Overexposure:EYES:PAIN, IRRITATION, CORNEAL
INJURY. SKIN:IRRITATION, DRYING OF
SKIN, DERMATITIS. INHALATION;ANESTHETIC OR NARCOTIC
EFFECTS, DIZZINESS, NAUSEA, DRUNKENNESS. INGESTION:ORAL TOXICITY IS
LOW;AVOID TAKING INTERNAL LY.

===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O₂ IF
NEED;EYES/SKIN:FLUSH W LG AMTS H₂O FOR 15 MIN;INGEST:RINSE MOUTH;
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER
SYMPTOMS OF OVEREXPOSURE.

===== Fire Fighting Measures =====

Flash Point:NONE
Lower Limits:6.0
Upper Limits:16.7
Extinguishing Media:WATERFOG, CO₂, DRY CHEMICAL
Fire Fighting Procedures:USE NIOS/MSHA APPROVED SCBA IN AN ENCLOSED
AREA.
Unusual Fire/Explosion Hazard:THIS IS AN A

EROSOL PRODUCT;CONTENTS UNDER

PRESSURE,HEAT MAY CAUSE BURSTING;PRODUCT MAY ALSO DECOMPOSE UNDER
FIRE CONDITION.

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PRSONAL PROTECTION;REPLACE CAP AND
DISCARD FOR PROPER DISPOSAL.CONTAINERS MUST BE DEPRESSURIZED BEFORE
DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED
AREA.KEE

P BELOW 120F;WASH AFTER EACH USE.DO NOT SMOKE IN WORK AREA.

Other Precautions:FOLLOW LABEL DIRECTION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC
VAPOR/MIST.

Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN