

KALCOR COATINGS CO., INC -- V-7708,STAIN,DARK REDWOOD,TT-S-708A -- 8010-00-926-9130

===== Product Identification =====

Product ID:V-7708,STAIN,DARK REDWOOD,TT-S-708A

MSDS Date:01/01/1985

FSC:8010

NIIN:00-926-9130

MSDS Number: BFWYG

==== Responsible Party ====

Company Name:KALCOR COATINGS CO., INC

Address:37721 STEVENS BLVD

City:WILLOUGHBY

State:OH

ZIP:44094-6231

Country:US

CAGE:DO396

==== Contractor

Identification ===

Company Name:KALCOR COATING CO

Address:37721 STEVENS BLVD

Box:City:WILLOUGHBY

State:OH

ZIP:44094-6231

Country:US

Phone:216-946-4700

CAGE:33201

Company Name:KALCOR COATINGS COMPANY

Address:37721 STEVENS BLVD

City:WILLOUGHBY

State:OH

ZIP:44094

Phone:800-424-9300 CHEMTREC

CAGE:DO396

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 19.6%

OSHA PEL:100 PPM

Ingred

Name:PENTACHLOROPHENOL (SARA III)

CAS:87-86-5

RTECS #:SM6300000

Fraction by Wt: 4.8%

OSHA PEL:S, 0.5 MG/M3

ACGIH TLV:S, 0.5 MG/M3; 9192

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 4.8%

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:LINSEED OIL (64.5 MIN % BY WT)

CAS:8001-26-1

RTECS #:OI9690000

Ingred Name:IRON OXIDE

CAS:1309-37-1

RTECS #:NO7400000

OSHA PEL:10 MG/M3 (FE)

ACGIH TLV:5 MG/M3(F

E),B2; 9293

===== Hazards Identification =====

Effects of Overexposure:ACUTE:SKIN & EYE IRRITANT.CHRONIC:INGESTION OF MATERIAL CAN BE EXTREMELY HARMFUL.

===== First Aid Measures =====

First Aid:SKIN & EYE:FLUSH AFFECTED AREA W/PLENTY OF WATER FOR 15 MIN. IF INGESTED, DO NOT INDUCE VOMITING, CALL MD IMMEDIATELY.(ONLY UNDER MDS DIRECTIONS SHOULD VOMITING BE INDUCED.

===== Fire Fighting Measure

S =====

Flash Point:63F SCC

Extinguishing Media:CO₂, DRY CHEMICAL, FOAM

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCES OF IGNITION, USE DISPOSABLE ABSORBENT.CLEAN AS ANY PAINT

===== Handling and Storage =====

Handling and Storage Precautions:AVOID EXCESS HEAT, FLAMES & SPARKS

===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL VETILATION N

ECCESSARY

Protective Gloves:RECOMMENDED

Eye Protection:SAFETY GOGGLES OR GLASSES

Supplemental Safety and Health

ADD HAZ INGRED:MAGNESIUM SILICA(TALC),APPROX,14% & PARAFFIN WAX,MIN 2.6%.VAPOR DENS:HEAVIER THAN AIR.WT PER GALLON:7.95 LBS. DOT: FLAMMABLE LIQUID CLASS 1 B.

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:176-385F

Spec Gravity:0.9600

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NEGLIGIBLE

Appearance an

d Odor:REDDISH LIQUID/PETROLEUM SPIRITS ODOR

Percent Volatiles by Volume:29.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:EXCESS HEAT, SPARKS, OPEN FLAME

===== Disposal Considerations =====

Waste Disposal Methods:EPA APPROVED INCINERATION OR LANDFILL IF IN ACCORDANCE W/FED, STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.