

FILTRON CO. INC -- SP207 -- 5915-00-964-3683

===== Product Identification =====

Product ID:SP207

MSDS Date:01/01/1985

FSC:5915

NIIN:00-964-3683

MSDS Number: BFZMC

=== Responsible Party ===

Company Name:FILTRON CO. INC

Address:148 SWEET HOLLOW RD

City:OLD BETHPAGE

State:NY

ZIP:11804-1315

Country:US

Emergency Phone Num:914-699-2000

CAGE:JO771

=== Contractor Identification ===

Company Name:FILTRON CO INC

Address:148 SWEET HOLLOW RD

Box:City:OLD BETHPAGE

State:NY

ZIP:11804-1315

Country:US

Phone:914-699-2000

CAGE:81831

Company Name:FILTRON CO. INC

Address:148 SWEET HOLLOW RD

Box:City:OLD BETHPAGE

State:NY

ZIP:11804-1315

Country:US

CAGE:JO771

===== Composition/Information on Ingredients =====

Ingred Name:POLYCHLORINATED BIPHENYLS (PCBS) (SARA III)

CAS:1336-36-3

RTECS #:TQ1350000

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

===== Hazards Identification =====

Effects of Overexposure:INHAL:RESP TK IRRIT;  
SKIN/

EYE;IRRIT,INFLAM,CHLROACNE; MAY CAUSE LIVER DAMAGE.

===== First Aid Measures =====

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG,GIVE CPR; IF BRTHNG  
DIFF,GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH  
W/SOAP&WATER. RMV CONTAM CLTHG&SHOES. INGEST:INDUCE VOMIT.RPT UNTIL  
VOMIT IS CL EAR. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.

===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Me

dia:EXTINGUISH W. AGENT SUITABLE FOR SURROUNDING FIRE.

Fire Fighting Procedures:WEAR CHEMICAL PROTECTIVE SUIT WITH SELF CONTD  
BRTHG APP.

Unusual Fire/Explosion Hazard:MATL IS NON-FLAMMABLE BUT MAY GENERATE  
TOXIC GASES IN HEAT OF FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:EVAC NON-ESSENTL PERSONNEL. VENT SPIL AREA.  
WEAR PROTECT EQUIPT. STOP LEAK. SOAK UP LIQUID W/NON-REACTIVE MATL  
(SAND, DIRT, ETC) OR RMV BY DIKE & PUMPING  
OR OTHER SUITABLE MEANS.  
CLEAN AREA W/SUITABLE SAFETY SOLVENT. LAUNDER CONTAMINATED CLTHG.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED  
AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP  
CONTAINERS TIGHTLY CLOSED

Other Precautions:CHLORODIPHENYLS MAY ATTACK SOME TYPES OF RUBBER AND  
PLASTIC. DO NOT USE CONTAMINATED WORK CLOTHING. WASH/SHOWER AFTER  
EXPOSURE TO PCB'S.

=

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MESA APPR SCBA/AIR SUPP RESPIR.

Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES/FACE SHIELD

Other Protective Equipment:WEAR FULL PROTECTIVE CLOTHING.

Supplemental Safety and Health

OVEREXPOS:CAN CAUSE FORMATION OF CYSTS,CAUSES STILLBIRTHS.IRRITATES  
EYES,NOSE THROAT.

===== Physical/Chemical Properties =====

HCC:Z3

Sol

ubility in Water:NEGLIGIBLE

Appearance and Odor:PALE YELLOW VISCOUS LIQUID W/HYDROCARBON ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:SEE OTHER PRECAUTIONS

Hazardous Decomposition Products:HYDROGEN CHLORIDE, CO, & OTHER  
TOXIC/IRRITATING GASES/FUMES.

===== Disposal Considerations =====

Waste Disposal Methods:CONTROLLED DISPOSAL REQD.

GEN. V.HIGH TEMP

INCINERATION. IN ACCORDANCE WITH ALL LOCAL, STATE, & FEDERAL  
REGULATIONS. PERMITTED DISPOSAL OPERATOR REQUIRED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should se

ek competent professional advice to verify and

assume responsibility for the suitability of this information to their  
particular situation.