

L. B. ALLEN COMPANY INC -- E100 ALL SOL FLUX

=====
MSDS Safety Information
=====

FSC: 3439
NIIN: 00-964-5589
MSDS Date: 04/01/1991
MSDS Num: BFZMG
Product ID: E100 ALL SOL FLUX
MFN: 01
Responsible Party
Cage: EO560
Name: L. B. ALLEN COMPANY INC
Address: 725 NORTH CENTRAL AVENUE
City: WOOD DALE IL 60
191
Info Phone Number: 708-595-2600
Emergency Phone Number: 800-533-5053
Review Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: EO560
Name: L. B. ALLEN COMPANY, INC.
Address: UNKNOWN
City: UNKNOWN NK 00000
Phone: UNKNOWN
Cage: 70279
Name: L.B. ALLEN CO INC
Address: 725 N CENTRAL
City: WOODALE IL 60191-1240
Phone: 708-595-2600

=====
Item Description Information
=====

Item Name: FLUX,SOLDERING
=====

=====
Ingredients
=====

Cas: 7647-01-0
RTECS #: MW4025000
Name: HYDROCHLORIC ACID; (HCL) (HYDROGEN CHLORIDE) (SARA III)
% Wt: 35
OSHA PEL: 5 PPM, C
ACGIH TLV: 5 PPM, C
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS

Cas: 12125-02-9
RTECS #: BP4550000
Name: AMMONIUM

CHLORIDE (SARA III)

% Wt: 3

Other REC Limits: 1 PPM (MFR)

OSHA PEL: 10MG/M3;20STEL(FUME)

ACGIH TLV: 10MG/M3;20STEL(FUME)

EPA Rpt Qty: 5000 LBS

DOT Rpt Qty: 5000 LBS

Cas: 7646-85-7

RTECS #: ZH1400000

Name: ZINC CHLORIDE (SARA III) (LIMITS GIVEN FOR ZN CHLORIDE FUME)

% Wt: 31

OSHA PEL: 1 MG/M3/2 STEL

ACGIH TLV: 1 MG/M3/2STEL FUME93

EPA Rpt Qty: 1000 LBS

DOT Rpt Qty: 1000 LBS

=====
Health Hazards Data

=====
LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: BURNING OR BITING SENSATION ON SKIN, COUGHING, IRRITATION OF EYES OR THROAT.

Explanation Of Carcinogenicity: NOT RELEVANT.

Signs And Symptoms Of Overexposure: SEE HEALTH HAZARDS.

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid: SKIN/MUCOUS M

EMBRANE:FLUSH W/LARGE AMOUNTS OF WATER & PAT ON

SODIUM BICARBONATE (BAKING SODA). INHAL:REMOVE TO ADEQUATE VENTILATION &

CALL MD. EYES:FLUSH W/POTABLE WATER FOR AT LEAST 15 MINS. GET MEDIC AL

ATTENTION (FP N). INGEST:GIVE A TEASPOON OF MILK OF MAGNESIA OR TAKE MILK OR

WATER IN LARGE AMOUNTS & CALL MD.

=====
Handling and Disposal

=====
Spill Release Procedures: FLUSH WITH LARGE A

MOUNTS OF H*20 IF PRODUCT IS

SPILLED. AVOID BREATHING VAPORS OR CONTACT WITH SKIN.

Neutralizing Agent: SODA ASH OR LIMESTONE.

Waste Disposal Methods: NEUTRALIZE W/SODA ASH OR LIMESTONE & FLUSH W/ADEQUATE AMOUNTS OF WATER. DISPOSAL MUST BE IN ACCORDANCE W/FEDERAL, STATE & LOCAL REGULATIONS (FP N).

Handling And Storage Precautions: STORE IN PLASTIC LINED DRUMS OR GLASS BOTTLES. KEEP FROM EXCESSIVE HEAT IN WELL VENTILATED ROOM.

Other Precautions: AVOID CONTACT W/SKIN, EYES & CLOTHING. KEEP OUT OF CHILDREN'S REACH.

=====
Fire and Explosion Hazard Information
=====

Flash Point Text: NONE

Extinguishing Media: FOAM OR BICARBONATE OF SODA, COPIOUS AMOUNTS OF WATER.

Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT (FP N). FLOOD W/WATER. KEEP GOOD VENTILATION AT ALL TIMES.

Unusual Fire/Explosion Hazard: PRODUCT PRODUCES IRRITATING TOXIC FUMES & BURNS TO SKIN OR TISSUE.

=====
Control Measures
=====

Respiratory Protection: NIOSH/MSHA ACID TYPE OR OXYGEN MASK.

Ventilation: MECHANICAL VENTILATION (GOOD FAN)RECOMMENDED.

Protective Gloves: RUBBER

Eye Protection: CHEM WORK GOG & FULL LENGH FCSHLD (FP N)

Other Protective Equipment: RUBBER APRON OR JACKET & BOOTS.

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Suppleme

ntal Safety and Health: NONE SPECIFIED BY MANUFACTURER.
=====

Physical/Chemical Properties
=====

B.P. Text: >228F,>109C

Spec Gravity: 0.908 (H*2O=1)

Evaporation Rate & Reference: >1 (ETHER=1)

Solubility in Water: SOLUBLE

Appearance and Odor: STRONGLY ACIDIC ODOR, GREENISH LIQUID.

Percent Volatiles by Volume: 52
=====

Reactivity Data
====

Stability Indicator: YES
Stability Condition To Avoid: OVERHEATING OR USE IN UNVENTILATED AREAS.
Materials To Avoid: AVOID REACTION W/STRONG ALKALIES, CHLORINE TYPE BLEACHES OR OTHER HOUSEHOLD CHEMICALS.
Hazardous Decomposition Products: PRODUCES STRONG ACIDS ON DECOMPOSITION.
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: NOT RELEVANT.

Toxicological Information

Ecological Information

MSDS Transport Information

Regulatory Information

Other Information

Transportation Information

Responsible Party Code: EO560
Trans ID NO: 95127
Product ID: E100 ALL SOL FLUX
MSDS Prepared Date: 04/01/1991
Review Date: 10/19/1984
MFN: 1
Multiple KIT Number: 0
Review IND: Y
Additional Data: NOT REGULATED FOR SHIPPING.

Detail DOT Information

DOT PSN Code: ZZZ
DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Detail IMO Information

IMO PSN Code: ZZZ
IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

Detail IATA Information

=====
IATA PSN Code: ZZZ
IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

Detail AFI Information

=====
AFI PSN Code: ZZZ
AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

HAZCOM Label

=====
Prod
uct ID: E100 ALL SOL FLUX
Cage: EO560
Assigned IND: Y
Company Name: L. B. ALLEN COMPANY, INC.
Street: UNKNOWN
City: UNKNOWN NK
Zipcode: 00000
Health Emergency Phone: 800-533-5053
Label Required IND: Y
Date Of Label Review: 01/19/1993
Status Code: C
Label Date: 01/19/1993
Origination Code: G
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: DANGER
Respiratory Protection IND: YES
Health Hazard: Moderate
Contact Hazard: Severe
Fire Hazard: None
Reactivity Hazard: None
Hazard And Precautions: AVOID ALKALIES, CHLORINE TYPE BLEACHES AND OTHER
HOUSEHOLD CHEMICALS. ACUTE: BURNING OR BITING SENSATION ON SKIN, COUGHING,
IRRITATION OF EYES OR THROAT. HARMFUL OR FATAL IF SWALLOWED. CAN CAUSE SEVE
RE BURNS. VAPORS HARMFUL. CHRONIC: NONELISTED BY MANUFACTURER.
=====

Disclaimer (provided with this information by the compiling agencies): This
information is formulated for use by elements of the Department of Defense.
The United S

tates of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.