View NSN Online: https://aerobasegroup.com/nsn/9150-00-964-9228

ELECTROFILM,INC. -- LUBE-LOK 2396 CONCENTRATE -- 9150-00-964-9228

Product ID:LUBE-LOK 2396 CONCENTRATE MSDS Date:01/01/1987 FSC:9150 NIIN:00-964-9228 **MSDS Number: BFZNB** === Responsible Party === Company Name: ELECTROFILM, INC. Emergency Phone Num:805-257-2240 CAGE:HO291 === Contractor Identification === Company Name: ELECTROFILM MFG CO Address:27727 AVE SCOTT Box:5 5669 **City:VALENCIA** State:CA ZIP:91355 Country:US Phone:805-257-2242 CAGE:85932 Company Name: ELECTROFILM, INC. Address:27727 AVE SCOTT Box:55669 **City:VALENCIA** State:CA ZIP:91355 Country:US CAGE:HO291

Ingred Name:MOLYBDENUM DISULFIDE AND GRAPHITE MIXTURE (TLV AS MO,INSOLUBLE COMPOUNDS) Fraction by Wt: 40.0% ACGIH TLV:10MG/CUM

Ingred Name:SODIUM SILICATE, CAS #6834-92-0 CAS:6834-92-0 RTECS #:VV9275000 Fraction by Wt: 10.0% A

CGIH TLV:10MG/CUM (MFR)
Ingred Name:WATER, CAS #7732-18-5 CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 50.0%
======================================
Effects of Overexposure:IRRITATION OF EYES AND SKIN;MAY ALSO IRRITATE RESPIRATORY TRACT.
======================================
First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*20 FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION F OR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.
======================================
Extinguishing Media:USE ANY MEDIA SUITABLE FOR SURROUNDING FIRES Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED AREA
Unusual Fire/Explosion Hazard:NONE NOTED BY THE MFR
======================================
Spill Release Procedures:WIPE UP & WASH WITH WATER
e ====================================
Handling and Storage Precautions:STORE IN COOL,DRY AREA.KEEP CONTAINER CLOSED WHEN NOT IN USE. Other Precautions:AVOID CONTACT WITH SKIN AND EYES;DO NOT INHALE DUST/MIST.WASH THOROUGHLY AFTER EACH USE.
======================================
Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR DUST/MIST IF ABOVE TLV

Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN