

EASTMAN KODAK COMPANY -- 186 2804,VERSMAT FIXER & REPL,TYPE A,PART A --
6750-00-965-4580

===== Product Identification =====

Product ID:186 2804,VERSMAT FIXER & REPL,TYPE A,PART A

MSDS Date:08/05/1982

FSC:6750

NIIN:00-965-4580

MSDS Number: BFZTF

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE ST

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:NEAREST KODAK

MARKET & DISTRIB CTR

Emergency Phone Num:(716)-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 40-50%

Ingred Name:AMMONIUM THIOSULFATE

CAS:7783-18-8

RTECS #:XN6465000

Fraction

by Wt: 40-50%

Ingred Name:SODIUM METABISULFITE

CAS:7681-57-4

RTECS #:UX8225000

Fraction by Wt: 5-10%

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3; 9192

===== Hazards Identification =====

Effects of Overexposure:NONE NOTED BY MFR. LOW TOXICITY & LOW HAZARD TO HEALTH.

===== First Aid Measures =====

First Aid:SKIN:WASH WITH SOAP AND WATER. EYES: FLUSH WITH WATER.
INHALED: REMOVE TO FRESH AIR. REMOVE CONTAMINATED CLOTHING.

=

===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE

Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL CONTR.

Unusual Fire/Explosion Hazard:NONE NOTED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:NEUTRALIZE WITH SODIUM BICARBONATE. FLUSH WITH COPIOUS AMOUNTS OF WATER. OBSERVE LOCAL, STATE & FEDERAL

REGULATIONS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED

AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED

Other Precautions:NOT KNOWN

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED.

Ventilation:GEN MECHANICAL RECOMMENDED.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES

Ot

her Protective Equipment:FOLLOW GOOD INDUSTRIAL HYGIENE PRACTICES.
Supplemental Safety and Health
THIS IS PART A OF A 2-PART PRODUCT. SEE PNIB B FOR OTHER PART. SOLN NR
4333.

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:>212F/>100C
Vapor Pres:17
Vapor Density:0.6
Spec Gravity:1.34
pH:5.3
Solubility in Water:COMPLETE
Appearance and Odor:CLEAR, COLORLESS, VINEGAR ODOR
Percent Volatiles by Volume:45

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID MINERAL ACIDS AND STRONG ALKALI
Stability Condition to Avoid:EXCESSIVE HEAT
Hazardous Decomposition Products:SULFUR DIOXIDE - AMMONIA

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE, LANDFILL, OR FOLLOW ABOVE STEPS.
OBSERVE LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.