View NSN Online: https://aerobasegroup.jp/nsn/6750-01-064-7321

EASTMAN KODAK COMPANY -- 180 3972, MICROFILM BLEACH & REPLENISHER -- 6750-01-064-7321

Product ID:180 3972, MICROFILM BLEACH & REPLENISHER MSDS Date:01/01/1985 FSC:6750 NIIN:01-064-7321 **MSDS Number: BGJYR** === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET **City:ROCHESTER** State:NY ZIP:14650 Country:US Info Phone Num:716-722-5151 Emer gency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139

Ingred Name:SULFAMIC ACID(15-20%) (CAS #5329-14-6) CAS:5329-14-6 RTECS #:WO5950000 Fraction by Wt: 17.5%

Ingred Name:POTASSIUM BICHROMATE (SARA III) CAS:7778-50-9 RTECS #:HX7 680000 Fraction by Wt: 7.5% OSHA PEL:C,0.1 MG/M3 CRO3 ACGIH TLV:0.5 MG CR/M3; 9293 EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS

Ingred Name:AQUEOUS SOLUTION,HAZARD UNKNOWN,UNIDENTIFIED(70-80%) Fraction by Wt: 75.0%

Effects of Overexposure:EYES:LIQD CONTACT CAN CAUSE BURNS;SKIN:PROLNGD/REPEATD CONTACT MAY CAUSE BURNS/ALLERGIC REACTION.

First Aid:EYES OR S KIN:IMMEDIATELY FLUSH SKIN OR EYES W/PLENTY OF WATER FOR 15 MIN & GET MED ATTN FOR EYES;INH:IF DIFFICULT IN BREATHING,REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF NEEDED & GET MED ATTN.

Flash Point:NONE Lower Limits:NONE Upper Limits:NONE Extinguishing Media:CO*2,FOAM,DRY CHEM Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP;COOL EXPSD CONTNRS W/WATER SPRAY Unusual Fire/Explosion Hazard:SPILL/RUNOFF MAY CAUSE POLL UTION,FIRE &/OR EXPLOSION HAZARDS;EXPOSED CONTNRS MAY EXPLODE IN FIRE.

Spill Release Procedures: ELIM IGN SOURCES. USE PROTECTV EQUIP, PROVIDE VENT.STOP LEAK W/O RISK. DIKE LG SPILL & PUMP INTO COVRD DRUMS; ABSORB/CONTAIN SMALL SPILL IN CONTNR PENDING DISPOSL; MFR RECOMMENDS, NEUTRLZ W/SOD BICARBONATE THEN FLUSH TO SEWER W/LG AMT H*20 IAW EXISTG REGS.

Handling and Storage Precautions: STORE IN COOL, DRY, WELL VENTILATED AREA.KEEP CONTNRS TIGHTLY CLOSED.PROTECT CONTNRS FROM PHYSICAL DAMAGE. Other Precautions: AVOID PROLONGED/REPEATED CONTACT W/PRODUCT; REMOVE & WASH CONTAMINATED CLOTHING.WASH HANDS AFTER USE; APPROX PH OF PRODUCT:0.7; UNIT CONTNR QTY 5 GAL IS TO MAKE 20 GAL WORKING SOLN. Respiratory Protection: NONE REQD IN NORMAL CONDITIONS Ventilation:MECHA NICAL(GEN) IF NEEDED Protective Gloves: IMPERVIOUS Eye Protection: SAFETY GLASSES Other Protective Equipment: AS NECESSARY TO PREVENT SKIN CONTACT. Supplemental Safety and Health MSDS FM MFR DTD:2/21/78;REISSUED:3/79:PER MFR LTR 8/18/82,RECORDAK MICROFILM BLEACH/REPLNSHR WAS RENAMED "KODAK MICROFILM BLEACH & REPLENISHER"(DATE UNKNOWN)PROBABLY BEFORE 2/78;SEE ADDL DATA. HCC:C1 Boiling Pt:B.P. Text:>212 F Vapor Pres:17 Vap or Density:0.6 Spec Gravity:1.14 Solubility in Water:COMPLETE Appearance and Odor:REDDISH-BROWN; ODORLESS Percent Volatiles by Volume:85. Stability Indicator/Materials to Avoid:YES BASES(CAUSTICS), FLAMMABLE LIQUIDS, OXIDIZERS Stability Condition to Avoid:UNK Hazardous Decomposition Products:NONE Waste Disposal Methods: KEEP IN COVERD CONTNRS PENDING DISPOSAL.

SHIP

WASTE TO NEUTRALZNG/DISPOSAL AREA IAW DOT/EPA REGS.HANDLE/DISPOSE OF IAW FED,STATE/LOCAL REGS;MFR SUGGESTS:NEUTRALZ W/SODIUM BICARBONATE THEN FLUSH TO SEWE R W/LG AMT H*20.FED STATE/LOCAL LAWS TAKE PRECEDEN

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accura te and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.