JEFCO LABORATORIES, INC. -- JEFCIDE 114 -- 6840-01-104-0780 Product ID:JEFCIDE 114 MSDS Date:01/01/1987 FSC:6840 NIIN:01-104-0780 MSDS Number: BGLYL === Responsible Party === Company Name: JEFCO LABORATORIES, INC. Emergency Phone Num:312-398-7392 CAGE:67031 === Contractor Identification === Company Name: JEFCO LABORATORIES INC Address:6000 S OAK PARK AVE Box:City:CHICAGO State:IL ZIP:60638-4012 Country:US Phone:312-586-1000 CAGE: 67031 ======= Composition/Information on Ingredients ======== Ingred Name: PYRETHRUM (SARA III) CAS:8003-34-7 RTECS #:UR4200000 Fraction by Wt: 3% OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3; 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB Ingred Name:PIPERONYL BUTOXIDE(CAS#51-03-6).LD50=6150MG/KG-TAT. CAS:51-03-6 RTECS #:XS8050000 Fraction by Wt: 6%

Ingred Name: N-OCTYL BICYCLOHEPTENE

DICARBOXIMIDE(CAS#113-48-4),LD50=2800MG/KG-RAT.

CAS:463-04-7

RTECS #:RB8575000 Fraction by Wt: 10%

Ingred Na

Fraction by Wt: 81%
OSHA PEL:400 PPM ACGIH TLV:400 PPM; 8990
======================================
First Aid:TREAT ESSENTIALLY AS FOR KEROSENE POISONING,IN MILD CASE OF INGESTION,NO ACTIVE MEASURES.SEVERE CASES,AVOID REGURGITATED OIL IN LUNGS(EMESIS).GIVE CAREFUL GASTRIC LAVAGE.
======================================
Flash Point:170F/77C (O .C)
Extinguishing Media:CO*2 FOAM OR POWDER EXTINGUISHER OR SAND Fire Fighting Procedures:USE SCBA IN FIRES AND IN CONFINED AREA WITH FULL PROTECTION.
Unusual Fire/Explosion Hazard:COMBUSTIBLE LIQUID,KEEP CONTAINER COOL TO PREVENT EXPLOSIVE IGNITION.
======== Accidental Release Measures =========
Spill Release Procedures:SOAK UP SPILLAGE WITH ABSORBENT MATERIALS,SUCH AS SAWDUST,COTTON WASTE DIATOMITE.
========== Handling and Storage ========
======
Handling and Storage Precautions:IF SPILLED ON SKIN,WASH WITH SOAP & WATER.STORE & HANDLE AWAY FROM NAKED FLAMES. Other Precautions:IF SPLASHED IN EYES,WASH WITH SOAP & WATER & ISOTONIC SOLUTION.OTHERWISE, NO SPECIAL PRECAUTIONS.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NONE Ventilation:LOCAL EXHAUST Protective Gloves:OIL RESISTANT Eye Protection:LIGHT INDUSTRIAL GOGGLES Other Protective Equipment:NONE Supplemental Safety and

me:PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT)

CAS:8002-05-9

RTECS #:SE7449000

UPDATE PER UNDATED NON-OSHA MSDS RECD 14NOV86.
======================================
HCC:T4 Spec Gravity:0.8213 Solubility in Water:NEGLIGIBLE Appearance and Odor:YELLOWISH COLOR-PLEASANT ODOR
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES NONE Stability Condition to Avoid:NONE Hazardous Decomposition Products:NONE
====== Disposal Considerations ==========
Waste D isposal Methods: INCINERATION IAW FEDERAL STATE & LOCAL REGS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for th

e suitability of this information to their particular situation.

Health