

EASTMAN KODAK COMPANY -- 159 7350,FLEXCLR AR DEVLPR REPLNSHR,PART B --
6750-01-145-7833

===== Product Identification =====

Product ID:159 7350,FLEXCLR AR DEVLPR REPLNSHR,PART B

MSDS Date:07/30/1983

FSC:6750

NIIN:01-145-7833

MSDS Number: BGNWF

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Emergency Phone Num:716-72

2-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:HYDROXYLAMINE SULFATE (DISSOCIATES TO SULFURIC ACID IN
WATER)

CAS:10039-54-0

RTECS #:NC5425000

Fraction by Wt: 20-25%

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by W

t: 75-80%

===== Hazards Identification =====

Effects of Overexposure:EYES:LIQUID IRRITATES;SKIN:MAY IRRITATE,REPEATED CONTACT MAY CAUSE ALLERGIC SKIN REACTION.

===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR,GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH;GET MEDICAL ATTENTION FOR EYES OR OVEREXPOSURE.

===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:NON FLAMMABLE:USE MEDIA SUITABLE FOR SURROUNDING FIRE
Fire Fighting Procedures:SELF-CNTND BRTHG APP;H*2O SPRAY COOL CONT.
Unusual Fire/Explosion Hazard:CONTAINERS MAY RUPTURE IN HEAT OF FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS.DO NOT TOUCH SPILLED MATERIAL.WEAR PROTECTIVE EQUIPMENT.STOP LEAK IF POSSIBLE WITHOUT RISK.ABSORB WITH COMMERCIAL ABSORBENT,PUT IN APPR CONTAINERS;LG SPILL:CONTAIN W DIKE, TRANSFER TO APPR CONT.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA.KEEP CONTAINERS TIGHTLY CLOSED.PROTECT FROM PHYSICAL DAMAGE.
Other Precautions:MAINTAIN STANDARD HYGIENE FOR CHEMICAL HANDLING.MFG NOTES THAT TOXIC AMOUNTS MAY BE ABSORBED THRU SKIN:ALWAYS WASH THOROUGHLY AFTER HANDLING,USE NON-ALKALINE(ACID) HAND CLEANER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQUIREMENTS.
Ventilation:NO SPECIAL REQUIREMENTS
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY/CHEM GOGGLES
Other Protective Equipment:NO SPECIAL REQUIREMENTS,EXCEPT TO PREVENT SKIN CONTACT.
Supplemental Safety and Health
MSDS FROM MFR DATED:30JUL83;THIS DESCRIBES PART B OF 3 PART PROD(PART A:CAT #159 7335,NSN 6750011784698; PART C: CAT #159 7376,NSN 6750011447792); PH IS APPROX: 3.2

===== Physical/Chemical Properties =====

HCC:C1

Boiling Pt:B.P. Text:>212F,>100C

Vapor Pres:17

Vapor Density:0.6

Spec Gravity:1.16

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR AQUEOUS MIXTURE;ODORLESS

Percent Volatiles by Volume:75%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ALKALI

Stability Condition to Avoid:NONE NOTED

Hazardous Decomposition Products:AMMONIA, OXIDES OF S & N M

AY BE EMPTTD

BY THRML DECOMPOSTION

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED CONTAINERS PENDING

DISPOSAL.HANDLE AND DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE
INTERNATIONAL,FEDERAL,STATE AND LOCAL REGULATIONS.MFG SUGGESTS
FLUSHING TO SEWER WITH EXCESS OF WA TER.AFTER NEUTRALIZE W SODIUM
BICARBONATE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for

use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.