View NSN Online: https://aerobasegroup.jp/nsn/6750-01-214-4621

Product ID:186 2176, EKTPRNT 2 BLEACH-FIX, PART B MSDS Date:08/01/1988 FSC:6750 NIIN:01-214-4621 Kit Part:Y **MSDS Number: BGQSL** === Responsible Party === Company Name: EASTMAN KODAK CO. Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country:US Info Phone Num:716-722-5151 Emerg ency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 Ingred Name: AMMONIUM FERRIC ETHLYENEDIAMINETETRAACETIC ACID CAS:21265-50-9 Fraction by Wt: 40-45%

Ingred Name:AMMONIA (SARA III) CAS:7664-41-7 RTECS #:BO0875000 Fraction by Wt : 6% OSHA PEL:50 PPM ACGIH TLV:25 PPM/35 STEL; 9293 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

Ingred Name:ETHYLENEDIAMINE-TETRAACETIC ACID (EDTA) (SARA III) CAS:60-00-4 RTECS #:AH4025000 Fraction by Wt: 1-5% EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 45-55%

W/WATER 15 MIN, HOLD LIDS OPEN. SKIN:WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. INHALED:REMOVE TO FRESH AI R. INGESTED:DO NOT INDUCE VOMITING. GIVE 2 LARGE GLASSES OF MILK OR WATER AND GET IMMEDIATE MEDICAL CARE. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. IF IRRITATION PERSISTS OR IS SEVERE,SEE A DOCTOR.

Flash Point:NONE Extinguishing Media:USE EXTINGUISHING MEDI

A SUITABLE FOR SURROUNDING FIRES.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.
======================================
 Spill Release Procedures:EVACUATE UNPROTECTED PERSONS,PROVIDE VENTILATION, SAFE TY EQUIPMENTS IF NECESSARY.DIKE LARGE SPILL & PUMP INTO COVERED CONTNRS;ABSORB SM SPILL W/ABSORBING MATL & PLACE IN SAME CONTNR;MFR SUGGESTS FLUSH DOWN TO SEWER W/LG AMT OF H*20 IAW EXISTING REGS. Neutralizing Agent:NONE
======================================
 Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA.KEEP CONTNRS TIGHTLY CLOSED.PROTECT CONTNRS FROM PHYSICAL DAMAGE. Other Precautions:AVOID PROLONGED AND REPEATED SKI N CONTACT WITH PRODUCT. REMOVE & WASH CONTAMINATED CLOTHING. WASH HANDS AFTER USE.
======================================
Respiratory Protection:NONE NORMALLY NECESSARY. USE NIOSH/MSHA RESPIRATOR FOR ALKALINE FUMES IF EXPOSED ABOVE THE TLV. Ventilation:NORMAL ROOM VENTILATION IS SUFFICIENT. USE LOCAL EXHAUST IF AMMONIA ODORS BECOME IRRITATING. Protective Gloves:IMPERVIOUS/RUBR Eye Protection:SAFETY GLASSES/GOGGLES Other Protective Equipment:AS NECESSA RY TO PREVENT SKIN CONTACT Work Hygienic Practices:USE GOOD CHEMICAL HYGIENE PRACTICE. AVOID UNNECESSARY CONTACT. Supplemental Safety and Health ITEM HAS SEVEN PARTS IN THE KIT.THIS PART IS EKTAPRINT BLEACH-FIX, PART B WHICH MAY BE MARKED WITH CAT #186 5849. BUT CAT #186 2176 IS FOR THE KIT; THIS NSN IS DUPLICATE OF 6750-01-068-0727, SAME CAT & SOLUTION NO; YIELDS 1 GAL; MSDS OF CAT # 186 5849 IS USED FOR KIT. SOLUTION NUMBER= 3422; KEY1:N1.

====== Physical/Che

HCC:C1 Boiling Pt:B.P. Text:>212F/>100C Vapor Pres:18 MM Vapor Density:0.6 Spec Gravity:1.29 pH:7.0 Solubility in Water:COMPLETE Appearance and Odor:OPAQUE;REDDISH-BROWN;AMMONIACAL ODOR Percent Volatiles by Volume:55%

Stability Indicator/Materials to Avoid:YES METALS,STRONG OXIDIZING AGENTS Stability Condition to Avoid:HEAT,HIGH TEMPERATURES Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE, AMMONIA, NITROGEN OXIDES

Waste Disposal Methods:KEEP IN COVERED CONTAINERS PENDING DISPOSAL.DISPOSE IN FULL COMPLIANCE W/FEDERAL,STATE & LOCAL REGS;MFR RECOMMENDS TO FLUSH DOWN TO SEWER W COPIOUS AMT H*20.STATE & LOCAL EFFLUENT LAWS TAKE PRECEDENCE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department o

f Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.