

MAGNAFLUX CORPORATION -- ZL-22D ZYGLO PENETRANT -- 6850-01-268-8788

===== Product Identification =====

Product ID:ZL-22D ZYGLO PENETRANT
MSDS Date:11/17/1986
FSC:6850
NIIN:01-268-8788
Kit Part:Y
MSDS Number: BGSFW
=== Responsible Party ===
Company Name:MAGNAFLUX CORPORATION
Address:7300 W. LAWRENCE AVENUE
City:CHICAGO
State:IL
ZIP:60656-3504
Country:US
Info Phone Num:312-867-8000
Emergency Phone Number:312-867-8000
Preparer's Name:BRUCE C. GRAHAM
CAGE:37676
=== Contractor Identification ===
Company Name:ILLINOIS TOOL WORKS INC MAGNAFLUX DIV
Address:3624 WEST LAKE AVENUE
Box:City:GLENVIEW
State:IL
ZIP:60025
Country:US
Phone:847-657-5300/
CAGE:37676

===== Composition/Information on Ingredients =====

Ingred Name:DISTILLATES,(PETROLEUM)HYDROTREATED MIDDLE
CAS:64742-46-7
RTECS #:JN9379645
Fraction by Wt: 25.0%

Ingred Name:KEROSENE
CAS:8008-20-6
RTECS #:OA5500000
Fraction by

Wt: 10.0%
ACGIH TLV:100MG/CUM

Ingred Name:DISTILATES(PETROLEUM),CATALYTIC REFORMER FRACTIONATER
RESIDUE,LOW BOILING.
CAS:68477-31-6
Fraction by Wt: 20.0%

Ingred Name:UNIDENTIFIED COMPONENTS
Fraction by Wt: 45.0%

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:IRRITATES EYES,MILDLY.
Effects of Overexposure:INHALATION:SPRAY MIST MAY IRRITATE TO BREATHING
PASSAGES; EYES:LIQUID CONTACT MAY CAUSE IRRITATION; SKIN:SOLVENT IN
THE PRODUCT MAY IRRITATE SKIN; INGESTION:NOT NOTED BY MANUFACTURER.
Medical Cond Aggravated by Exposure:NOT STATED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR.IF BREATHING IS DIFFICULT,GIVE
OXYGEN; SKIN:REMOVE CONTAMINATED CLOTHES.WASH OFF WITH FLOWING
WATER.USE SOOTHING LOTION.IF IRRITATION PERSISTS,GET MEDICAL ATTN;
EYES:IMMEDIATELY RINSE/FLUSH WITH COPIOUS AMOUNT OF RUNNING
WATER,AND GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:>200F/>93C
Extinguishing Media:CARBON DIOXIDE,FOAM.
Fire Fighting Procedures:KEEP CONTAINERS COOL WITH WATER SPRAY.DO NOT
SPRAY ON BURNING PRODUCT.
Unusual Fire/Explosion Hazard:WHEN INVOLVE IN COMBUSTION,MAY EMIT TOXIC
GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.

===== Accidental Release Measures ===

=====

Spill Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB LIQUID WITH COMMERCIAL ABSORBENT.T.TRANSFER WASTE MATERIAL IN SALVAGE TANKS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES IN WELL VENTILATED AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:DO NOT BREATHE VAPORS.DO NOT SMOKE WHILE USING.DO NOT HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A RESPIRATOR WITH CHEMICAL CARTRIDGE. IN CONFINED AREAS,WEAR A FULL MASK WITH SEPARATE AIR SUPPLY.

Ventilation:GENERAL VENTILATION TO KEEP BELOW 350PPM LIMIT.

Protective Gloves:NITRILE RUBBER GLOVES.

Eye Protection:FULL

GOGGLES.WHEN SPRAYING OR POURING.

Other Protective Equipment:EITHER USE IN A SPRAY BOOTH OR NEXT TO AN EXHAUST VENT.

Work Hygienic Practices:WASH OFF PROMPTLY WITH WATER.AVOID SKIN CONTACT.

Supplemental Safety and Health

PER QPL-25135-15 OF MIL-I-25135D,THE SET MAY CONSIST OF ZL-22D OR ZL-27A PENETRANT AND ZE-3 OR ZE-4B EMULSIFIER UNDER TYPE I METHOD B,LEVEL 3;THIS NSN HAS 2 PARTS IN THE SET;THESE EMULSIFIERS & PENETRANTS ARE ALSO QUALIFIED PRODUCTS OF OTHER TYPES,METHODS &

LEVELS.SEE THE QPL;THIS ENTRY OF ZL-22D PENETRANT;KEY1:N1.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:410F/210C

Vapor Pres:0.5@100F

Vapor Density:>1.0

Spec Gravity:0.95

Solubility in Water:NEGLIGIBLE

Appearance and Odor:GREEN LIQUID WITH PETROLEUM DISTILLATE ODOR.

Percent Volatiles by Volume:5.0%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

MFR STATED "NONE".

Stability Con

dition to Avoid:HEAT,HIGH TEMPERATURES.

Hazardous Decomposition Products:EMITS OXIDES OF CARBON AND NITROGEN ON COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE D001 (IGNITABLE WASTE),IN ACCORDANCE WITH ALL APPLICABLE FEDERAL,STATE,LOCAL REGULATIONS;IF LOCAL AUTHORIES PROHIBIT DUMPING RINSINGS DOWN THE SEWER,PUR IFY RINSINGS W/MAGNAFLUX WASTEWATER TREATMNT SYSTM

Disclaime

r (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.