Box:847 City:EDISON State:NJ

ZIP:08818-0847

CAGE:60189

Box:847 City:EDISON State:NJ

=== Contractor Ide ntification ===

ZIP:08818-0847 Country:US

CAGE:60189

CAS:64742-47-8 Fraction by Wt: >1%

Reports

OSHA PEL:100 PPM

Other REC Limits:300 PPM (MFR)

Phone:732-287-4000

Info Phone Num:(201) 287-4000

Address: 226 TALMADGE RD

Emergency Phone Num:(201) 287-4000

Company Name: CON-LUX COATINGS INC

======= Composition/Information on Ingredients ========

========== Hazards Identification ===============

Ingred Name: HYDROTREATED LIGHT DISTILLATE, PETROLEUM

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:IRRITATION OF EYES AND SKIN MAY OCCUR WITH OVEREXPOSURE. CONTINUED BREATHING OF VAPORS MAY IRRITATE RESPIRATORY TRACT CAUSING HEADACHE, NAUSEA & DIZZINESS.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION OF EYES AND SKIN MAY OCCUR WITH OVEREXPOSURE. CONTINUED BREATHING OF VAPORS MAY IRRITATE RESPIRATORY TRACT CAUSING HEADACHE, NAUSEA & DIZZINESS.

First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE RESPIRATORY IF NECESSARY. TREAT SYMPTOMATICALLY. EYE: FLUSH W/COPIOUS QUANTITIES OF WATER FOR 15 MINS. CONSULT PHYSICIAN. SKIN: WASH AFFECTED AREAS W/SOAP & WA TER. REMOVE CONTAMINATED CLOTHING. CONSULT PHYSICIAN IF IRRITATION PERSISTS. INGESTION: DRINK 1 OR 2 GLASSES OF WATER. DON'T INDUCE VOMITING. CONSULT PHYSICIAN IMMEDIATELY.

 Fire Fighting Measures	=======

Flash Point Method:TCC

Flash Point:105F Lower Limits:1.0%

Extinguishing Media: FOAM, CO2, DRY CHEMICAL, WATER MIST

Fire Fighting Procedures: CONTAINS FLAMMABLE SOLVENT. DON'T USE IN AREAS WHERE SPARKS OR OPEN FLAMES ARE PRESENT.

Unusual Fire/Explosion Hazard:SMOTHER FLAMES WITH ONE OF THE ABOVE EXTINGUISHING MEDIA. WATER MAY BE USED TO COOL DOWN UNOPENED CONTAINERS IN VICINITY.

======== Accidental Release Measures ==========

Spill Release Procedures:E

LIMINATE ALL IGNITION SOURCES. WEAR

APPROPRIATE PERSONAL PROTECTION EQUIPMENT/APPROVED RESP. CONTAIN SPILL W/ABSORBANT MATERIAL/PUT INTO VAPOR TIGHT CONTAINERS. PREVENT MATERIAL FROM CONTACTING ANY W ATER SOURCES/SEWERS LEADING TO SURFACE WATERS.

=========== Handling and Storage ============

Handling and Storage Precautions:STORE IN AREAS DESIGNED TO COMPLY WITH ANSI/NFPA 30 FLAMMABLE/COMBUSTIBLE LIQUIDS CODE.

Other Precautions: GROUND CONTAINERS WHEN P

OURING LIQUIDS/POWDERS TO

AVOID STATIC CHARGE BUILD UP. PROVIDE ADEQUATE VENTILATION OR RESPIRATORY PROTECTION TO REMOVE DECOMPOSITION PRODUCTS DURING WELDING OR FLAME CUTTING COATED SURFACES.

===== Exposure Controls/Personal Protection ========

Respiratory Protection:IN OUTDOOR OR OPEN AREAS, USE APPROVED RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVER SPRAY DURING SPRAY APPLICATION. IN RESTRICTED VENTILATION AREAS USE APPROVED RESPIRATOR DESIGN T

O REMOVE A COMBINATION OF PARTICLES AND VAPOR. Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP AIR Evaporation Rate & Experimental Reference:SLOWER THAN ETHER Percent Volatiles by Volume:65.70%

======== Stability and Reactivity Data =========

Stability Indicator/Materials to Avoid:YES
OXIDIZING AGENTS
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAMES.
Hazardous Decomposition Products:MAY PRODUCE HAZARDOUS FUMES WHEN HEATED.

====== Disposal Consideratio

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent pr ofessional advice to verify and assume responsibility for the suitability of this information to their particular situation.