View NSN Online: https://aerobasegroup.jp/nsn/8010-00-902-0182

CON-LUX COATINGS, INC. -- ENAMEL LUSTERLESS QK DRY 34087 OLIVE DRAB -- 8010-00-902-0182

======== Product Identification ============

Product ID:ENAMEL LUSTERLESS QK DRY 34087 OLIVE DRAB

MSDS Date:04/25/1984

FSC:8010

NIIN:00-902-0182

MSDS Number: BHDYC === Responsible Party ===

Company Name: CON-LUX COATINGS, INC.

Address:TALMADGE ROAD

Box:847 City:EDISON State:NJ

ZIP:08818 Country:US

Info Phone Num:(201) 287

-4000

Emergency Phone Num:(201) 287-4000

CAGE:60189

=== Contractor Identification ===

Company Name: CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847 City:EDISON State:NJ

ZIP:08818-0847 Country:US

Phone:732-287-4000

CAGE:60189

======= Composition/Information on Ingredients ========

Ingred Name: ALIPHATIC NAPHTHA (LEL 1.0)

(VAPOR PRESSURE 30 @ 100F)

Fraction by Wt: 29.7% ACGIH TLV:500 PPM

Ingred Name: N-BUTYL ALCOHOL (SARA III)

CAS:71-36-3

RTECS #:EO1400000

Fractio

n by Wt: 7.4% **OSHA PEL:100 PPM** ACGIH TLV:S, C 50 PPM; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 5.1% OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM: 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name: LEAD CHROMATE PIGMENT (.1-CRO3-.2PB MGM3) Fraction by Wt: 1.8% OSHA PEL:0.05 MG/M3 (PB) ACGIH TLV:0.05MG/M3(CR)A2;8990 ========== Hazards Identification ================ Route s of Entry: Inhalation:YES Skin:YES Ingestion:NO Effects of Overexposure: EYES: MAY CAUSE IRRITATION SKIN: MAY CAUSE IRRITATION INHALATION: MAY IRRITATE RESPIRATORY TRA CT, CAUSING HEADACHE OR DIZZINESS. First Aid:EYES: FLUSH WITH PLENTY OF WATER SKIN: FLUSH WITH PLENTY OF WATER INHALATION: REMOVE TO FRESH AIR. IF IRRI TATION PERSISTS, CONSULT A PHYSICIAN ============= Fire Fighting Measures ======================== Flash Point Method:TCC Flash Point:50F/10C Extinguishing Media: FOAM, CO2, DRY CHEMICAL, WATER MIST Fire Fighting Procedures: SMOTHER FLAMES WITH ONE OF THE ABOVE EXTINGUISHING MEDIA. WATER MAY BE USED TO COOL DOWN UNOPENED

CONTAINERS IN VICINITY.
Unusual Fire/Explosion Hazard: CONTAINS FLAMMABLE SOLVENT. DO NOT USE IN AREAS WHERE SPARKS OR OPEN FLAMES ARE PRESENT.

======= Accidental Release Measures

=======================================
Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID PROLONGED BREATHING OF VAPORS. VENTILATE AREA.CLEAN UP WITH ABSORBENT MATERIAL.
============== Handling and Storage ==============
Handling and Storage Precautions:STORE IN BUILDINGS DESIGNED AND PROTECTED FOR STOREAGE OF NFPA CLASS II FLAMMABLE LIQUIDS. Other Precautions:STORE IN BUILDINGS DESIGNED AND PROTECTED FOR STOREAGE OF NFPA CLASS II FLAMMABLE LIQUIDS.
=====
===== Exposure Controls/Personal Protection ========
Respiratory Protection:IN OUTDOOR OR OPEN,USE NIOSH APPRVD FILTER RESPRTR TO REMOVE SOLID AIRBORNE PAR-TICLES OF OVERSPRAY DURING SPRAY APPLICATION.IN RESTRICTED VENTILATION AREAS,USENIOSH APPRVD CHEM FILTERS DESIGNED TO RE MOVE A COMBINATION OF PARTICULATE/VAPOR Ventilation:GENERAL DILUTION OR LOCAL EXHAUST VENTILATION. Protective Gloves:REQUIRED FOR LONG OR REPEATED EXPOSURE Eye Protection:USE SAFETY EYEWEAR Supplementa I Safety and Health PREVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING.
========= Physical/Chemical Properties ==========
Boiling Pt:B.P. Text:230-245F Vapor Density:>AIR Evaporation Rate & Evaporation Rate & Percent Volatiles by Volume:64.7
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES NK
Hazardous Decomposition Products:CO,CO2

======== Disposal Considerations =========

======

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOCAL, STATE, AND FEDERAL REGULATIONS. DONOT INCINERATE UNOPENED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should se ek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.