View NSN Online: https://aerobasegroup.jp/nsn/8010-00-290-4079

Product ID: MINERAL SPIRITS, TT-T-291F, TYPE 1 MSDS Date:10/01/1986 FSC:8010 NIIN:00-290-4079 **MSDS Number: BHJKT** === Responsible Party === Company Name:CSD, INC. Address:#5 HACKBERRY City:CUT & SHOOT State:TX ZIP:77302 Country:US CAGE:KO005 === Contractor Identification === Company Name: CHEMICAL SPE CIALISTS AND DEVELOPMENT INC Address:2210 HACKBERRY LN Box:687 City:CONROE State:TX ZIP:77305 Country:US Phone:409-756-1065 CAGE:4N760 Company Name:CSD, INC. Address:5 HACKBURY ST Box:687 City:CONROE State:TX ZIP:77305 Country:US Phone:409-756-1065 CAGE:KO005

Ingred Name:MINERAL SPIRITS REGULAR CAS:64741-41-9 Fraction by Wt: 35% ACGIH TLV:500 PPM

Ingred Name:66/3 MINERAL SPIRITS CAS:64742-88-7 Fraction by Wt: 65% ACGIH TLV:1 Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Effects of Overexposure:VAPORS MIGHT AFFECT CONTROL OF NERVOUS SYSTEM AND CAUSE RESPIRATORY IRRITATION. ADVANCED TEMPERATURES WOULD INCREASE THIS HAZARD. ANESTHESIA IN HIGH CONCENTRATNEYE: IRRITANT

First Aid:EYE: WASH GENTLY W/PLENTY WTR FOR 15 MINS. GET MEDICAL ATTENTION. SK
IN: REMOVE CONTAMINATED CLOTH & WASH W/SOAP & WATER. SEEK MEDICAL ATTENTION. INHAL: SEEK AIR FREE OF VAPORS. IF BREAT HING STOPS GIVE ARTIFICIAL RESPIRATION& SEEK MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING, UNLESS DIRECTED BY PHYSICIAN. GET IMMEDIATE MEDICAL ATTENTION AND/OR ADVICE.

Flash Point Method:TCC Flash Point:105F/40.56C Lower Limits:6.0 Upper Limits:0.9 Extinguishing Media:MECHANICAL FO AM, DRY CHEMICAL, WATER FOG, CO2 Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS. STRAIGHT WATER STREAM WOULD SPREAD OIL FIRE. Unusual Fire/Explosion Hazard:KEEP WORK AREAS FREE OF HOT METAL SURFACES AND OTHER SOURCES.

Spill Release Procedures: AVOID ALL SOURCES OF IGNITION. STAY UPWIND, COLLECT & DISPOSE OF SPILLS. STOP DISCHARGE IF POSSIBLE. COVER W/INERT MATERIAL. USENONSPARKING TOOLS FOR CLEANUP.

KEEP OUT OF SEWERS, WATERWAYS, AND DRAINS.

Handling and Storage Precautions:COMPLY WITH LOCAL FIR REGULATIONS.
HANDLE AS CLII,COMBUSTIBLE LIQUID.
Other Precautions:CONTACTS FIRE AUTHORITIES,NOTIFY HEALTH/POLLUTION CONTROL AGENCIES.

======= Exposure Controls/Personal Protection ===============

Respiratory Protection:SELF CONTAINED BREATHING APPARATUS, WITH ADEQUATE VENTILATION. Ventilation: VENTILATE TO FIRE SAFE AREA. Protective Gloves:RECOMMENDED Eye Protection:GOGGLES Other Protective Equipment:IMPERMEABLE APRON, EYE WASHES, & SHOWERS AVAILABLE IN WORK AREAS. Supplemental Safety and Health NK

Boiling Pt:B.P. Text:310-405F Vapor Pres:1.8 @ 60F Vapor Density:5.05 Spec Gravity:.7741 Evaporation Rate & amp; Reference:0.08 Solubility in Water:NEGLIGIBLE Appearance and Odor:WATER WHITE LIQUID, MILD APLIPHATIC H YDROCARBON ODOR. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, STRONG ACIDS, OR BASES & SELECTED AMINES. Stability Condition to Avoid:NA

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agenci es):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.