Product ID:ORANGE FLUORESCENT STRIPE MSDS Date:06/08/1989 FSC:8010 NIIN:00-958-8148 MSDS Number: BHLTM === Responsible Party === Company Name:SEYMOUR OF SYCAMORE, INC. Address:917 CROSBY AVE. City:SYCAMORE State:IL ZIP:60178 Info Phone Num:(815) 895-9101 Emergency Phone Num:(815) 895-9101

CAGE:59581 === Contractor Identification === Company Name:SEYMOUR OF SYCAMORE Address:917 CROSBY AVE. Box:City:SYCAMORE State:IL ZIP:60178-1343 Country:US Phone:815-895-9101/800-255-3924 CAGE:59581

Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 3.91% Other REC Limits:100 PPM OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:VM&P NAPHTHA (LI

GROINE) CAS:8032-32-4 RTECS #:0I6180000 Fraction by Wt: 3.19% Other REC Limits:STEL 400 PPM OSHA PEL:300 PPM/400 STEL ACGIH TLV:300 PPM; 9192 Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III) CAS:1330-20-7 RTECS #:ZE2100000 Fraction by Wt: 9.15% Other REC Limits:100 PPM OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name: HEXANE (N-HEXANE) CAS:110-54-3 RTECS #:MN9275000 Fraction by Wt: 12.25% Other REC Limits:50 PPM **OSHA PEL:500 PPM** ACG IH TLV:50 PPM; 9293 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB Ingred Name:SOLVENT NAPHTHA (LIGHT AROMATIC) CAS:64742-95-6 Fraction by Wt: 5.25% ACGIH TLV:100 PPM Ingred Name: PROPANE CAS:74-98-6 RTECS #:TX2275000 Fraction by Wt: 18.7% Other REC Limits:1800 MG/CUM

OSHA PEL:1000 PPM ACGIH TLV:ASPHYXIANT; 9192

Ingred Name:ISOBUTANE CAS:75-28-5 RTECS #:TZ4300000 Fraction by Wt: 12.5% Other REC Limits:1000 PPM OSHA PEL:1800 MG/CUM ACGIH TLV:1000 PPM

========= Hazards Identification ========

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION: RESPIRATORY SYSTEM IRRITATION, HEADACHE, DIZZINESS, NAUSEA, UNCONSCIOUSNESS, ASPHYXIATION. EYE/SKIN: IRRITATION. Explanation of Carcinogenicity:NONE Effects of Overexposure:INHALATION: IRRITATION TO RESPIRATORY TRACT, HEADACHES, DIZZINESS, ANESTHETIC, & CENTRAL NERVOUS DEPRESSION & DEATH. EYES: IRRITATION. SKIN: DE FATTING, IRRITATION, DERMATITIS. . Medical Cond Aggravated by Exposure:HEALTH STUDIES HAVE SHOWN THAT PETROLEUM HYDROCARBONS POSE POTENTIAL HUMAN HEALTH RISKS WHICH MAY VARY FROM PERSON TO PERSON.

First Aid:INHALATION: REMOVE TO FRESH AIR. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION. SEEK MED ATT. EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MED ATT. SKIN: WASH W/SOAP & WATER. INGESTIO N : CALL PHYSICIAN.

Flash Point Method:TOC Flash Point:-10F Lower Limits:1.00% Upper Limits:2.30% Extinguishing Media:CO2, DRY CHEMICAL, FOAM Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CONTAINERS TO PREVENT BURSTING. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. WEAR GOGGLES & SCBA. Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT MAY CAUSE BURSTING OF AEROSOL CAN.

============

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, AVOID BREATHING VAPORS, VENTILATE AREA. WIPE UP W/INERT MATERIALS & PLACE IN APPROPRIATE CONTAINER.

Handling and Storage Precautions:DON'T STORE >120F. EXPOSURE TO HEAT OR PROLONG EXPOSURE TO SUN MAY CAUSE BURSTING. DON'T PLACE AEROSOL CANS IN HOME COMPACTOR. DON'T PUNCTURE. Other Precautions:EXPOSU RE TO LIQUIDS, VAPORS, MISTS OR FUMES SHOULD BE MINIMIZED. AVOID BREATHING VAPORS & SPRAY MISTS. USE ONLY A S DIRECTED. DILIBERATELY CONCENTRATING VAPORS & INHALING CONTENTS CAN BE HARMFUL OR FA TAL.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: AVOID CONTINUOUS BREATHING OF VAPORS & SPRAY MIST. A SELF CONTAINED BREATHING APPARATUS IS REQUIRED FOR CONCENTRATIONS >TLV LIMITS. Ventilation: USE W/ADEQUATE VENTILATION, SUFFICIENT TO P REVENT INHALATION OF SOLVENT VAPORS. Protective Gloves: OPTIONAL Eye Protection: UPON DIRECT CONTACT W/SPRAY Work Hygienic Practices: WASH W/SOAP & WATER. Supplemental Safety and Health HIGH VAPOR CONCENTRATIONS OF >1000 PPM ARE IRRITATING TO EYES & RESPIRATORY TRACT, CAUSING HEADACHES, DIZZINESS, & OTHER CNS EFFECTS INCLUDING DEATH.

HCC:V3 Vapor Density:>AIR Evaporation Rate & amp; Reference:FASTER THAN ETHER Percent Volatiles by Volume:85%

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING MATERIALS. Stability Condition to Avoid:DON'T STORE >120F. KEEP FROM SPARKS, PILOT LIGHTS OR OPEN FLAME. Hazardous Decomposition Products:HAZARDOUS FUMES, CO2, CO.

Waste Disposal Methods:DON'T INCINERATE AEROSOL, DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGU

LATIONS. DON'T PLACE AEROSOL CANS IN HOME COMPACTOR. DON'T PUNCTURE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsib ility for the suitability of this information to their

particular situation.