

ASPEN PAINTS -- ACRYLIC LATEX PAINT, EXTERIOR YELLOW 33727 -- 8010-00-418-4668

===== Product Identification =====

Product ID:ACRYLIC LATEX PAINT, EXTERIOR YELLOW 33727

MSDS Date:02/01/1989

FSC:8010

NIIN:00-418-4668

MSDS Number: BHMPG

=== Responsible Party ===

Company Name:ASPEN PAINTS

Address:1128 SW SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134-1197

Country:US

Info Phone Num:(206) 682-4603

Emerg

ency Phone Num:(303) 573-1014

Preparer's Name:DOUGLAS KIER

CAGE:0AL09

=== Contractor Identification ===

Company Name:ASPEN PAINTS

Address:1128 SW SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134

Country:US

Phone:800-424-9300 CHEMTREC

CAGE:0AL09

===== Composition/Information on Ingredients =====

Ingred Name:ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: < 5%

OSHA PEL:C 50 PPM

ACGIH TLV:C 50 PPM,VAPOR; 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Nam

e:AMMONIUM HYDROXIDE (SARA III)
CAS:1336-21-6
RTECS #:BQ9625000
Fraction by Wt: < 1%
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:INHAL: ADVERSE HEALTH EFFECTS FROM VAPORS/SPRAY
MISTS IN POORLY VENTED AREAS MAYCAUSE IRRITATION OF THE MUCOUS
MEMBRANES OF THE NOSE/THROAT/RESPIRATORY TRACT &
HEADACHE & NAUSEA.
SKIN & EYE: PROLONGED /REPEATED EXPOSURE MAY CAUSE SKIN
IRRI-TATION, DIRECT CONTACT MAY RESULT IN EYE IRRITATION

===== First Aid Measures =====

First Aid:INHAL: REMOVE SUBJECT TO FRESH AIR. EYE & SKIN: PROMPTLY &
THOROUGHLY WASH EYES W/WATER AT LEAST 15 MIN, CONSULT A DOCTOR IF
IRRI PERSISTS. REMOVE CONTAMINATED CLOTHING, WASH SKIN THOROUGHLY
WITH SOAP & WATER, WASH CLOTHING BEFORE REUSE

===== Fire
Fighting Measures =====

Flash Point:NONE
Lower Limits:NA
Upper Limits:NA
Extinguishing Media:PAINT WILL NOT BURN UNTIL WATER HAS EVAPORATED. FOR
RESIDUALSOLIDS: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL OR WATER FOG
Fire Fighting Procedures:CLOSED CONTAINER MAY EXPLODE WHEN EXPOSED TO
EXTREME HEAT. WATER MAY BE USED TO COOL UNRUPTURED CONTAINER. AVOID
SPREADING OF BURNING LIQ W/WATER USED TO COOL
Unusual Fire/Explosion Hazard:CAN SPLATTER IF TEMP EXCEED BOILING
POIN
T. RESIDUAL SOLIDS CAN BURN, GIVING OFF CARBON
MONOXIDE/DIOXIDE, ETC. SELF CONTAINED BREATHING APPARATUS MAY BE
NEEDED

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE LIQUID. PICK UP REMAINING LIQUID
WITHABSORBANT MATERIAL & PLACE INTO CONTAINER FOR DIS-POSAL. WASH
AREA WITH WATER & DETERGENT. DO NOT WASH INTO PUBLIC WATER
SOURCE.

===== Handling and Storage =====

Handling and St

Storage Precautions:STORE AT ROOM TEMP TO PROLONG STORAGE
LIFE. KEEP FROM FREEZING SO PRODUCT DOES NOT COAGULATE. DO NOT
APPLY WHEN TEMP IS BELOW 50F/10C.
Other Precautions:SHAKE OR STIR WELL BEFORE USING. DO NOT TAKE
INTERNALLY. AVOID PROLONGED CONTACT WITH SKIN OR BREATHING OF SPRAY
MIST. CLOSE CONTAINER AFTER EACH USE. KEEP AWAY FROM CHILDREN.
THESE PRODUCTS CONTAIN NO LEAD PIGMENTS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE ORGANIC VAPOR CANISTER OR SUPPLIED-AIR
RESPIRATORY PROTECTION WHEN TLV IS EXCEEDED.
Ventilation:SUFFICIENT MECHANICAL VENTILATION WITH EXPLOSION PROOF
EQUIPMENT TO MAINTAIN EXPOSURE LEVEL BELOW TLV.
Protective Gloves:IMPERMEABLE GLOVES
Eye Protection:SPLASH GOGGLES OR FACE SHIELD
Work Hygienic Practices:USE PROTECTIVE CREAM WHERE SKIN CONTACT IS
LIKELY. TO PREVENT REPEAT/PROLONGED CONTACT WEAR IMPERVIOUS
CLOTHING/BOOTS
Supplemental Safety and Health
WASH HANDS BEFORE EATING OR USING THE WASHROOM. SMOKE IN SMOKING AREA
ONLY.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212 F
Vapor Density:< AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:COMPLETE
Appearance and Odor:THICK LIQUID, WHITE AND VARIOUS COLORS, SLIGHT
AMMONIA ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:HIGH TEMPERATURE

Hazardous Decomposition Products:WHEN PRODUCT IS HEATED TO DECOMP IT
MAY PRODUCE FUMES WHICH CONTAIN CARBON MONOXIDE/DIOXIDE, ETC.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE &
LOCAL REGULATIONS. BEFORE ATTEMPTING CLEAN UP, REFER TO HAZARD
CAUTION INFORMATION IN OTHER SECTIONS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use

by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.