

PRATT & LAMBERT, INC. -- ENAMEL ALKYD GLOSS GRN 14050 ID742404 -- 8010-00-753-4550

===== Product Identification =====

Product ID:ENAMEL ALKYD GLOSS GRN 14050 ID742404

MSDS Date:03/23/1988

FSC:8010

NIIN:00-753-4550

MSDS Number: BHMVB

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Preparer's Name:W.A. ELLISON

C

AGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:Y

ES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PROLONG/REPEATED OVEREXPOSURE TO SOLVENTS W/PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE MAY BE HARMFUL OR FATAL. ASPIRATION OF MATERIAL INTO LUNG MAY CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. HIGH CONCENTRATIONS MAYCAUSE ACUTE CENTRAL NERVOUS SYSTEM DEPRESSION.

Explanation of Carcinogenicity:MANUFACTURER CONCLUDES THAT THERE IS NO SIGNIFICANT HAZARD FOR MAN.

Effects

ts of Overexposure:INGST: GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING. INHAL: NOSE/THROAT IRRITATION,HDACHES,DIZZINESS,NAUSEA, AND CONFUSION. EYE: IRRITATIONSKIN: IRRITATION AND DEFA TTING OF SKIN

===== First Aid Measures =====

First Aid:INGST: DO NOT INDUCE VOMITING, CALL A PHYSICIAN IMMEDIATELY INHAL: REMOVE TO FRESH AIR IMMED.,GIVE ARTIFICIAL RESP. IF NECESSARY,KEEP WARM & QUIET,GET MED ATTN IMMED.; EYE: FLUSH W/LA RGE AMTS OF WATER, LIFTING EYELIDSFOR AT LEAST 15 MIN. GET MED ATTN.; SKIN: REMOVE CONTAMINATED CLOTHES. WASH AFFECTED AREA W/SOAP & WTR. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:> 102 F/38.89 C

Extinguishing Media:NFPA CL B FIRE EXTING (CARBON DIOXIDE, ALL PUR DRY CHEM OR ALCOHOL FOAM) FOR EXTING FLAMM LIQ FIRES. POLYMER FOAM PERFER

Fire Fighting Procedures:SELF CONTAIN BREATH APPARATUS. WTR MAY BE

INEFFECT, USED TO COOL TO PREVENT PRESSURE BUILD-UP/AUTO-IGNITE/EXPLOSION FROM HEAT. IF WTR USED, FOG NOZZLES PREFERR

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELEC. EQUIP, SPARKS, & FLAME.CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. DIKE & CONTAIN SPILL W/INERT MATERIAL. USE NON SPAR

KING TOOL ONLYPLACE

ABSORBENT DIKING MATERIALS IN COVERED METAL CONTAINER FOR DISPOSAL.
PREVENT SEWERS, STREAMS & GROUNDWATER WITH SPILLED MATERIAL OR
USED ABSORB

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95 DEG F. STORE LG
QTY IN COMPLIANCE W/OSHA 29CFR1910.106. CLOSE CONTAINER AFTER EACH
USE. NEVER USE PRESSURE TO EMPTY CONTAINER.

Other Precautions:KEEP AWAY FROM CHILDREN. DO NOT BREATHE SANDIN
G DUST.

EMPTY CONTAINERS MUST NOT BE WASHED AND REUSED FOR ANY PURPOSE.
CONTAINERS SHOULD BE GROUNDED & BONDED TO RECEIVING CONTAINER. DO
NOT WELD, BRAZE OR CUT ON EMPTY CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESTRICTED AREAS USE A NIOSH APPROVED CHEMICAL
CARTRIDGE RESPIRATOR. FOR SPRAYING USE A MECHANICAL
PREFILTER. IN CONFINED AREAS
USE A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR.

Venti

lation:GENERAL DILUTION AND LOCAL EXHAUST

Protective Gloves:SOLVENT IMPERMEABLE GLOVE

Eye Protection:WEAR SAFETY SPECTACLES

Other Protective Equipment:NONE LIKELY NEEDED

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:280-388 F

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:62

===== Stability and Reactivity Data =====

Stability Indicator/Ma

terials to Avoid: YES

STRONG ACIDS OR ALKALINE MATERIALS

Stability Condition to Avoid: EXCESSIVE HEAT & SOURCES OF IGNITION.

Hazardous Decomposition Products: BURNING, INCLUDE WHEN HEATED BY
WELD/CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE/DIOXIDE.

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT SPARKS AND FLAME

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND
LOCAL REGULATION. DO NOT INCIN
ERATE CLOSED CONTNRS INCINERATE ONLY
IN EPA PERMITTED FACILITY. CONTAMINATED ABSORBANT MAY BE DISPOSED
IN A HAZARDOUS WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document s
ould seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.