

CHEMRAY COATING CORP -- PAINT, TRAFFIC, HIGHWAY-WHITE -- 8010-00-900-2940

===== Product Identification =====

Product ID:PAINT, TRAFFIC, HIGHWAY-WHITE

MSDS Date:04/25/1990

FSC:8010

NIIN:00-900-2940

MSDS Number: BHVVT

=== Responsible Party ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Info Phone Num:201-245-1111

Emergency Phone Num:800

-424-9300 (CHEMTREC)

Preparer's Name:FRED ARMSTRONG

CAGE:33832

=== Contractor Identification ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:201-245-1111

CAGE:33832

===== Composition/Information on Ingredients =====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: 13.4%

OSHA PEL:350 PPM/450 STEL

ACGIH TLV:350 PPM/450STEL;9192

EPA Rpt Qty:1000

LBS  
DOT Rpt Qty:1000 LBS  
Ozone Depleting Chemical:1

Ingred Name:1,4-DIOXANE (DIETHYLENE DIOXIDE) (SARA III)  
CAS:123-91-1  
RTECS #:JG8225000  
OSHA PEL:S, 100 PPM  
ACGIH TLV:S, 25 PPM; 9293  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 4.0%  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:XR2275000  
Fraction by Wt: 9.4%  
OSHA PEL:15 M  
G/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)  
CAS:78-93-3  
RTECS #:EL6475000  
Fraction by Wt: 7%  
OSHA PEL:200 PPM/300 STEL  
ACGIH TLV:200 PPM/300STEL 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:VOC=2.07 LBS/GAL OR 248 GRAMS/LITER  
RTECS #:9999999VO

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE:IRRIT. SKIN:IRRIT, DRY & CRACKING.  
MAY BE ABSORBED(TOXICITY ARE NOT ANTICIPATED BY THIS ROUTE ALONE  
UNDER NORMAL CONDITIONS OF USE). BREATHING HIGH CONCENTRATE OF  
VAPORS/MISTS MAY CAUSE IRRIT OF N OSE, THROAT, NERV SYS DEPRESS.  
ASTHMA LIKE CONDITIONS AGGRAVATED. LUNG INFLAMMATION & DAMAGE. SEE  
FILE FOR ADDIT INFO

Explanation of Carcinogenicity:EDITORS NOTE: 1,4 DIOXANE IS LISTED AS  
CLASS 2 B CARCINOGEN. NOT MENTIONED ON MSDS.

#### Effects

of Overexposure:EYES:IRRIT, DIRECT CONTACT-STING, TEARS,  
REDNESS. SKIN: IRRIT, REDNESS, BURNING, DRYING, CRACKING. IF  
PRE-EXISTING DISORDERS, MAY BE MORE SUSCEPTIBLE. INHALE:HEADACHE,  
DROWSINESS, DIZZINESS, LOSS OF C OORDINATION, FATIGUE,  
INGESTION:NAUSEA,VOMIT, DIARRHEA, DROWSINESS, DIZZINESS. VOMIT CAN  
CAUSE LUNG INFLAMMATION/DAMAGE

Medical Cond Aggravated by Exposure:PRE-EXIST SKIN DISORDER MAY BE MORE  
SUSCEPTIBLE TO EFFECTS & PRE-EXISTING LUNG DISORDER(E.G.  
ASTHMA

-LIKE CONDITONS)MAY BE AGGRAVATED.MAY BE ASSOCIATED W/CARDIAC  
ARRHYTHMIAS & AGGRAVATED LIVER DISORDER

#### ===== First Aid Measures =====

First Aid:EYES:GET FRESH AIR, FLUSH W/WTR. IF SYMP PESIST, SEEK MED  
ATTN. SKIN: REMOVE CONTAM SHOES/CLOTHES, CLEANSE THORO W/SOAP &  
WTR. IF IRRIT/REDNESS DEVELOP/PERSIST, SEEK MED. INHALE:MOVE TO  
FRESH AIR, SYM P PERSIST, SEEK MED IMMED. BREATH STOP GIVE CPR, IF  
BREATH DIFF, GIVE OXYGEN, SEEK MED IMMED. IN  
GEST:DON'T INDUCE  
VOMIT/GIVE ANYTHING BY MOUTH.IF UNCONC/DROWSI PLACE ON LEFT SIDE  
W/HEAD DOWN. SEEK MED

#### ===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:24 F/-4.4 C

Autoignition Temp:Autoignition Temp Text:960 F

Lower Limits:1.0

Upper Limits:11.0

Extinguishing Media:CARBON DIOXIDE, FOAM, WATER FOG, DRY CHEMICAL.

Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT. COOL  
ENCLOSED CONTAINERS WITH WATER SPRAY. AVOID BREA

THING VAPORS OR  
FUMES.

Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER  
SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. KEEP FROM HEAT,  
SPARKS & OPEN FLAME. ADD ABSORBENT (SAND, EARTH, SAWDUST) TO SPILL.  
VENT AREA (OPEN WINDOWS, DOORS). LARGE SPILL: KEEP PRODUCT FROM  
ENTERING SEWERS/WATERCOURSES BY DIKING. ADVISE AUTHORITIES IF DOES  
ENTER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM IGNITION SOURCES. KEEP  
IN COOL, DRY, WELL VENTILATED AREAS. AVOID DIRECT SUNLIGHT &  
EXTREME TEMPERATURES, HOT OR COLD.

Other Precautions:AVOID EYE, SKIN CONTACT, INHALATION OR INGESTION OF  
MISTS, SPRAY OR VAPORS. AVOID BREATHING SANDING OR BLASTING DUST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR  
RESPIRATOR IN CONFINED AREAS.

Ventilation:LOCAL EXHAUST: FACE VELOCITY 60FPM. SPECIAL: USE ONLY  
W/ADEQUATE VENTILATION. MECHANICAL: USE EXPLOSION PROOF EQUIPMENT.

Protective Gloves:CHEMICAL RESISTANT.

Eye Protection:SPLASH GOGGLES OR FACE SHIELDS.

Other Protective Equipment:USE CHEMICAL RESISTANT APRON OR CLOTHING.

Supplemental Safety and Health

SEE FILE FOR ADDITIONAL INFORMATION.

===== Physical/Chemical Properties =====

=

Boiling Pt:B.P. Text:162F,72C

Melt/Freeze Pt:M.P/F.P Text:0 F(-17.8C)

Decomp Temp:Decomp Text:600 F(316C)

Vapor Pres:45-134 @68F

Vapor Density:4.6 @ 77 F

Spec Gravity:1.67 (H2O=1)

Viscosity:70-80 @77FKREB

Evaporation Rate & Reference:5.0 (BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:WHITE LIQUID WITH PAINT SOLVENT ODOR.

Percent Volatiles by Volume:40.8

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
CAN

REACT W/OXIDIZING MATERIAL WHEN HEAT TO DECOMP. STRONG ACIDS/BASES,  
ALKALIES & REACTIVE METALS(IE SODIUM, POTASSIUM)

Stability Condition to Avoid:HIGH TEMPERATURE AND HIGH PRESSURE IN  
ALUMINUM SYSTEMS.

Hazardous Decomposition Products:CARBON MONOXIDE, PHOSGENE &  
HYDROCHLORIC ACID, CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:ASSURE CONFORMITY WITH APPLICABLE DISPOSAL  
REGULATIONS DISPOSE OF ABSORBED MATERIAL AT AN APP  
ROVED DISPOSAL  
SITE OR FACILITY. DISPOSE IN CONFORMITY WITH STATE & FEDERAL  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to veri  
fy and  
assume responsibility for the suitability of this information to their  
particular situation.