View NSN Online: https://aerobasegroup.jp/nsn/6750-01-281-4599

EASTMAN KODAK COMPANY -- 140 2767,T-MAX DEVELOPER -- 6750-01-281-4599

Product ID:140 2767, T-MAX DEVELOPER MSDS Date:06/23/1989 FSC:6750 NIIN:01-281-4599 MSDS Number: BHXQW === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET **City:ROCHESTER** State:NY ZIP:14650 Country:US Info Phone Num:716-722-5151 Emergency Phone Num:716-722-5151 С AGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139

Ingred Name:DIETHANOLAMINE-SULFUR DIOXIDE COMPLEX CAS:63149-47-3 Fraction by Wt: 45-50% Other REC Limits:NONE SPECIFIED

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 40-45% Other REC Li mits:NONE SPECIFIED

Ingred Name:HYDROQUINONE (SARA III) CAS:123-31-9 RTECS #:MX3500000 Fraction by Wt: 4% Other REC Limits:NONE SPECIFIED OSHA PEL:2 MG/M3 ACGIH TLV:2 MG/M3; 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:SODIUM BISULFITE (SASA III) CAS:7631-90-5 RTECS #:VZ2000000 Fraction by Wt: 1-5% Other REC Limits:NONE SPECIFIED OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:PENIETIC ACID, PENTA SODIUM SALT CAS:140-01-2 Fraction by Wt: < 1% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:LD50 (ORAL RAT) IS NOT ESTABLISHED. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES/SKIN: CAUSES IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION. INGESTION: HARMFUL - CAUSES GASTROINTESTINAL TRACT IRRITATION. INHALATION: LOW HAZARD FOR RECOMMENDED INDUSTRIAL H ANDLING. Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexposure:IRRITATION OF EYES/SKIN/GASTROINTESTINAL SYSTEM.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS OR WITH A PRE-EXISTING DISEASE INVOLVING THE SKIN MAY BE AT INCREASED RISK FROM EXPOSURE.

First Aid:EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATE

R FOR 15 MINUTES HOLDING EYELIDS OPEN. GET IMMEDIATE MEDICAL ATTENTION. SKIN:REMOVE CONTAMINATED CLOTHING AND SHOES. WASH SKIN WITH SOAP AND WATER. WASHING WI TH A NON-ALKALINE TYPE OF SKIN CLEANER IS RECOMMENDED. GET MEDICAL ATTENTION. INGESTION: DRINK 1-2 GLASSES OF WATER AND GET MEDICAL ATTENTION AT ONCE. Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL AS APPROPRIATE FOR SU **RROUNDINGS.** Fire Fighting Procedures: WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. Unusual Fire/Explosion Hazard: COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS. Spill Release Procedures: REMOVE RESIDUE WITH LARGE AMOUNTS OF WATER BY FLUSHING TO THE SEWER (ACID-FREE). DI SCHARGE MAY BE GOVERNED BY LOCAL LAW. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. Handling and Storage Precautions: KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE AND AWAY FROMSTRONG ACIDS AND OXIDIZING AGENTS. Other Precautions: AVOID CONTACT WITH EYES. WASH THOROUGHLY AFTER HANDLING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Respiratory Protection: AN APPROPRIATE NIOSH-APPROVED RESPIRATOR FOR ORGANIC VAPOR SHOULD BE WORN IF NEEDED. Ventilation: MECHANICAL (GENERAL) ROOM VENTILATION IS NORMALLY ADEQUATE. Protective Gloves: NEOPRENE OR NATURAL RUBBER Eye Protection: SAFETY GLASSES Other Protective Equipment: EYE WASH STATION AND SAFETY SHOWER. INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED. Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR

FOOTWEAR. Supplemental Safety and Health AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. LAUNDER CONTAMINATED CLOTHING PRIOR TO REUSE. THE ROUTINE USE OF A NON-ALKALINE (ACID) SKIN CLEANER AND REGULAR CLEANING OF WORKING SURFACES WILL MINIMIZE THE POSSIBILITYOF AN ALLERGIC SKIN REACTION.

HCC:N1 Boiling Pt:B.P. Text:>212 Vapor Pres:18 @20C Vapor Density:0.6 Spec Gravity:1.23 pH:8.3 Evapora tion Rate & amp; Reference:NEGLIGIBLE Solubility in Water:COMPLETE Appearance and Odor:CLEAR LIQUID; AMINE ODOR Percent Volatiles by Volume:30

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, STRONG ACIDS Stability Condition to Avoid:HIGH HEAT Hazardous Decomposition Products:CARBON DIOXIDE AND PROBABLY CARBON MONOXIDE AS WELL AS OXIDES OF SULFUR AND NITROGEN.

====== Disposal Consideration

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.