

EASTMAN KODAK COMPANY -- 818 3428;FLEXICOLOR AR DEVELOPER REPLENISHER;PT C;KAN449572 -- 6750-01-285-1765

=====  
Product Identification  
=====

Product ID:818 3428;FLEXICOLOR AR DEVELOPER REPLENISHER;PT C;KAN449572

MSDS Date:08/03/1994

FSC:6750

NIIN:01-285-1765

MSDS Number: BHZHJ

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Co

Country:US

Info Phone Num:716-722-5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

=====  
Composition/Information on Ingredients  
=====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 50-55%

Other REC Limits:NONE RECOMMENDED

Ingred Name:4-(N-ETHYL-N-2-

HYDROXYETHYL)-2-METHYLPHENYLENEDIAMINE  
SULFATE

CAS:25646-77-9

RTECS #:KJ6477000

Fraction by Wt: 45-50%

Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM BISULFITE (SASA III)

CAS:7631-90-5

RTECS #:VZ2000000

Fraction by Wt: 1-5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3; 9394

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====  
===== Hazards Identification =====  
=====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS 25-50MG/KG INGRED #2

Routes of Entry: I

nhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES:MAY CAUSE IRRITATION.SKIN:MAY

CAUSE IRRITATION.INGEST:RELEASES SULFUR DIOXIDE GAS.MAY CAUSE GI

TRACT IRRITATION.INHAL:MAY CAUSE RESPIRATORY IRRITATION.CHRONIC:MAY

CAUSE BLOOD DISORDERS AND KIDNEY DAMAGE.

Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1%

WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.

Effects of Overexposure:SK

IN:ALLERGIC SKIN REACTIONS.

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING

RESPIRATORY AILMENTS(ASTHMA,RESPIRATORY SENSITIVITY) MAY BE AT

INCREASED RISK FROM EXPOSURE.

=====  
===== First Aid Measures =====  
=====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND

WATER.USE A NON-ALKALINE SKIN CLEANER.EYES:FLUSH WITH WATER FOR 15

MINUTES.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR ARTIFICIAL

RESPIRATION IF NEEDED.INGEST:GET PR

OMPT QUALIFIED MEDICAL

ATTENTION. IF CONSCIOUS, INDUCE VOMITING AS DIRECTED BY MEDICAL PERSONNEL.

===== Fire Fighting Measures =====

Flash Point: NONE

Extinguishing Media: WATER FOG, DRY CHEMICAL, CARBON DIOXIDE, ALCOHOL FOAM.

Fire Fighting Procedures: USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT. COOL FIRE EXPOSED CONTAINERS WITH WATER FOG.

Unusual Fire/Explosion Hazard: FIRE CONDITIONS MAY EVOLVE TOXIC FUMES.

=====

== Accidental Release Measures =====

Spill Release Procedures: SOAK UP WITH NON-COMBUSTIBLE INERT ADSORBENT (EG. CLAY); PLACE COLLECTED MATERIAL IN AN APPROPRIATE CONTAINER FOR DISPOSAL; CLEAN SPILL AREA TO REMOVE SLIPPERINESS. FOR SMALL SPILLS, PH BETWEEN 3-12, FLUSH TO SEWER WITH PLENTY OF WATER.

Neutralizing Agent: DEPENDS ON PH; LOW PH USE LIME, SODIUM BICARBONATE/HIGH PH USE VINEGAR (ACETIC ACID)

===== Handling and Storage =====

Handling and Storage Precautions: USE WITH ADEQUATE VENTILATION. KEEP CONTAINERS CLOSED. KEEP AWAY FROM OXIDIZERS AND HEAT.  
Other Precautions: FOLLOW LABEL DIRECTIONS. AVOID BREATHING VAPORS. AVOID SKIN AND EYE CONTACT. CONTAINERS MAY BUILD UP PRESSURE. USE OF A NON-ALKALINE SKIN CLEANER MAY AVOID ALLERGIC SKIN REACTIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: WHERE ENVIRONMENTAL CONTROLS ARE LACKING OR IN ENCLOSED SPACES USE EITHER A SELF-CONTAINED BREATHING APPARATUS OR A NIOSH/MSHA APPROVED RESPIRATOR FOR ACID GAS, DEPENDING ON THE AIRBORN CONCENTRATION.

Ventilation: USE GENERAL DILUTION VENTILATION. MFR RECOMMENDS 10 AIR CHANGES/HOUR. USE SUPPLEMENTARY LOCAL EXHAUST AT THE WORKSITE.

Protective Gloves: IMPERVIOUS

Eye Protection: CHEMICAL GOGGLES.

Other Protective Equipment: PROTECTIVE CLOTHING, AS NEEDED. PROVIDE A LOCAL EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices: WASH HANDS. SEPERATE WORK CLOTHES FROM ST

REET

CLOTHES.LAUNDRER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK AREA.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:C1

Boiling Pt:B.P. Text:>212F,>100C

Vapor Pres:18

Vapor Density:0.6

Spec Gravity:1.19

pH:2.1

Solubility in Water:COMPLETE

Appearance and Odor:LIQUID;YELLOW;STRONG SULFUR DIOXIDE

Percent Volatiles by Volume:50-60

===== Stability and Reactivity Data =====

Stability Indicator/

Materials to Avoid:YES

STRONG OXIDIZING AGENTS(EG.BLEACH),BASES

Stability Condition to Avoid:HIGH HEAT ABOVE 338F CAN CAUSE DECOMPOSITION.

Hazardous Decomposition Products:CARBON DIOXIDE,CARBON MONOXIDE,OXIDES OF NITROGEN AND SULFUR(INCLUDING SULFUR DIOXIDE-TLV IS 2MG/M3 TWA).

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.PRETREATMENT MAY BE REQUIRED BEFORE RELEASE INTO

SEWER IF PH IS OUTSIDE OF THE RANGE,3-12.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of t

his information to their particular situation.