

DEXTER ADHESIVES AND STRUCTURAL MATERIALS DIVISION -- EA 9309.3 NA PART A --
8040-01-202-7201

===== Product Identification =====

Product ID:EA 9309.3 NA PART A

MSDS Date:09/29/1989

FSC:8040

NIIN:01-202-7201

Kit Part:Y

MSDS Number: BJJJM

=== Responsible Party ===

Company Name:DEXTER ADHESIVES AND STRUCTURAL MATERIALS DIVISION

Address:2850 WILLOW PASS ROAD

Box:312

City:PITTSBURG

State:CA

ZIP:94565-

3237

Country:US

Info Phone Num:415-687-4201

Preparer's Name:SUZANNE FRANZ

CAGE:33564

=== Contractor Identification ===

Company Name:ADHESIVES PACKAGING SPECIALTIES INC

Address:103 FOSTER ST

Box:City:PEABODY

State:MA

ZIP:01960-5933

Country:US

Phone:978-531-3300

CAGE:64201

Company Name:DEXTER CORPORATION ADHESIVE & COATING SYSTEMS

Address:2850 WILLOW PASS ROAD

Box:312

City:BAY POINT

State:CA

ZIP:94565-3299

Country:US

Phone:202-483-7616

CAGE:33564

===== Composition/Information on Ingredie

nts =====

Ingred Name:EPOXY RESIN SYSTEM

Ingred Name:SILICA (TLV IS FOR FUSED SILICA, CAS 60676-86-0, FPN)

CAS:112945-52-5

RTECS #:VV7310000

Fraction by Wt: 149C

Extinguishing Media:DRY CHEMICAL OR HALON FIRE EXTINGUISHER, OR WATER SPRAY, FOAM OR FOG.

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES IN CONFINED AREAS.

Unusual Fire/Explosion Hazard:DENSE SMOKE AND TOXIC GASES MAY BE LIBERATED.

===== Accidental Release Measurements =====

Spill Release Procedures:WEAR PROTECTIVE CLOTHING, GLOVES AND SAFETY GLASSES. SCRAPE UP AND TRANSFER TO METAL CONTAINER. WIPE UP REMAINING RESIDUE WITH SOLVENTS, OBSERVING SOLVENT FLAMMABILITY CAUTIONS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP COOL IN ACCORDANCE WITH LABEL INSTRUCTIONS. STORE AT ROOM TEMPERATURE (77 DEG. F) NO LONGER THAN

12 MONTHS .

Other Precautions:FOLLOW RECOMMENDED CURING SCHEDULE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN . NOT NEEDED WITH GOOD INDUSTRIAL VENTILATION.

Ventilation:LOCAL EXHAUST RECOMMENDED.

Protective Gloves:IMPERVIOUS PLASTIC OR RUBBER.

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:AS NEEDED TO PROTECT SKIN AND CLOTHING.

Work Hygienic Practices:

AVOID CONTACT WITH EYES OR SKIN. WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

CNDTNS (POLYM):DO NOT HEAT MIXED ADHESIVES ABOVE 75 DEG F UNLESS CURING SURFACES TO BE BONDED. FAILURE TO OBSERVE CAUTION MAY RESULT IN EXCESSIVE HEAT BUILD-UP WITH THE RELEASE OF TOXIC GASES.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:DECOMPOSES

Vapor Pres:1

Evaporation Rate & Reference:NIL

Solubility in Water:NIL

Appearance and

Odor:VISCOUS PINK PASTE WITH SLIGHT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG LEWIS OR MINERAL ACIDS.

Stability Condition to Avoid:NOT APPLICABLE.

Hazardous Decomposition Products:CO, NO*X, ALDEHYDES, ACIDS AND UNDETERMINED ORGANICS.

Conditions to Avoid Polymerization:AVOID MIXING RESIN AND CURING AGENT IN BATCHES GREATER THAN 1 POUND TOTAL. (SEE SUPP DATA).

=====

Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS HAZARDOUS WASTE ACCORDING TO FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.