

LIQUID DEVELOPMENT INC -- LDC-2801 NICKEL

=====

MSDS Safety Information

=====

FSC: 6810
NIIN: 01-197-7797
MSDS Date: 01/01/1996
MSDS Num: BJMJZ
Product ID: LDC-2801 NICKEL
MFN: 01
Responsible Party
Cage: 57868
Name: LIQUID DEVELOPMENT CO INC
Address: 3748 E 91ST STREET
City: CLEVELAND OH 44105
In
fo Phone Number: 216-641-9366
Emergency Phone Number: 216-641-9366/800-424-9300(CHEMTREC)
Proprietary Ind: Y
Review Ind: Y
Published: Y

=====

Contractor Summary

=====

Cage: 57868
Name: LIQUID DEVELOPMENT CO INC
Address: 3748 E 91ST STREET
City: CLEVELAND OH 44105-2156
Phone: 216-641-9366/800-424-9300(CHEMTREC)

=====

Item Description Information

=
=====

Item Manager: S9G
Item Name: PLATING SOLUTION,NI
Specification Number: NONE
Type/Grade/Class: NONE
Unit of Issue: GL
UI Container Qty: 4 L (MSDS)
Type of Container: BOTTLE (MSDS)

=====

Ingredients

=====

Name: *** PROPRIETARY ***

=====

Health Hazards Data

=====

=====

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Route Of Entry Inds - Inhalation: YES

Skin: NO

Ingestion: YES

Carcinogenicity Inds - NTP: YES

IARC: YES

OSHA: YES

Effects of Exposure: ACUTE-INGESTION:MAY CAUSE VOMITING,BURNING IN MOUTH AND MIGHT CAUSE SHOCK.EYES/NOSE/THROAT:IRRITATION.SKIN:NICKEL ITCH OR RASH.CHRONIC-LONG TERM EXPOSURE CAN CAUSE BLISTERING OF SKIN,COUGHING & DIFFICULTY OF BREATHING.

Explanation Of Carcinogenicity: ALL

CONCLUDED THAT NICKEL COMPOUNDS MAY REASONABLY BE ANTICIPATED TO BE CARCINOGENS.

Signs And Symptoms Of Overexposure: WATERING EYES, COUGHING, NASAL IRRITATION, SKIN RASH, BURNING OF MOUTH AND VOMITING

Medical Cond Aggravated By Exposure: CHRONIC RESPIRATORY DISEASE, SKIN DISORDERS, KIDNEY DISEASE, LIVER DISEASE AND EYE DISORDERS

First Aid: INHALATION:REMOVE TO FRESH AIR.IF NOT BREATHING GIVE CPR.GET MEDICAL ATTENTION.EYE:IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR 15 MINUTES.GET

IMMEDIATE MEDICAL ATTENTION.SKIN: IMMEDIATELY WASH WITH PLENTY OF WATER.REMOVE CONTAMINATED CLOTHING. INGESTION:SEEK IMMEDIATE MEDICAL ATTENTION.

=====

Handling and Disposal

=====

Spill Release Procedures: EVACUATE AND VENTILATE AREA.WEAR PROTECTIVE CLOTHING.SMOTHER WITH EXCESS NEUTRALIZING AGENTS.SCOOP INTO CONTAINER FOR PROPER DISPOSAL.DO NOT FLUSH INTO SEWER SYSTEM.

Neutralizing Agent:

SODA ASH

Waste Disposal Methods: SEND TO APPROVED TREATMENT/DISPOSAL FACILITY. DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

Handling And Storage Precautions: STORE BETWEEN 50-75F,OUT OF DIRECT LIGHT,IN A WELL VENTILATED AREA.KEEP CONTAINERS TIGHTLY SEALED.

Other Precautions: DO NOT GET IN EYES, ON SKIN, OR ON CLOTHING.DO NOT BREATHE VAPOR OR MIST.USE WITH ADEQUATE VENTILATION.WASH THOROUGHLY AFTER HANDLING.DO NOT EAT,DRINK OR

SMOKE IN WORK AREA.

=====

Fire and Explosion Hazard Information

=====

Flash Point Text: NONE

Extinguishing Media: WATER, CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & CHEMICAL RESISTANT CLOTHING. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard: CARBON MONOXIDE MAY BE PRODUCED DURING A FIRE.

=====

Control Measures

=====

Respiratory Protection: USE NIOSH/MSHA APPROVED RESPIRATOR AS NECESSARY.

Ventilation: LOCAL EXHAUST VENTILATION IS REQUIRED.

Protective Gloves: RUBBER

Eye Protection: SAFETY CHEMICAL GOGGLES & FACE SHIELD

Other Protective Equipment: EYE WASH STATION & SAFETY SHOWER.CHEMICAL RESISTANT BOOTS, APRON, AND PROTECTIVE CLOTHING AS REQUIRED BY JOB CONDITIONS.

Work Hygienic

Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health: DO NOT GET ON SKIN, IN EYES OR ON CLOTHING. DO NOT BREATHE VAPORS OR MISTS. WASH THOROUGHLY AFTER HANDLING. TRADE SECRET INFORMATION WILL BE DISCLOSED ONLY UPON FULL COMPLIANCE WITH CRITERIA LISTED IN OSHA STANDARD "HAZARD COMMUNICATION", 29 CFR 1910.1200

=====

Physical/Chemical Properties

=====

HCC: C1

B.P. Text: >200F,>93C

M.P/F.P Text: UNKNOWN

Decomp Text: UNKNOWN

Vapor Pres: UNKNOWN

Vapor Density: UNKNOWN

Spec Gravity: 1.25 - 1.35

PH: 0- 1.5

Evaporation Rate & Reference: UNKNOWN

Solubility in Water: COMPLETE

Appearance and Odor: DARK GREEN LIQUID, FORMIC ACID ODOR

Corrosion Rate: UNKNOWN

=====

Reactivity Data

=====

=====

Stability Indicator: YES
Stability Condition To Avoid: NONE
Materials To Avoid: STRONG CAUSTICS, SULFURIC ACID CONCENTRATED
Hazardous Decomposition Products: CARBON MONOXIDE DURING A FIRE.
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: NOT REVELANT

=====

Toxicological Information

=====

Ecological Information

=====

MSDS Transport Information

=====

Regulatory Information

=====

Other Information

=====

Transportation Information

=====

Responsible Party Cage: 57868
Trans ID NO: 114454
Product ID: LDC-2801 NICKEL
MSDS Prepared Date: 01/01/1996
Review Date: 12/20/1996
MFN: 1
Tech Entry NOS Shipping Nm: NICKEL SULFATE
Net Unit Weight: UNKNOWN
Multiple KIT Number: 0
Review IND: Y
Unit Of Issue: GL
Container QTY: 4 L (MSDS)
Type Of Container: BOTTLE (MSDS)
Additional Data: THE MFG. (LYNN HUTCHINSON) HAS STATED THIS ITEM IS SHIPP

ED AS
SHOWN. IF A DIFFERENT LABEL IS USED ON SHIPMENTS SUCH AS "ENVIRONMENTALLY
HAZARD" THE A COMPETITOR HAS USED SUCH A LABEL.

=====

Detail DOT Information

=====

DOT PSN Code: DWE
Symbols: G
DOT Proper Shipping Name: CORROSIVE LIQUIDS, N.O.S.
Hazard Class: 8
UN ID Num: UN1760
DOT Packaging Group: II
Label: CORROSIVE
Special Provision: B2,T14
Packaging Exception: 154
Non Bulk Pack: 202
Bulk
Pack: 242
Max Qty Pass: 1 L
Max Qty Cargo: 30 L
Vessel Stow Req: B
Water/Ship/Other Req: 40

=====

Detail IMO Information

=====

IMO PSN Code: ESH
IMO Proper Shipping Name: CORROSIVE LIQUID, N.O.S. o
IMDG Page Number: 8147
UN Number: 1760
UN Hazard Class: 8
IMO Packaging Group: I/II/III
Subsidiary Risk Label: -
EMS Number: 8-15
MED First Aid Guide NUM: 760

=====

=====

Detail IATA Information

=====

IATA PSN Code: HKR
IATA UN ID Num: 1760
IATA Proper Shipping Name: CORROSIVE LIQUID, N.O.S. *
IATA UN Class: 8
IATA Label: CORROSIVE
UN Packing Group: II
Packing Note Passenger: 808
Max Quant Pass: 1L
Max Quant Cargo: 30L
Packaging Note Cargo: 812

=====

Detail AFI Information

=====

AFI PSN Code: HKR
AFI

Symbols: *
AFI Proper Shipping Name: CORROSIVE LIQUID, N.O.S.
AFI Hazard Class: 8
AFI UN ID NUM: UN1760
AFI Packing Group: II
Special Provisions: P4
Back Pack Reference: A12.3

HAZCOM Label

Product ID: LDC-2801 NICKEL
Cage: 57868
Company Name: LIQUID DEVELOPMENT CO INC
Street: 3748 E 91ST STREET
City: CLEVELAND OH
Zipcode: 44105-2156
Health Emergency Phone: 216-641-9366/800-424-9300(C
HEMTREC)
Label Required IND: Y
Date Of Label Review: 06/12/1996
Status Code: C
MFG Label NO: UNKNOWN
Label Date: 06/12/1996
Origination Code: F
Chronic Hazard IND: Y
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: DANGER
Respiratory Protection IND: YES
Health Hazard: Severe
Contact Hazard: Severe
Fire Hazard: None
Reactivity Hazard: None
Hazard And Precautions: ACUTE-INGESTION:MAY CAUSE VOMITING,BURNING IN MOUTH AND
MIGHT CAUSE SHOCK.EYES/NOSE/THROAT:IRRITATION.SKIN:NICKEL ITCH O
R
RASH.CHRONIC-LONG TERM EXPOSURE CAN CAUSE BLISTERING OF SKIN,COUGHING &
DIFFICULTY OF BREATHING.STORAGE-STORE BETWEEN50-75F,OUT OF DIRECT LIGHT,IN A
WELL VENTILATED AREA.KEEP CONTAINERS TIGHTLY SEALED. FIRST AID-
INHALATION:REMOVE TO FRESH AIR.IF NOT BREATHING GIVE CPR.GET MEDICAL
ATTENTION.EYE:IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR 15 MINUTES. GET
IMMEDIATE MEDICAL ATTENTION.SKIN:IMMEDIATELY WASH WITH PLENTY OF WATER.
REMOVE CONTAMINATED CLOTHING.INGESTION:SEEK IM

MEDIATE MEDICAL ATTENTION.
TARGET ORGANS: SKIN

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor a

ny person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation

.