View NSN Online: https://aerobasegroup.com/nsn/6810-00-222-2751

CSD,INC -- ETHYLENE GLYCOL MONOETHYL ETHER -- 6810-00-222-2751

Product ID: ETHYLENE GLYCOL MONOETHYL ETHER MSDS Date:10/16/1986 FSC:6810 NIIN:00-222-2751 **MSDS Number: BJQNS** === Responsible Party === Company Name:CSD,INC Address:5 HACKBURY ST Box:687 City:CONROE State:TX ZIP:77305 Country:US Info Phone Num:409-756-1065 Emergency Phone Num:409-756-1065 CAGE: JO942 = == Contractor Identification === Company Name: CHEMICAL SPECIALISTS AND DEVELOPMENT INC Address:2210 HACKBERRY LN Box:687 City:CONROE State:TX ZIP:77305 Country:US Phone:409-756-1065 CAGE:4N760 Company Name:CSD,INC Address:5 HACKBURY ST Box:687 City:CONROE State:TX ZIP:77305 Country:US CAGE: JO942 Ingred Name:2-ETHOXYETHANOL (EGEE) (SARA III) CAS:110-80-5 RTECS #:KK8050000

Fraction by Wt: 100% OSHA PEL:S,200 PPM

ACGIH TLV:S, 5

PPM; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:MAY BE HARMFUL IF INHALED, ABSORBED THROUGH SKIN OR SWALLOWED. Explanation of Carcinogenicity:NOT APPLICABLE. Effects of Overexposure:MAY BE HARMFUL IF INHALED,ABSORBED THROUG SKIN OR SWALLOWED. Medical Cond Aggravated by Exp osure:NONE SPECIFIED BY MANUFACTURER.

First Aid:SKIN:WASH WITH SOAP AND WATER. EYES:FLUSH WITH WATER. INGESTED:GIVE 2 GLASSES OF WATER.INDUCE VOMITING.CALL A PHYSICIAN. INHALE:REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF NEED.KEEP WARM AND QUIET.IF UNCON SCIOUS,DO NOT TAKE ANYTHING BY MOUTH.

Flash Point Method:TCC Flash Point:=43.3C, 110.F Lower Limi ts:1.68 Upper Limits:15.6 Extinguishing Media:SMALL FIRE: CO*2, DRY CHEMICAL. LARGE FIRE: WATER SPRAY, WATER FOG OR FOAM. Fire Fighting Procedures:WEAR CHEMICAL PROTECTIVE SUIT WITH SELF CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: ELIMINATE ALL IGNITION SOURCES. SMALL SPILLS MAY BE COLLECTED WITH ABSORBENT MATL. FOR LARGE SPILLS, USE WATER SPRAY TO DILUTE SPILL TO A

NON COMBUSTIBLE MIXTURE.PREVENT RUN-OFF FROM ENTERING DRAINS SEW ERS,OR STREAMS. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: KEEP AWAY FROM HEAT.SPARKS.& OPEN FLAME. CLEAN BEFORE REUSING OR ALTERING PACKAGE. Other Precautions: NONE SPECIFIED BY MANUFACTURER.

Respiratory Protection:NONE NORMALLY NEEDED WITH GOOD VENTILATION. NIOSH/MSHA-APPROVED AIR SUPPLIED RESPIRATOR OR SCBA IF TLV IS EXCEEDED. Ventilation:MECHANICAL(GENERAL) RECOMMENDED,LOCAL EXHAUST IF NEEDED Protective Gloves:IMPERVIOUS Eye Protection:SAFETY GLASSES Other Protective Equipment:IMPERMEABLE APRON OR SMOCK. Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING. Supplemental Safety and Health

MSDS DATED 10-16-86.

HCC:F4 NRC/State Lic Num:NOT RELEVANT Boiling Pt:=133.9C, 273.F Vapor Pres:3.8 Vapor Density:3.1 Spec Gravity:0.93 Evaporation Rate & amp; Reference:0.3,BUAC=1 Solubility in Water:COMPLETE Appearance and Odor:COLORLESS LIQ WITH A MILD AGREEABLE ODOR. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES OXIDIZING MATERIAL: SUCH AS ALUMINUM. Stability Condition to Avoid:NONE Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE.

Waste Disposal Methods: KEEP IN COVERED DRUMS, PENDING DISPOSAL. HANDLE AND DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to b e accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.