

BEESTON -- DAMPING FLUID, SILICONE BASE -- 9150-00-257-5434

=====  
Product Identification  
=====

Product ID:DAMPING FLUID, SILICONE BASE

MSDS Date:06/01/1988

FSC:9150

NIIN:00-257-5434

MSDS Number: BJRCW

=== Responsible Party ===

Company Name:BEESTON

Address:540 DEERING AV

Box:1116

City:SCARBOROUGH

State:ME

ZIP:04074

Country:US

Info Phone Num:207-883-5541

Emergency Phone Num:800-424-9300 (CHEMTREC)

CAGE:43728

=== Contractor Identification ===

Company Name:BEESTON

Address:540 DEERING AV

Box:1116

City:SCARBOROUGH

State:ME

ZIP:04074

Country:US

Phone:207-883-5541

CAGE:43728

Company Name:BOLT INC

Box:1208

City:SCARBOROUGH

State:ME

ZIP:04074

Country:US

Phone:207-883-5541,CHEMTREC 800-424-9300

CAGE:0DR30

=====  
Composition/Information on Ingredients  
=====

Ingred Name:"NOT HAZARDOUS"

Fraction by Wt: 100%

Other REC Limits:NONE ESTABLISHED

=====  
Hazards Identific

ation =====

LD50 LC50 Mixture:LD50 > 5G/KG (RAT)

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:LOW HAZARD, SLIGHTLY IRRITATING AT MOST.

Effects of Overexposure:SEE "HEALTH HAZARDS"

Medical Cond Aggravated by Exposure:NONE STATED.

===== First Aid Measures =====

First Aid:HUMAN EXPERIENCE WITH SILICONE FLUIDS HAS NOT INDICATED ANY SERIOUS

EFFECTS RELATED TO EXPOSURE BY ANY ROUTE. DIRECT EYE

CONTACT CAN CAUSE A TRANSITORY IRRITATION BUT IS NOT INJURIOUS.

THIS IRRITATION MAY PERSIST FOR UP TO 24 HOURS.

===== Fire Fighting Measures =====

Flash Point Method:OC

Flash Point:>275F/135C

Extinguishing Media:DRY CHEMICAL, WATER SPRAY, FOAM, CARBON DIOXIDE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:UNDER FIRE CONDITIONS IRRITATING AND/OR T

OXIC VAPORS OR GASES MAY BE PRESENT.

===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP MATERIAL. RESUDUE IS SLIPPERY. APPLY SAWDUST OR SWEEPING COMPOUND TO AREA OF SPILL TO MINIMIZE SLIP.

===== Handling and Storage =====

Handling and Storage Precautions:NO SPECIAL PRECAUTIONS.

Other Precautions:NONE STATED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE

USUALLY.  
Ventilation:NORMAL VENTILATION.  
Protective Gloves:NONE USUALLY  
Eye Protection:SAFETY GLASSES  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6  
Boiling Pt:B.P. Text:>572F/300C  
Melt/Freeze Pt:M.P/F.P Text:< -40F/-40C  
Vapor Density:> 1  
Spec Gravity:0.9 - 0.97  
Solubility in Water:INSOLUBLE  
Appearance and Odor:CLEAR, COLORLESS, ODORLESS LIQUID.

===== Stability and Reactivity Data =====

Stability Indicator  
/Materials to Avoid:YES  
NONE STATED.  
Stability Condition to Avoid:NONE STATED.  
Hazardous Decomposition Products:MAY PRODUCE CARBON MONOXIDE, CARBON DIOXIDE AND OXIDES OF SILICON.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATION OR LANDFILL IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL ENVIRONMENTAL CONTROL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.