View NSN Online: https://aerobasegroup.jp/nsn/9150-00-482-6884

DOW CORNING CORPORATION -- 3451 CHEM RESIST BEARING GREASE -- 9150-00-482-6884

============= Product Identification ==============

Product ID:3451 CHEM RESIST BEARING GREASE

MSDS Date:04/24/1990

FSC:9150

NIIN:00-482-6884

MSDS Number: BJVZQ === Responsible Party ===

Company Name: DOW CORNING CORPORATION

Address:3901 SOUTH SAGINAW ROAD

City:MIDLAND

State:MI

ZIP:48686-5601

Country:US

Info Phone Num:517-496-6000

Emerge

ncy Phone Num:517-496-5900

Preparer's Name: JACK L. SHENEBERGER

CAGE:5D028

=== Contractor Identification ===

Company Name: DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name: MCKEOWN ROBERT CO. INC.

Address:111 CHAMBERS BROOK RD.

Box:City:SOMERVILLE

State:NJ ZIP:08876 Country:US

Phone:908-218-9000

CAGE:7B953

====== Composition/Information on Ingredients ========

Ingred Name:ETHYLE

| NE, TETRAFLUORO- POLYMER (POLYTETRAFLUOROETHYLENE), PTFE, TEFLON CAS:116-14-3 RTECS #:KX4025000 Fraction by Wt: 38% |
|--|
| Ingred Name:FLUOROSILICONE OIL CAS:63148-56-1 Other REC Limits:NONE RECOMMENDED OSHA PEL:NOT ESTABLISHED. ACGIH TLV:NOT ESTABLISHED. |
| ========== Hazards Identification ============ |
| Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES: TEMPORARY DISCOMFORT. ING ESTION |
| OF LARGE AMOUNTS: DIGESTIVE DISCOMFORT. Explanation of Carcinogenicity:NONE |
| Effects of Overexposure:EYES: MILD REDNESS & DRYNESS SIMILAR TO WINDBURN. |
| Medical Cond Aggravated by Exposure:MAY ENHANCE ALLERGIC CONDITIONS. |
| ====================================== |
| First Aid:EYES: FLUSH W/WATER. SKIN: WIPE OFF & FLUSH W/WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES. |
| ====================================== |
| Flash Point Method: CC Flash Point:200F/93C Extinguishing Media:WATER FOG, CO2, DRY CHEMICAL, FOAM Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS & FULL PROTECTIVE CLOTHING. Unusual Fire/Explosion Hazard:HAZARDOUS FLUORINE GASES MAY FORM. |
| ======== Accidental Release Measures ========= |
| Spill Release Procedures:REMOVE PRODUCT & USE ABSORBENT MATERIAL TO TAKE CARE OF ANY OIL-LIKE RESIDUES. |
| ========== Handling and Storage ============ |
| Handling a |

nd Storage Precautions:USE REASONABLE CARE & CAUTION. AVOID TEMPERATURES >300F. USE W/ADEQUATE VENTILATION. AVOID UNNECESSARY EXPOSURE & CONTACT W/SKIN.

====== Exposure Controls/Personal Protection ========

Ventilation:MECHANICAL (GENERAL): RECOMMENDED.

Eye Protection: SAFETY GLASSES

Work Hygienic Practices: WASHING AT MEALTIME & END OF SHIFT IS ADEQUATE.

Supplemental Safety and Health

======== Physical/Chemical Properties ==========

HCC:V6 NRC/State L ic Num:NOT RELEVANT Vapor Pres: