

STANDARD OIL CO OF OHIO -- X-232,HYDRAULIC OIL -- 9150-00-162-8385

===== Product Identification =====

Product ID:X-232,HYDRAULIC OIL

MSDS Date:04/01/1986

FSC:9150

NIIN:00-162-8385

MSDS Number: BKBVY

=== Responsible Party ===

Company Name:STANDARD OIL CO OF OHIO

Address:200 PUBLIC SQ

City:CLEVELAND

State:OH

ZIP:44114-2375

Country:US

Info Phone Num:800-321-8642/216-586-8024

Emergency Phone Num:800-3

21-8642/800-362-8059(OHIO)

Preparer's Name:R. K. RIGNEY

CAGE:82250

=== Contractor Identification ===

Company Name:BP OIL COMPANY

Address:200 PUBLIC SQ

Box:City:CLEVELAND

State:OH

ZIP:44114-2375

Country:US

Phone:216-586-8023

CAGE:82250

Company Name:HYDRONIC CORP (313-477-2288)

CAGE:12017

===== Composition/Information on Ingredients =====

Ingred Name:KEROSENE (ALIPHATIC PETROLEUM SOLVENT)

CAS:8008-20-6

RTECS #:OA5500000

Fraction by Wt: 80-90%

Other REC Limits:NONE SPECIFIED

In

gred Name:PETROLEUM OIL (DISTILLATE (PETROLEUM) SOLVENT REFINED LIGHT
PARAFFINIC)
CAS:64741-89-5
RTECS #:PY8041500
Fraction by Wt: 10-20%
Other REC Limits:NONE SPECIFIED

Ingred Name:MIXTURE OF PETROLEUM HYDROCARBON AND SELECTED ADDITIVES
(SUCH AS ANTIFOAM,ANTIRUST,DEMULSIFYING AGENT)
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSH
A:NO

Health Hazards Acute and Chronic:ACUTE: MAY CAUSE IRRITATION TO SKIN,
EYES, AND RESPIRATORY TRACT. INGESTION: MAY LEAD TO VOMITING,
NAUSEA, HEADACHE, DIARRHEA. CHRONIC: REPEATED AND PROLONGED SKIN
CONTACT MAY CAUSE DERMATITIS.

Explanation of Carcinogenicity:THE COMPONENTS OF THIS PRODUCT HAVE NOT
SHOWN ANY EVIDENCE OF BEING CARCINOGENIC.

Effects of Overexposure:INHALATION:OVEREXPOSURE MAY LEAD TO RESPIRATORY
IRRITATION. INGESTION:MAY CAUSE NAUSEA,VOMITING,AND DIARRHEA AN

D

POSSIBLY UNCONSCIOUSNESS. EYES:CAUSES MILD IRRITATION.VAPORS MAY
CAUSE TEARS/IRRITATION . SKIN:COMPONENTS ARE UNLIKELY TO BE
ABSORBED THROUGH SKIN IN HARMFUL CONCENTRATION BUT MAY CAUSE
IRRITATION.

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN
DISORDER SHOULD USE CAUTION WHEN HANDLING OR USING THIS PRODUCT.

===== First Aid Measures =====

First Aid:SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER.
G

ET MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION: REMOVE TO
FRESH AIR & RESTORE BREATHING IF NECESSARY. GET MEDICAL ATTENTION.
EYE : IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING
EYELIDS OPEN. GET MEDICAL ATTENTION. INGESTION: GET IMMEDIATE
MEDICAL ATTENTION. DO NOT INDUCE VOMITING. NOTHING BY MOUTH IF
UNCONSCIOUS.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:140F,60C
Lower Limits:0.7
Upper Limits

:5.0

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL
FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS.RUNOFF TO SEWER MAY CAUSE FIRE OR
EXPLOSION HAZARD.CONTAINERS MAY EXPLODE IN HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES.USE PROTECTIVE GEARS.
SMALL SPILL:ABSORB WITH RAGS,CLAY AND PLACE IN CLOSED DOT DRUMS.
LARGE SPILL:CONTAIN BY DIKING WITH CLAY,VERMICULITE,OR SIMILAR
ABSORBENT MATERIAL.PUMP LI Q TO SALVAGE TANK.PLACE ABSORBED WASTE
IN DOT DRUM

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, VENTILATED WORK AREA.
KEEP CONTAINERS CLOSED WHEN
NOT IN USE.AVOID PHYSICAL DAMAGE TO
CONTAINERS.AVOID SKIN AND CLOTHING CONTACT.

Other Precautions:THE SELECTION OF PERSONAL PROTECTIVE EQUIPMENT SHOULD
BE MADE BY THE MATERIAL USER BASED ON THE PARTICULAR CONDITIONS
WHERE THE MATERIAL IS TO BE USED TOGETHER WITH INFORMATION
CONTAINED IN THIS MSDS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IN CONFINED SPACES OR
WHEN NEEDED, USE NIOSH APPROVED RESPIRATOR. AIR-SUPPLIED OR
FILTERING TYPE WITH ORGANIC VAPOR CARTRIDGES ARE RECOMMENDED.

Ventilation:LOCAL AND MECHANICAL EXHAUST RECOMMENDED.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GOGGLES/GLASSES.

Other Protective Equipment:EYE WASH STATION & SAFETY SHOWER.

Work Hygienic Practices:DO NOT TAKE INTERNALLY. AVOID SKIN CONTACT.
WASH SKIN AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORK
AREA.

Supplemental Safety and Health

NON-SPECIFICATION ITEM.PER DLSC-TIR,ITEM IS SOLE SOURCE

CE UNDER

P/N:ENERGOL HLP-2,CAGE 8225(SOHIO); AND P/N:X-232,CAGE
12017,(HYDRONIC CORP). DURING 80'S HYDRONIC CORP SUPPLIED THE ITEM
BUT FURNISHED MS DS OF SOHIO'S PRODUCT ENERGOL HLP-2. THIS ENTRY IS
ACTUALLY OF ENERGO HLP-2 FOR X-232 UNDER HYDRONIC CORP.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:>310.C, 590.F

Vapor Pres:0.5MMHG

Vapor Density:>1 AIR=1

Spec Gravity:0.825

Viscosity:1.8-2.7 CST

Evaporation Rate & Reference: