

SEYMOUR OF SYCAMORE, INC -- CLEAR -- 8010-00-515-2487

===== Product Identification =====

Product ID: CLEAR
MSDS Date: 05/18/1990
FSC: 8010
NIIN: 00-515-2487
MSDS Number: BKHNY
=== Responsible Party ===
Company Name: SEYMOUR OF SYCAMORE, INC
Address: 917 CROSBY AVE
City: SYCAMORE
State: IL
ZIP: 60178
Info Phone Num: (815) 895-9101
Emergency Phone Num: (815) 895-9101
CAGE: 59581
=== Contractor Identification ==
=
Company Name: SEYMOUR OF SYCAMORE
Address: 917 CROSBY AVE.
Box: City: SYCAMORE
State: IL
ZIP: 60178-1343
Country: US
Phone: 815-895-9101/800-255-3924
CAGE: 59581

===== Composition/Information on Ingredients =====

Ingred Name: ETHYL BENZENE (SARA III)
CAS: 100-41-4
RTECS #: DA0700000
Fraction by Wt: 0.55%
Other REC Limits: 100 PPM
OSHA PEL: 100 PPM/125 STEL
ACGIH TLV: 100 PPM/125 STEL 9192
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Ingred Name: HYDROTREATED LIGHT DISTILLATE, PETROLEUM; C12-

C15
ISOPARAFFINIC HYDROCARBONS
CAS:64742-47-8
Fraction by Wt: 0.24%
Other REC Limits:300 PPM (MFR)
OSHA PEL:500 PPM
ACGIH TLV:100 PPM

Ingred Name:DIBUTYL PHTHALATE (SARA III)
CAS:84-74-2
RTECS #:TI0875000
Fraction by Wt: 0.67%
Other REC Limits:5 MG/CUM
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3; 9192
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:METHYLENE CHLORIDE (SARA III)
CAS:75-09-2
RTECS #:PA8050000
Fraction by Wt: 18.43%
OSHA PEL:500 PPM/C,1000; Z2
ACGIH TLV:50 PPM, A2; 9192
EPA Rpt Qty
:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 34.37%
Other REC Limits:100 PPM
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 4.50%
Other REC Limits:50 PPM
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:VM&P NAPHTHA (LIGROINE)
CAS:80

32-32-4
RTECS #:OI6180000
Fraction by Wt: 0.20%
Other REC Limits:STEL 400 PPM
OSHA PEL:300 PPM/400 STEL
ACGIH TLV:300 PPM; 9192

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 0.94%
Other REC Limits:100 PPM
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:2-BUTOXYETHANOL
CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: 0.12%
Other REC Limits:25 PPM (SKIN)
OSHA PEL:S, 50 PPM
ACGIH TLV:S
, 25 PPM; 9293

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 18%
Other REC Limits:1800 MG/CUM
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9192

Ingred Name:ISOBUTANE, 2-METHYLPROPANE
CAS:75-28-5
RTECS #:TZ4300000
Fraction by Wt: 12%
Other REC Limits:1000 PPM
OSHA PEL:1800 MG/CUM
ACGIH TLV:1000 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:INHALATION: RESPIRATORY SYSTEM/UPPER RESPIRATORY TRACT IRRITATION, HEADACHE, DIZZINESS, NAUSEA, UNCONSCIOUSNESS, ASPHYXIATION, WEAKNESS, NOSE/THROAT IRRITATION, NARCOSIS, HARMFUL. EYE: IRRITATION. SKIN: DEFATTING, IRRITATION, & DERMATITIS.INGESTION: GASTROINTESTINAL SYMPTOMS.

Explanation of Carcinogenicity:METHYLENE CHLORIDE IS A CONSIDERED TO BE AN A2 CARCINOGEN.

Effects of Overexposure:INHALATION: CARBOXYHEMOGLOBINEMIA, BLOOD IMPAIRMENT

TO TRANSPORT OXYGEN, CENTRAL NERVOUS SYSTEM, LIVER, OR KIDNEY EFFECTS, PERMANENT BRAIN, NERVOUS SYSTEM DAMAGE, CENTRAL NERVOUS SYSTEM DEPRESSION, HEMOLYSIS, & DEATH. EYE: IRRITATION. SKIN: DEFATTING, IRRITATION, & DERMATITIS. INGESTION: GASTROINTESTINAL SYMPTOMS.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. GIVE CPR OR OXYGEN IF NEEDED. EYE: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. SKIN: WASH W/S

W/ SOAP & WATER. INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point Method:TOC

Flash Point:-10F

Lower Limits:1.27%

Extinguishing Media:USE CO2, DRY CHEMICAL OR FOAM.

Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. WEAR SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:WATER MAY BE USED TO COOL CONTAINERS EXPOSED TO HEAT OR PROLONG EXPOSURE FROM THE SUN TO PREVENT BURSTING.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA. WIPE UP W/INERT MATERIALS & PLACE IN APPROPRIATE CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:DON'T STORE >120F. EXPOSURE TO HEAT OR PROLONG EXPOSURE TO SUN MAY CAUSE BURSTING. USE ONLY AS DIRECTED. USE W/ADEQUATE VENTILATION.

Other

r Precautions:AVOID BREATHING OF VAPORS OR SPRAY MIST, & CONTACT W/EYES. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING VAPORS/INHALING CONTENTS CAN BE HARMFUL OR FATAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A SELF CONTAINED BREATHING APPARATUS FOR CONCENTRATIONS >TLV.

Ventilation:PROVIDE SUFFICIENT VENTILATION TO PREVENT INHALATION OF SOLVENT VAPORS.

Protective Gloves:AS REQUIRED

Eye Protection:AS REQUIRED

Supplementa

I Safety and Health

===== Physical/Chemical Properties =====

Vapor Pres:40 PSIA

Vapor Density:>AIR

Evaporation Rate & Reference:FASTER THAN ETHER

Appearance and Odor:AEROSOL CONTAINER.

Percent Volatiles by Volume:85%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS & STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:HEAT, SPARKS, PILOT LIGHTS, OPEN FLAME, SOURCES OF IGNITION, &

TEMPS >120F.

Hazardous Decomposition Products:CO₂, CO, HYDROGEN CHLORIDE VAPOR & TRACES OF PHOSGENE.

===== Disposal Considerations =====

Waste Disposal Methods:DON'T INCINERATE AEROSOL CONTAINERS. DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS. DON'T PLACE AEROSOL CANS IN HOME COMPACTOR. DON'T PUNCTURE. DOT: CONSUMER COMMODITY ORMD.

Disclaimer (provided with this information by the compiling agencies):

This information is formu

lated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.