View NSN Online: https://aerobasegroup.jp/nsn/6750-01-206-3612

Product ID:814 9569 KODAK ULTRATEC DEVELOPER & REPLENISHER 5 GALLONS MSDS Date:01/04/1990 FSC:6750 NIIN:01-206-3612 MSDS Number: BKHYT === Responsible Party === Company Name: EASTMAN KODAK CO Address:343 STATE ST **City:ROCHESTER** State:NY ZIP:14650-1115 Country:US Info Phone Num:716-724-6481/716-722-5151 Emergency Phone Num:716-722-5151/716-724-4501 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139

======= Composition/Information on Ingredients ==========

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 80-85%

Ingred Name: POTASSIUM PHOSPHATE TRIBASIC, TRIPOTA

SSIUM PHOSPHATE CAS:7778-53-2 RTECS #:TC8450000 Fraction by Wt: 5-10%

Ingred Name:SODIUM SULFITE CAS:7757-83-7 RTECS #:WE2150000 Fraction by Wt: 5-10% Other REC Limits:5 MG/CUM (DUST)

Ingred Name:HYDROQUINONE; 1,4-DIHYDROXYBENZENE; 1,4-BENZENEDIOL CAS:123-31-9 RTECS #:MX3500000 Fraction by Wt: 3% OSHA PEL:2 MG/CUM ACGIH TLV:2 MG/CUM EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:SODIUM HYDROXIDE, CAUSTIC SODA, LYE *98-2* CAS:1310-73-2 RTECS #:WB4900000 Fraction by Wt: 1-5% Other REC Limits:2 MG/M3 CEILING NIOSH OSHA PEL:2 MG/CUM ACGIH TLV:2 MG/CUM CEILING EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES: MAY CAUSE BURNS. SKIN: PROLONGED/REPEATED CONTACT MAY CAUSE IRRITATION. ALLERGIC REACTION. LOW HAZARD FOR INHALATION/INGESTION. Explanation of Carcinogenicity:NONE Effec

ts of Overexposure:BURNS, IRRITATION	ts
--------------------------------------	----

	First Aid Measures	
--	--------------------	--

First Aid:EYES: FLUSH W/PLENTY OF WATER FOR 15 MINS. SKIN: FLUSH W/PLENTY OF WATER & WASH W/A NON-ALKALINE (ACID) TYPE OF CLEANSER. INGESTION: DRINK 1-2 GLASSES OF WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Flash Point:NONE Extinguishing Media:USE APPROPRIATE AGENT FOR SURROUNDING FIRE. Fire Fighting Proc edures:WEAR A SELF-CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHING. Unusual Fire/Explosion Hazard:FIRE/EXCESSIVE HEAT MAY CAUSE PRODUCTION

OF HAZARDOUS DECOMPOSITION PRODUCTS.

Spill Release Procedures:NEUTRALIZE W/SODIUM BISULFATE. FLUSH MATERIAL TO AN ACID-FREE SEWER W/PLENTY OF WATER. Neutralizing Agent:SODIUM BISULFATE

Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED & AWAY FROM ACIDS.

======= Exposure Controls/Personal Protection ==========

Ventilation:GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT. Protective Gloves:IMPERVIOUS Eye Protection:SAFETY GLASSES W/SIDE SHIELDS, GOGGLES Work Hygienic Practices:KEEP AREAS CLEAN & ROUTINELY USE A NON-ALKALINE (ACID) TYPE SKIN CLEANER. Supplemental Safety and Health

Boiling Pt:B.P. Te

xt:>212F Vapor Pres:18 Vapor Density:0.6 Spec Gravity:1.162 pH:11.37 Evaporation Rate & amp; Reference:(N-BU AC =1): 0.4 Solubility in Water:COMPLETE Appearance and Odor:CLEAR, SLIGHTLY YELLOW SOLUTION W/SLIGHT ODOR. Percent Volatiles by Volume:90/WT

Stability Indicator/Materials to Avoid:YES STRONG ACIDS Stability Condition to Avoid:FIRE/EXCESSIVE HEAT Hazardous Decomposition Products:OXIDES OF SULFUR & PHOSPHOROUS.

Waste Disposal Methods:DISCHARGE, TREAT/DISPOSAL SHOULD BE IAW/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizin g this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.