View NSN Online: https://aerobasegroup.jp/nsn/7930-01-183-9562

Product ID: FINISH FLOOR NONBUFFING QPL-24685 DECK FINI MSDS Date:04/20/1990 FSC:7930 NIIN:01-183-9562 **MSDS Number: BLJNM** === Responsible Party === Company Name: HILLYARD CHEMICAL CO Address:302 NORTH FOURTH ST City:ST JOSEPH State:MO ZIP:64502 Country:US Info Phone Num:816-233-1321 Emergency Phone Num:816-233-1321 CAGE:DO351 === Contractor Identification === Company Name: HILLYARD CHEMICAL CO Address:302 NORTH FOURTH STREET City:ST. JOSEPH State:MO ZIP:64502 Phone:816-233-1321 CAGE:DO351 Company Name: HILLYARD INDUSTRIES Address:302 NORTH FOURTH STREET Box:City:ST JOSEPH State:MO ZIP:64501 Country:US Phone:816-233-1321 (EXT 2303) CAGE:28745

Ingred Name:NON HAZARDOUS INGREDIENT

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE:CONTACT MAY CAUSE MILD EYE IRRITATION. CHRONIC:NONE KNOWN. Explanation of Carcinogenicity:NOT RELEVANT. Effects of Overexposure:NONE KNOWN. Medical Cond Aggravated by Exposure:NONE KNOWN.

====

First Aid:EYE:FLUSH W/WATER FOR AT LEAST 15 MINS. IF WEARING CONTACT LENSES, REMOVE & FLUSH AGAIN W/PLENTY OF WATER. IF IRRITATION PERSISTS, GET MD. SKIN:FLUSH W/COPIOUS AMOUNTS OF WATER . INHAL:REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE OXYGEN/ARTIFICIAL RESPIRATION) . INGEST:CALL MD IMMEDIATELY .

Flash Point Method:TCC

Flash Point:NONE

Extinguishing Media:MEDIA SUITABLE FOR SURROUNDING FIRE CONDITIO NS .

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:MATERIAL MAY SPATTER IF TEMPERATURES EXCEED BOILING POINT. POLYMER FILM CAN BURN.

Spill Release Procedures: PICK UP W/MOP OR WET VAC & WASH AWAY W/WATER. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precaut

ions:PRODUCT SHELF LIFE IS BEST RETAINED BY

STORAGE AT 45-100F TEMPERTURES. FREEZING OF PRODUCT MAY RUPTURE CONTAINER.

Other Precautions: INHALATION EXPOSURE TO SPRAY MIST SHOULD BE MAINTAINED AT LESS THAN 10 MG/M3 PER EIGHT HOUR EXPOSURE (TWA LIMIT EST. FOR NUISANCE DUST).

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE REQUIRED. Ventilation:MECHANICAL GENERAL SUGGESTED. Protective Gloves:NONE REQUIRED. Eye Protection:CHEMICAL WOR KERS GOGGLES .
Other Protective Equipment:NONE REQUIRED.
Work Hygienic Practices:DO NOT TAKE INTERNALLY. WASH CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health
SPEC GRAV:1.014 @ 102 F; 1.026 @ 68 F

HCC:N1 Boiling Pt:B.P. Text:210F,99C Spec Gravity:SEE SUPP DATA Evaporation Rate & amp; Reference: