

COURTAULDS AEROSPACE INC -- PR-1440, PART A -- 8030-00-753-5009

=====  
Product Identification  
=====

Product ID:PR-1440, PART A

MSDS Date:12/06/1989

FSC:8030

NIIN:00-753-5009

MSDS Number: BLLVY

=== Responsible Party ===

Company Name:COURTAULDS AEROSPACE INC

Address:757 CALIFORNIA ST

Box:1800

City:GLENDALE

State:CA

ZIP:91203

Country:US

Info Phone Num:818-549-7973

Emergency Phone Num:818-549-7973

Pre

parer's Name:AS

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

=====  
Composition/Information on Ingredients  
=====

Ingred Name:MANGANESE DIOXIDE (EXPOS LIM BASED ON AIRBORNE PARTICLES.  
IN THIS PRODUCT MAT'L IS FULLY ENCAPSULATED-NO AIRBORNE PART)

CAS:1313-13-9

RTECS #:OP0350000

Fraction by Wt: 60%

Other REC Limits:NONE SPECIFIED  
OSHA PEL:5 MG/M3 STEL CEILING  
ACGIH TLV:5 MG/M3

Ingred Name:1,3 DIPHENYL GUANIDINE (DPG)  
CAS:102-06-7  
RTECS #:MF0875000  
Fraction by Wt: < 5%  
Other REC Limits:NONE SPECIFIED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYES/SKIN: IRRITATION. INHALATION:  
ALTHOUGH THE MAIN HAZARD OF MANGANESE COM  
POUNDS IS BY BREATHING  
DUST, INGESTION SHOULD BE AVOIDED AS A PRECAUTION AGAINST MANGANESE  
POISONING. SYMPTOMS OF MANGANESE POISONING ARE WEAKNESS AND  
SLEEPINESS.

=====  
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LUKEWARM WATER FOR 15 MINUTES. IF SYMPTOMS  
PERSIST, CONSULT PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. IF  
SYMPTOMS PERSIST, CONSULT A PHYSICIAN. INHALATION: REMOVE TO FRESH  
AIR. IF SYMPTOMS ARE PRESENT, CONSULT A  
PHYSICIAN. INGESTION:  
CONSULT A PHYSICIAN.

=====  
===== Fire Fighting Measures =====

Flash Point:NONE  
Lower Limits:NA  
Upper Limits:NA  
Extinguishing Media:CO2, DRY CHEMICAL, FOAM, WATER.  
Fire Fighting Procedures:USE AIR SUPPLIED RESPIRATOR. USE WATER TO COOL  
HEAT EXPOSED CONTAINERS.  
Unusual Fire/Explosion Hazard:EXCESSIVE HEAT MAY CAUSE DECOMPOSITION OF  
MANGANESE DIOXIDE, RESULTING IN OXIDIZATION AND POSSIBLE IGNITION  
OF HYDROCARBON VEHICLE.

=====

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP INTO CONTAINERS. CLEAN-UP RESIDUE WITH 1,1,1-TRICHLOROETHANE.

===== Exposure Controls/Personal Protection =====

Ventilation:GENERAL VENTILATION

Protective Gloves:SOLVENT RESISTANT GLOVES

Eye Protection:SAFETY GLASSES

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE SMOKING OR EATING. AVOID INGESTION.

Supplemental Safety and Health

KEY1:N1. THIS PRODUCT CONTAINS

A TOXIC CHEMICAL OR CHEMICALS SUBJECT TO

THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PA RT 372 (SARA 313).

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:NA

Vapor Pres:NA

Vapor Density:NA

Spec Gravity:1.95

Evaporation Rate & Reference:UNK

Solubility in Water:NEGLIGIBLE

===== Stability and Reactivity Data =====

Stability

Indicator/Materials to Avoid:YES

EASILY OXIDIZABLE MATERIALS.

Hazardous Decomposition Products:OXIDES OF CARBON AND NITROGEN, MANGANESE COMPOUNDS.

===== Disposal Considerations =====

Waste Disposal Methods:NOT A HAZARDOUS WASTE ACCORDING TO EPA REGULATIONS. CONSULT STATE REGULATIONS PRIOR TO DISPOSAL OF SPILLAGE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Departm

ent  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.